

Produktinformation



Forschungsprodukte & Biochemikalien



Zellkultur & Verbrauchsmaterial



Diagnostik & molekulare Diagnostik



Laborgeräte & Service

Weitere Information auf den folgenden Seiten! See the following pages for more information!



Lieferung & Zahlungsart

siehe unsere Liefer- und Versandbedingungen

Zuschläge

- Mindermengenzuschlag
- Trockeneiszuschlag
- Gefahrgutzuschlag
- Expressversand

SZABO-SCANDIC HandelsgmbH

Quellenstraße 110, A-1100 Wien

T. +43(0)1 489 3961-0

F. +43(0)1 489 3961-7

mail@szabo-scandic.com

www.szabo-scandic.com

linkedin.com/company/szaboscandic in



3-Amino-1,2,4-triazole

sc-202016

Material Safety Data Sheet



The Power to Question

Hazard Alert Code Key:

EXTREME

HIGH

MODERATE

LOW

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

3-Amino-1,2,4-triazole

STATEMENT OF HAZARDOUS NATURE

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

HEALTH AZARD INSTALLITY

SUPPLIER

Santa Cruz Biotechnology, Inc. 2145 Delaware Avenue Santa Cruz, California 95060 800.457.3801 or 831.457.3800

EMERGENCY: ChemWatch


Within the US & Canada: 877-715-9305 Outside the US & Canada: +800 2436 2255 (1-800-CHEMCALL) or call +613 9573 3112

SYNONYMS

C2-H4-N4, Amitrol, Aminotriazol, Amizol, Azaplant, Azolan, Amerol, aminotriazole, 2-aminotriazole, 3-aminotriazole, 3-amino-s-triazole, AT, Azole, "2-amino-1, 3, 4-triazole", "3-amino-1H-1, 2, 4-triazole", "1H-1, 2, 4-triazol-3-amine", "amino triazole plant regulator", "Weedkiller 90", Amitol, Amitril, "Solution concentrate T271", "Campaprim A 1544", Cytrol, Cytrole, Diurol, Domatol, Elmasil, Elmisol, "Ent 25445", Fenamine, Fenavar, "Herbidal total", Herbizole, Kleer-lot, Orga-414, Ramizol, Simazol, Triazolamine, Vorox, "Weedar ads", Weedazol, "Weedazol, "Weedazole T", Weedoclor, "X-all liquid"

Section 2 - HAZARDS IDENTIFICATION

CHEMWATCH HAZARD RATINGS







CANADIAN WHMIS SYMBOLS



EMERGENCY OVERVIEW

RISK

Harmful if swallowed.

May cause CANCER.

Possible risk of harm to the unborn child.

Harmful: danger of serious damage to health by prolonged exposure if swallowed.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

■ Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.

EYE

■ Although the material is not thought to be an irritant, direct contact with the eye may cause transient discomfort characterized by tearing or conjunctival redness (as with windburn). Slight abrasive damage may also result.

CKIN

- The material is not thought to be a skin irritant (as classified using animal models). Abrasive damage however, may result from prolonged exposures.
- Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.
- Open cuts, abraded or irritated skin should not be exposed to this material.
- Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

INHALED

- The material is not thought to produce either adverse health effects or irritation of the respiratory tract following inhalation (as classified using animal models). Nevertheless, adverse effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting
- Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.

CHRONIC HEALTH EFFECTS

■ Harmful: danger of serious damage to health by prolonged exposure if swallowed.

Harmful: danger of serious damage to health by prolonged exposure if swallowed.

This material can cause serious damage if one is exposed to it for long periods. It can be assumed that it contains a substance which can produce severe defects

Results in experiments suggest that this material may cause disorders in the development of the embryo or fetus, even when no signs of poisoning show in the mother.

Long term exposure to high dust concentrations may cause changes in lung function i.e. pneumoconiosis; caused by particles less than 0.5 micron penetrating and remaining in the lung.

A statistically significant increase in the incidence of total tumours and lung tumours was found among workers exposed to amitrole and combinations of other herbicides. In a follow-up study results did not show a statistically significant increase in cancer incidence in workers exposed to amitrole alone but did show a significant increase in tumours in workers exposed to amitrole and phenoxy acids together.

Animal testing at high doses has produced goiter and thyroid tumors. Rats fed on diets containing 50 ppm for 2-years had enlarged thyroids and those receiving 100 ppm developed hyperplasias and malignant tumours of the thyroid.

Amitrole also has an antitumorigenic effect. It reduces the number of liver tumours in rats induced by 4-dimethylaminobenzene. High doses of amitrole also delayed the occurrence of virus-induced mammary tumours, decreased the number of X-ray induced lymphomas and decreased the number of neutron radiation-induced tumours of the Harderian gland and ovaries in mice.

Exposure may aggravate existing hypothyroidism or myxdema. [CCINFO 23648]

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
3-amino-1.2.4-triazole	61-82-5	>98

Section 4 - FIRST AID MEASURES

SWALLOWED

· IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY. · Where Medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed otherwise:

EYE

■ If this product comes in contact with the eyes: · Wash out immediately with fresh running water. · Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.

SKIN

■ If skin contact occurs: · Immediately remove all contaminated clothing, including footwear · Flush skin and hair with running water (and soap if available).

INHALED

 \cdot If dust is inhaled, remove from contaminated area. \cdot Encourage patient to blow nose to ensure clear passage of breathing. \cdot If irritation or discomfort persists seek medical attention.

NOTES TO PHYSICIAN

■ for poisons (where specific treatment regime is absent):

-----BASIC TREATMENT

- · Establish a patent airway with suction where necessary.
- · Watch for signs of respiratory insufficiency and assist ventilation as necessary.

Treat symptomatically.

Amitrole (3-amino-1,2,4-triazole) is rapidly absorbed and excreted from the body. Up to 50% of the portion absorbed is eliminated, unchanged in the urine within a few hours. [NIOSHTIC]

Section 5 - FIRE FIGHTING MEASURES			
Vapour Pressure (mmHG):	Not applicable		
Upper Explosive Limit (%):	Not applicable.		
Specific Gravity (water=1):	Not available.		
Lower Explosive Limit (%):	Not applicable.		

EXTINGUISHING MEDIA

- · Water spray or fog.
- · Foam.

FIRE FIGHTING

- · Alert Emergency Responders and tell them location and nature of hazard.
- · Wear breathing apparatus plus protective gloves for fire only.

When any large container (including road and rail tankers) is involved in a fire,

consider evacuation by 100 metres in all directions.

GENERAL FIRE HAZARDS/HAZARDOUS COMBUSTIBLE PRODUCTS

- · Solid which exhibits difficult combustion or is difficult to ignite.
- · Avoid generating dust, particularly clouds of dust in a confined or unventilated space as dusts may form an explosive mixture with air, and any source of ignition, i.e. flame or spark, will cause fire or explosion. Dust clouds generated by the fine grinding of the solid are a particular hazard; accumulations of fine dust may burn rapidly and fiercely if ignited.

Combustion products include: carbon monoxide (CO), carbon dioxide (CO2), nitrogen oxides (NOx), other pyrolysis products typical of burning organic material.

May emit clouds of acrid smoke.

FIRE INCOMPATIBILITY

■ Avoid contamination with oxidizing agents i.e. nitrates, oxidizing acids, chlorine bleaches, pool chlorine etc. as ignition may result.

PERSONAL PROTECTION

Glasses:

Chemical goggles.

Gloves:

Respirator:

Particulate

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- · Clean up waste regularly and abnormal spills immediately.
- Avoid breathing dust and contact with skin and eyes.
- Wear protective clothing, gloves, safety glasses and dust respirator.
- · Use dry clean up procedures and avoid generating dust.
- · Vacuum up or sweep up. NOTE: Vacuum cleaner must be fitted with an exhaust micro filter (HEPA type) (consider explosion-proof machines designed to be grounded during storage and use).

- · Dampen with water to prevent dusting before sweeping.
- · Place in suitable containers for disposal.

Environmental hazard - contain spillage.

MAJOR SPILLS

- · Clear area of personnel and move upwind.
- · Alert Emergency Responders and tell them location and nature of hazard.

Environmental hazard - contain spillage.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- · Avoid all personal contact, including inhalation.
- · Wear protective clothing when risk of exposure occurs.

Empty containers may contain residual dust which has the potential to accumulate following settling. Such dusts may explode in the presence of an appropriate ignition source.

- · Do NOT cut, drill, grind or weld such containers.
- \cdot In addition ensure such activity is not performed near full, partially empty or empty containers without appropriate workplace safety authorisation or permit.

RECOMMENDED STORAGE METHODS

- · Polyethylene or polypropylene container.
- · Check all containers are clearly labelled and free from leaks.

STORAGE REQUIREMENTS

■ Observe manufacturer's storing and handling recommendations.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m³	STEL ppm	STEL mg/m³	Peak ppm	Peak mg/m³	TWA F/CC	Notes
									
Canada - Alberta Occupational Exposure Limits	3-amino-1,2,4- triazole (Amino-1,2,4 triazole (Amitrole))		0.2						
Canada - British Columbia Occupational Exposure Limits	3-amino-1,2,4- triazole (Amitrole Revised 2006)		0.2						R
US ACGIH Threshold Limit Values (TLV)	3-amino-1,2,4- triazole (Amitrole)		0.2						TLV Basis: Thyroid effects
US NIOSH Recommended Exposure Limits (RELs)	3-amino-1,2,4- triazole (Amitrole)		0.2						See Appendix A; Ca
US - Minnesota Permissible Exposure Limits (PELs)	3-amino-1,2,4- triazole (Amitrole)	ù	0.2						
US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants	3-amino-1,2,4- triazole (Amitrole)		0.2						
US - California Permissible Exposure Limits for Chemical Contaminants	3-amino-1,2,4- triazole (Amitrole)		0.2						

US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	3-amino-1,2,4- triazole (Amitrole)	0.2		
US - Hawaii Air Contaminant Limits	3-amino-1,2,4- triazole (Amitrole)	0.2		
US - Washington Permissible exposure limits of air contaminants	3-amino-1,2,4- triazole (Amitrole)	0.2	0.6	
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	3-amino-1,2,4- triazole (Amitrole)	0.2	0.6	T20
US - Alaska Limits for Air Contaminants	3-amino-1,2,4- triazole (Amitrole)	0.2		
Canada - Prince Edward Island Occupational Exposure Limits	3-amino-1,2,4- triazole (Amitrole)	0.2		TLV Basis: Thyroid effects
Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)	3-amino-1,2,4- triazole (Amitrole)	0.2		
US - Michigan Exposure Limits for Air Contaminants	3-amino-1,2,4- triazole (Amitrole)	0.2		
Canada - Nova Scotia Occupational Exposure Limits	3-amino-1,2,4- triazole (Amitrole)	0.2		TLV Basis: Thyroid effects

PERSONAL PROTECTION



RESPIRATOR

ENDOELTABLE

Particulate

Consult your EHS staff for recommendations

- · Safety glasses with side shields · Chemical goggles.

HANDS/FEET

■ Wear chemical protective gloves, eg. PVC.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: such as:

- · frequency and duration of contact, · chemical resistance of glove material,
- · glove thickness and
- · dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739).

- · When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended.
- · When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended.
- · Contaminated gloves should be replaced.

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

· Neoprene gloves.

Avoid contact with moisture.

OTHER

- · Overalls.
- · P.V.C. apron.
- · Barrier cream.
- · Skin cleansing cream.
- · Eye wash unit.

ENGINEERING CONTROLS

- · Employees exposed to confirmed human carcinogens should be authorized to do so by the employer, and work in a regulated area.
- Work should be undertaken in an isolated system such as a "glove-box". Employees should wash their hands and arms upon completion of the assigned task and before engaging in other activities not associated with the isolated system.
- · Within regulated areas, the carcinogen should be stored in sealed containers, or enclosed in a closed system, including piping systems, with any sample ports or openings closed while the carcinogens are contained within.
- · Open-vessel systems are prohibited.
- · Each operation should be provided with continuous local exhaust ventilation so that air movement is always from ordinary work areas to the operation.
- · Exhaust air should not be discharged to regulated areas, non-regulated areas or the external environment unless decontaminated. Clean make-up air should be introduced in sufficient volume to maintain correct operation of the local exhaust system.
- · For maintenance and decontamination activities, authorized employees entering the area should be provided with and required to wear clean, impervious garments, including gloves, boots and continuous-air supplied hood. Prior to removing protective garments the employee should undergo decontamination and be required to shower upon removal of the garments and hood.
- Except for outdoor systems, regulated areas should be maintained under negative pressure (with respect to non-regulated areas).
- · Local exhaust ventilation requires make-up air be supplied in equal volumes to replaced air.
- Laboratory hoods must be designed and maintained so as to draw air inward at an average linear face velocity of 150 feet/ min. with a minimum of 125 feet/ min. Design and construction of the fume hood requires that insertion of any portion of the employees body, other than hands and arms, be disallowed.

Concentrate material is measured and mixed, preferably outdoors, in proportions as recommended by manufacturer.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL PROPERTIES

Solid

Mixes with water.

State	Divided solid	Molecular Weight	84.08
Melting Range (°F)	318.2	Viscosity	Not Applicable
Boiling Range (°F)	Not available.	Solubility in water (g/L)	Miscible
Flash Point (°F)	Not applicable.	pH (1% solution)	5-7
Decomposition Temp (°F)	Not available.	pH (as supplied)	Not applicable
Autoignition Temp (°F)	Not available.	Vapour Pressure (mmHG)	Not applicable
Upper Explosive Limit (%)	Not applicable.	Specific Gravity (water=1)	Not available.
Lower Explosive Limit (%)	Not applicable.	Relative Vapor Density (air=1)	2.8
Volatile Component (%vol)	Not applicable	Evaporation Rate	Not applicable

APPEARANCE

 $White \ crystalline \ solid; \ soluble \ in \ water. \ No \ odour. \ Soluble \ in \ methanol, \ ethanol \ and \ chloroform. \ Slightly \ soluble \ in \ ethyl \ acetate.$

log Kow -0.15

Material Value

Section 10 - CHEMICAL STABILITY

CONDITIONS CONTRIBUTING TO INSTABILITY

· Presence of incompatible materials.

· Product is considered stable.

STORAGE INCOMPATIBILITY

Avoid reaction with oxidizing agents.

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

3-AMINO-1,2,4-TRIAZOLE

TOXICITY AND IRRITATION

3-AMINO-1,2,4-TRIAZOLE:

■ unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY IRRITATION
Oral (rat) LD50: 1100 mg/kg Nil Reported
Dermal (rat) LD50: >10000 mg/kg
Oral (mouse) LD50: 14700 mg/kg
Intraperitoneal (mouse) LD50: 200 mg/kg

Intravenous (mouse) LD50: >5000 mg/kg

■ The substance is classified by IARC as Group 3:

NOT classifiable as to its carcinogenicity to humans.

Evidence of carcinogenicity may be inadequate or limited in animal testing. Tenth Annual Report on Carcinogens: Substance anticipated to be Carcinogen [National Toxicology Program: U.S. Dep. of Health & Human Services 2002]. Foetotoxicity, foetolethality, specific developmental abnormalities

(endocrine system) recorded. ADI: 0.003 mg/kg/day NOEL: 0.025 mg/kg/day

CARCINOGEN

AMITROLE	US Environmental Defense Scorecard Recognized Carcinogens	Reference(s)	P65
AMITROLE	US Environmental Defense Scorecard Suspected Carcinogens	Reference(s)	P65

Section 12 - ECOLOGICAL INFORMATION

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

This material and its container must be disposed of as hazardous waste.

Avoid release to the environment.

Refer to special instructions/ safety data sheets.

Ecotoxicity

Persistence: Water/Soil

3-amino-1,2,4- HIGH

Persistence: Air Bioaccumulation Mobility

LOW LOW HIGH

Section 13 - DISPOSAL CONSIDERATIONS

US EPA Waste Number & Descriptions

B. Component Waste Numbers

When 3-amino-1,2,4-triazole is present as a solid waste as a discarded

commercial chemical product, off-specification species, as a container residue,

or a spill residue, use EPA waste number U011 (waste code T).

Disposal Instructions

All waste must be handled in accordance with local, state and federal regulations.

l' Puncture containers to prevent re-use and bury at an authorized landfill.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- · Reduction
- · Reuse
- · Recycling
- · Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

DO NOT allow wash water from cleaning equipment to enter drains. Collect all wash water for treatment before disposal.

- · Recycle wherever possible.
- · Consult manufacturer for recycling options or consult Waste Management Authority for disposal if no suitable treatment or disposal facility can be identified.

Section 14 - TRANSPORTATION INFORMATION



DOT:

Symbols: G Hazard class or Division: 9 Identification Numbers: UN3077 PG: III Label Codes: 9 Special provisions: 8, 146,

335, B54, IB8, IP3, N20, T1, TP33

Packaging: Exceptions: 155 Packaging: Non-bulk: 213 Packaging: Exceptions: 155 Quantity limitations: No limit

Passenger aircraft/rail:

Quantity Limitations: Cargo No limit Vessel stowage: Location: A

aircraft only:

Vessel stowage: Other: None

Hazardous materials descriptions and proper shipping names:

Environmentally hazardous substance, solid, n.o.s

Air Transport IATA:

ICAO/IATA Class: 9 ICAO/IATA Subrisk: None UN/ID Number: 3077 Packing Group: III

Special provisions: A97

Cargo Only

Packing Instructions: 911 Maximum Qty/Pack: 400 kg Passenger and Cargo Passenger and Cargo Packing Instructions: 911 Maximum Qty/Pack: 400 kg

Passenger and Cargo Limited Quantity Passenger and Cargo Limited Quantity

Packing Instructions: Y911 Maximum Qty/Pack: 30 kg G

Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S. *(CONTAINS 3-AMINO-1,2,4-TRIAZOLE)

Maritime Transport IMDG: IMDG Class: 9 IMDG Subrisk: None UN Number: 3077 Packing Group: III

EMS Number: F-A, S-F Special provisions: 179 274 335 909

Limited Quantities: 5 kg Marine Pollutant: Yes

Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

Section 15 - REGULATORY INFORMATION

3-amino-1,2,4-triazole (CAS: 61-82-5) is found on the following regulatory lists;

"Canada - Alberta Occupational Exposure Limits", "Canada - British Columbia Occupational Exposure Limits", "Canada - Nova Scotia Occupational Exposure Limits", "Canada - Prince Edward Island Occupational Exposure Limits", "Canada - Prince Edward Island Occupational Exposure Limits", "Canada - Prince Edward Island Occupational Exposure Limits", "Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)", "Canada - Saskatchewan Industrial Hazardous Substances", "Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits", "Canada - Saskatchewan Occupational Health and Safety Regulations - Designated Chemical Substances", "Canada Domestic Substances List (DSL)", "International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs", "OECD Representative List of High Production Volume (HPV) Chemicals", "US - Alaska Limits for Air Contaminants", "US - California Air Toxics ""Hot Spots"" List (Assembly Bill 2588) Substances for which emissions must be

quantified","US - California Occupational Safety and Health Regulations (CAL/OSHA) - Hazardous Substances List","US - California Permissible Exposure Limits for Chemical Contaminants", "US - California Proposition 65 - Carcinogens", "US - California Proposition 65 - No Significant Risk Levels (NSRLs) for Carcinogens", "US - Connecticut Hazardous Air Pollutants", "US - Hawaii Air Contaminant Limits","US - Maine Chemicals of High Concern List","US - Massachusetts Oil & Hazardous Material List","US - Michigan Exposure Limits for Air Contaminants", "US - Minnesota Hazardous Substance List", "US - Minnesota Permissible Exposure Limits (PELs)", "US -New Jersey Right to Know Hazardous Substances", "US - Pennsylvania - Hazardous Substance List", "US - Rhode Island Hazardous Substance List", "US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants", "US - Vermont Hazardous Constituents", "US - Vermont Hazardous wastes which are Discarded Commercial Chemical Products or Off-Specification Batches of Commercial Chemical Products or Spill Residues of Either","US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants", "US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants", "US - Washington Class A toxic air pollutants: Known and Probable Carcinogens","US - Washington Dangerous waste constituents list","US - Washington Discarded Chemical Products List - ""U"" Chemical Products","US - Washington Permissible exposure limits of air contaminants","US ACGIH Threshold Limit Values (TLV)", "US ACGIH Threshold Limit Values (TLV) - Carcinogens", "US Department of Transportation (DOT) List of Hazardous Substances and Reportable Quantities - Hazardous Substances Other Than Radionuclides", "US DOE Temporary Emergency Exposure Limits (TEELs)", "US EPA Master Testing List - Index I Chemicals Listed", "US EPCRA Section 313 Chemical List", "US List of Lists - Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112(r) of the Clean Air Act", "US National Toxicology Program (NTP) 11th Report Part B. Reasonably Anticipated to be a Human Carcinogen", "US NIOSH Recommended Exposure Limits (RELs)","US RCRA (Resource Conservation & Recovery Act) - Hazardous Constituents - Appendix VIII to 40 CFR 261","US RCRA (Resource Conservation & Recovery Act) - List of Hazardous Wastes","US Toxic Substances Control Act (TSCA) -Inventory", "US TSCA Section 8 (a) - Preliminary Assessment Information Rules (PAIR) - Reporting List", "US TSCA Section 8 (d) - Health and Safety Data Reporting"

Section 16 - OTHER INFORMATION

Reasonable care has been taken in the preparation of this information, but the author makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The author makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. For additional technical information please call our toxicology department on +800 CHEMCALL.

- Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

 A list of reference resources used to assist the committee may be found at:

 www.chemwatch.net/references.
- The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: Apr-26-2008 Print Date: Dec-23-2010