



SZABO SCANDIC

Part of Europa Biosite

Produktinformation



Forschungsprodukte & Biochemikalien



Zellkultur & Verbrauchsmaterial



Diagnostik & molekulare Diagnostik



Laborgeräte & Service

Weitere Information auf den folgenden Seiten!
See the following pages for more information!



Lieferung & Zahlungsart

siehe unsere [Liefer- und Versandbedingungen](#)

Zuschläge

- Mindermengenzuschlag
- Trockeneiszuschlag
- Gefahrgutzuschlag
- Expressversand

SZABO-SCANDIC HandelsgmbH

Quellenstraße 110, A-1100 Wien

T. +43(0)1 489 3961-0

F. +43(0)1 489 3961-7

mail@szabo-scandic.com

www.szabo-scandic.com

[linkedin.com/company/szaboscandic](https://www.linkedin.com/company/szaboscandic) 

Manganese(II) sulfate monohydrate

sc-203130



The Power is Question

Material Safety Data Sheet

Hazard Alert Code Key: **EXTREME** **HIGH** **MODERATE** **LOW**

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

Manganese(II) sulfate monohydrate

STATEMENT OF HAZARDOUS NATURE

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

NFPA



SUPPLIER

Company: Santa Cruz Biotechnology, Inc.

Address:

2145 Delaware Ave

Santa Cruz, CA 95060

Telephone: 800.457.3801 or 831.457.3800

Emergency Tel: CHEMWATCH: From within the US and Canada:
877-715-9305

Emergency Tel: From outside the US and Canada: +800 2436 2255
(1-800-CHEMCALL) or call +613 9573 3112

SYNONYMS

MnSO₄ H₂O, "sulfuric acid, manganese(2+) salt, hydrate", "manganous sulphate", "manganous sulfate"

Section 2 - HAZARDS IDENTIFICATION

CANADIAN WHMIS SYMBOLS



EMERGENCY OVERVIEW

RISK

Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed.
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

Manganese(II) sulfate monohydrate

sc-203130



The Power is Question

Material Safety Data Sheet

Hazard Alert Code Key: **EXTREME** **HIGH** **MODERATE** **LOW**

SWALLOWED

- Accidental ingestion of the material may be damaging to the health of the individual.
- Poisonings rarely occur after oral administration of manganese salts because they are poorly absorbed from the gut.
- Sulfates are not well absorbed orally, but can cause diarrhea.

EYE

- Although the material is not thought to be an irritant, direct contact with the eye may cause transient discomfort characterized by tearing or conjunctival redness (as with windburn). Slight abrasive damage may also result. The material may produce foreign body irritation in certain individuals.

SKIN

- The material is not thought to produce adverse health effects or skin irritation following contact (as classified using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.
- Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

INHALED

- The material is not thought to produce respiratory irritation (as classified using animal models). Nevertheless inhalation of dusts, or fume, especially for prolonged periods, may produce respiratory discomfort and occasionally, distress.
- Inhalation of dusts, generated by the material during the course of normal handling, may produce serious damage to the health of the individual.
- Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.
- Manganese fume is toxic and produces nervous system effects characterized by tiredness. Acute poisoning is rare although acute inflammation of the lungs may occur. A chemical pneumonia may also result from frequent exposure. Inhalation of freshly formed metal oxide particles sized below 1.5 microns and generally between 0.02 to 0.05 microns may result in "metal fume fever". Symptoms may be delayed for up to 12 hours and begin with the sudden onset of thirst, and a sweet, metallic or foul taste in the mouth. Other symptoms include upper respiratory tract irritation accompanied by coughing and a dryness of the mucous membranes, lassitude and a generalized feeling of malaise. Mild to severe headache, nausea, occasional vomiting, fever or chills, exaggerated mental activity, profuse sweating, diarrhea, excessive urination and prostration may also occur. Tolerance to the fumes develops rapidly, but is quickly lost. All symptoms usually subside within 24-36 hours following removal from exposure.

CHRONIC HEALTH EFFECTS

- Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed. This material can cause serious damage if one is exposed to it for long periods. It can be assumed that it contains a substance which can produce severe defects. This has been demonstrated via both short- and long-term experimentation. Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems. Long term exposure to high dust concentrations may cause changes in lung function i.e. pneumoconiosis; caused by particles less than 0.5 micron penetrating and remaining in the lung. Prime symptom is breathlessness; lung shadows show on X-ray. Manganese is an essential trace element. Chronic exposure to low levels of manganese can include a mask-like facial expression, spastic gait, tremors, slurred speech, disordered muscle tone, fatigue, anorexia, loss of strength and energy, apathy and poor concentration.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

HAZARD RATINGS

| | Min | Max |
|---------------|-----|-----|
| Flammability: | 0 | |
| Toxicity: | 3 | |
| Body Contact: | 0 | |
| Reactivity: | 0 | |
| Chronic: | 2 | |

Min/Nil=0
Low=1
Moderate=2
High=3
Extreme=4



Manganese(II) sulfate monohydrate

sc-203130



The Power is Question

Material Safety Data Sheet

| | | | | |
|-----------------------------------|----------------|-------------|-----------------|------------|
| Hazard Alert Code Key: | EXTREME | HIGH | MODERATE | LOW |
| NAME | CAS RN | % | | |
| Manganese(II) sulfate monohydrate | 10034-96-5 | > 95 | | |

Section 4 - FIRST AID MEASURES

SWALLOWED

-
- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Seek medical advice.

EYE

- If this product comes in contact with the eyes:
 - Immediately hold eyelids apart and flush the eye continuously with running water.
 - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
 - Continue flushing until advised to stop by the Poisons Information Center or a doctor, or for at least 15 minutes.
 - Transport to hospital or doctor without delay.
 - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin or hair contact occurs:
 - Flush skin and hair with running water (and soap if available).
 - Seek medical attention in event of irritation.

INHALED

-
- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor, without delay.

NOTES TO PHYSICIAN

■ Both dermal and oral toxicity of manganese salts is low because of limited solubility of manganese. No known permanent pulmonary sequelae develop after acute manganese exposure. Treatment is supportive. [Ellenhorn and Barceloux: Medical Toxicology] In clinical trials with miners exposed to manganese-containing dusts, L-dopa relieved extrapyramidal symptoms of both hypokinetic and dystonic patients. For short periods of time symptoms could also be controlled with scopolamine and amphetamine. BAL and calcium EDTA prove ineffective. [Gosselin et al: Clinical Toxicology of Commercial Products.].

Section 5 - FIRE FIGHTING MEASURES

| | |
|-----------------------------|----------------|
| Vapour Pressure (mmHG): | Not applicable |
| Upper Explosive Limit (%): | Not applicable |
| Specific Gravity (water=1): | 3.25 |
| Lower Explosive Limit (%): | Not applicable |

EXTINGUISHING MEDIA

Manganese(II) sulfate monohydrate

sc-203130



The Power is Question

Material Safety Data Sheet

Hazard Alert Code Key:

EXTREME

HIGH

MODERATE

LOW

-
- Water spray or fog.
- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

FIRE FIGHTING

-
- Alert Emergency Responders and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves for fire only.
- Prevent, by any means available, spillage from entering drains or water course.
- Use fire fighting procedures suitable for surrounding area.
- Do not approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

GENERAL FIRE HAZARDS/HAZARDOUS COMBUSTIBLE PRODUCTS

- - Non combustible.
 - Not considered to be a significant fire risk, however containers may burn.
- Decomposition may produce toxic fumes of: sulfur oxides (SOx), metal oxides.

FIRE INCOMPATIBILITY

- None known.

PERSONAL PROTECTION

Glasses:
Chemical goggles.
Gloves:
Respirator:
Particulate

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

-
- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid contact with skin and eyes.
- Control personal contact by using protective equipment.
- Use dry clean up procedures and avoid generating dust.
- Place in a suitable, labelled container for waste disposal.

Environmental hazard - contain spillage.

MAJOR SPILLS

- Environmental hazard - contain spillage.

Moderate hazard.

- CAUTION: Advise personnel in area.
- Alert Emergency Responders and tell them location and nature of hazard.
- Control personal contact by wearing protective clothing.
- Prevent, by any means available, spillage from entering drains or water courses.
- Recover product wherever possible.
- IF DRY: Use dry clean up procedures and avoid generating dust. Collect residues and place in sealed plastic bags or other containers for disposal. IF WET: Vacuum/shovel up and place in labelled containers for disposal.
- ALWAYS: Wash area down with large amounts of water and prevent runoff into drains.
- If contamination of drains or waterways occurs, advise emergency services.

Manganese(II) sulfate monohydrate

sc-203130


Material Safety Data Sheet



The Power is Question

Hazard Alert Code Key: **EXTREME** **HIGH** **MODERATE** **LOW**

PROTECTIVE ACTIONS FOR SPILL



FOOTNOTES

- 1 PROTECTIVE ACTION ZONE is defined as the area in which people are at risk of harmful exposure. This zone assumes that random changes in wind direction confines the vapour plume to an area within 30 degrees on either side of the predominant wind direction, resulting in a crosswind protective action distance equal to the downwind protective action distance.
- 2 PROTECTIVE ACTIONS should be initiated to the extent possible, beginning with those closest to the spill and working away from the site in the downwind direction. Within the protective action zone a level of vapour concentration may exist resulting in nearly all unprotected persons becoming incapacitated and unable to take protective action and/or incurring serious or irreversible health effects.
- 3 INITIAL ISOLATION ZONE is determined as an area, including upwind of the incident, within which a high probability of localised wind reversal may expose nearly all persons without appropriate protection to life-threatening concentrations of the material.
- 4 SMALL SPILLS involve a leaking package of 200 litres (55 US gallons) or less, such as a drum (jerrican or box with inner containers). Larger packages leaking less than 200 litres and compressed gas leaking from a small cylinder are also considered "small spills". LARGE SPILLS involve many small leaking packages or a leaking package of greater than 200 litres, such as a cargo tank, portable tank or a "one-tonne" compressed gas cylinder.
- 5 Guide 171 is taken from the US DOT emergency response guide book.
- 6 IERG information is derived from CANUTEC - Transport Canada.

ACUTE EXPOSURE GUIDELINE LEVELS (AEGL) (in ppm)

AEGL 1: The airborne concentration of a substance above which it is predicted that the general population, including susceptible individuals, could experience notable discomfort, irritation, or certain asymptomatic nonsensory effects. However, the effects are not disabling and are transient and reversible upon cessation of exposure.

AEGL 2: The airborne concentration of a substance above which it is predicted that the general population, including susceptible individuals, could experience irreversible or other serious, long-lasting adverse health effects or an impaired ability to escape.

AEGL 3: The airborne concentration of a substance above which it is predicted that the general population, including susceptible individuals, could experience life-threatening health effects or death.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.

Manganese(II) sulfate monohydrate

sc-203130



The Power is Question

Material Safety Data Sheet

Hazard Alert Code Key: **EXTREME** **HIGH** **MODERATE** **LOW**

- DO NOT allow material to contact humans, exposed food or food utensils.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Launder contaminated clothing before re-use.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.


RECOMMENDED STORAGE METHODS

- Glass container.
- Polyethylene or polypropylene container.
- Check all containers are clearly labelled and free from leaks.

STORAGE REQUIREMENTS

- Observe manufacturer's storing and handling recommendations.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



X: Must not be stored together

O: May be stored together with specific preventions

+: May be stored together

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

| Source | Material | TWA ppm | TWA mg/m ³ | STEL ppm | STEL mg/m ³ | Peak ppm | Peak mg/m ³ | TWA F/CC | Notes |
|---|---|---------|-----------------------|----------|------------------------|----------|------------------------|----------|-------|
| US - California Permissible Exposure Limits for Chemical Contaminants | manganese sulfate, hydrate (Manganese and compounds, as Mn) | | 0.2 | | | | | | |
| US - Idaho - Limits for Air Contaminants | manganese sulfate, hydrate (Manganese compounds (as Mn)) | | | | | | 5 | | |
| US NIOSH Recommended Exposure Limits (RELs) | manganese sulfate, hydrate (Manganese compounds and fume (as Mn)) | | 1 | | 3 | | | | |
| US - Minnesota Permissible Exposure Limits (PELs) | manganese sulfate, hydrate (Manganese compounds (as Mn)) | | | | | | 5 | | |

Manganese(II) sulfate monohydrate

sc-203130



The Power is Question

Material Safety Data Sheet

| Hazard Alert Code Key: | | EXTREME | HIGH | MODERATE | LOW |
|---|--|---------|------|----------|-----|
| US - Minnesota Permissible Exposure Limits (PELs) | manganese sulfate, hydrate (Manganese fume (as Mn)) | | 1 | 3 | |
| US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants | manganese sulfate, hydrate (Manganese fume (as Mn)) | | (C)5 | | |
| US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants | manganese sulfate, hydrate (Manganese compounds (as Mn)) | | | | 5 |
| US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants | manganese sulfate, hydrate (Manganese fume (as Mn)) | | 1 | 3 | |
| US - Idaho - Limits for Air Contaminants | manganese sulfate, hydrate (Manganese fume (as Mn)) | | | | 5 |
| US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants | manganese sulfate, hydrate (Manganese compounds (as Mn)) | | | | 5 |
| US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants | manganese sulfate, hydrate (Manganese compounds (as Mn)) | | (C)5 | | |
| US - Hawaii Air Contaminant Limits | manganese sulfate, hydrate (Manganese fume (as Mn)) | | 1 | 3 | |
| US - Alaska Limits for Air Contaminants | manganese sulfate, hydrate (Manganese Compounds (as Mn)) | | | | 5 |
| US - Michigan Exposure Limits for Air Contaminants | manganese sulfate, hydrate (Manganese, Compounds (as Mn)) | | | | 5 |
| Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances | manganese sulfate, hydrate (Manganese and compounds (as Mn)) | - | 5 | - | - |
| US - Washington Permissible exposure limits of air contaminants | manganese sulfate, hydrate (Manganese and compounds (as Mn)) | | | | 5 |
| US - Hawaii Air Contaminant Limits | manganese sulfate, hydrate (Manganese compounds (as Mn)) | | | | 5 |
| Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English) | manganese sulfate, hydrate (Manganese (as Mn): Dust and compounds) | | 5 | | |
| US OSHA Permissible Exposure Levels (PELs) - Table Z1 | manganese sulfate, hydrate (Manganese compounds (as Mn)) | | | | 5 |

Manganese(II) sulfate monohydrate

sc-203130



The Power is Question

Material Safety Data Sheet

| Hazard Alert Code Key: | | EXTREME | HIGH | MODERATE | LOW |
|---|---|---------|------|----------|--|
| US OSHA Permissible Exposure Levels (PELs) - Table Z1 | manganese sulfate, hydrate (Manganese fume (as Mn)) | | | 5 | |
| US - Oregon Permissible Exposure Limits (Z1) | manganese sulfate, hydrate (Manganese Compounds (as Mn)) | | | 5 | |
| Canada - Northwest Territories Occupational Exposure Limits (English) | manganese sulfate, hydrate (Manganese & compounds (as Mn)) | | | 5 | |
| Canada - Northwest Territories Occupational Exposure Limits (English) | manganese sulfate, hydrate (Manganese fume (as Mn)) | | 1 | 3 | |
| Canada - Alberta Occupational Exposure Limits | manganese sulfate, hydrate (Manganese, elemental & inorganic compounds, as Mn) | | 0.2 | | |
| Canada - Ontario Occupational Exposure Limits | manganese sulfate, hydrate (Manganese, and inorganic compounds (as manganese)) | | 0.2 | | |
| Canada - British Columbia Occupational Exposure Limits | manganese sulfate, hydrate (Manganese - Elemental & inorganic compounds, as Mn) | | 0.2 | | R |
| Canada - Nova Scotia Occupational Exposure Limits | manganese sulfate, hydrate (Manganese - Elemental & inorganic cmpds (as Mn)) | | 0.2 | | TLV Basis: central nervous system impairment |
| Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits | manganese sulfate, hydrate (Manganese and inorganic compounds, (as Mn)) | | 0.2 | 0.6 | |
| US ACGIH Threshold Limit Values (TLV) | manganese sulfate, hydrate (Manganese - Elemental & inorganic cmpds (as Mn)) | | 0.2 | | TLV Basis: central nervous system impairment |
| Canada - Prince Edward Island Occupational Exposure Limits | manganese sulfate, hydrate (Manganese - Elemental & inorganic cmpds (as Mn)) | | 0.2 | | TLV Basis: central nervous system impairment |
| US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants | manganese sulfate, hydrate (Manganese compounds (as Mn)) | | | 5 | |

EMERGENCY EXPOSURE LIMITS

| Material | Revised IDLH Value (mg/m3) | Revised IDLH Value (ppm) |
|----------------------------|----------------------------|--------------------------|
| manganese sulfate, hydrate | 500 | |

MATERIAL DATA

MANGANESE SULFATE, HYDRATE:

■ A number of studies have shown that susceptibility to the effects of manganese at or about 1 - 5 mg/m3 (TWA) can lead to clinical manifestations of manganism or more commonly to the development of indicators of sub-clinical manganism (e.g. hand tremor, exaggerated reflexes, short-term memory deficits, poor psychomotor performance). Long term exposure at, or below the recommended

Manganese(II) sulfate monohydrate

sc-203130



The Power is Question

Material Safety Data Sheet

Hazard Alert Code Key:

EXTREME

HIGH

MODERATE

LOW

ES TWA should provide protection for those individuals susceptible to neurological effects of prolonged exposure.

PERSONAL PROTECTION



Consult your EHS staff for recommendations

EYE

-
- Safety glasses with side shields
- Chemical goggles.
- Contact lenses pose a special hazard; soft lenses may absorb irritants and all lenses concentrate them.

HANDS/FEET

- Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: such as:
 - frequency and duration of contact,
 - chemical resistance of glove material,
 - glove thickness and
 - dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739).

- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended.
- When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended.
- Contaminated gloves should be replaced.

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Wear chemical protective gloves, eg. PVC.

Wear safety footwear or safety gumboots, eg. Rubber.

OTHER

-
- Overalls.
- P.V.C. apron.
- Barrier cream.
- Skin cleansing cream.
- Eye wash unit.
-
- Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.
- The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).
- Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory . These may be government mandated or vendor recommended.
- Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.
- Use approved positive flow mask if significant quantities of dust becomes airborne.
- Try to avoid creating dust conditions.

RESPIRATOR

■

Manganese(II) sulfate monohydrate

sc-203130



The Power is Question

Material Safety Data Sheet

| Hazard Alert Code Key: | EXTREME | HIGH | MODERATE | LOW |
|------------------------|----------------------|----------------------|------------------------|-----|
| Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator | |
| 10 x PEL | P1 Air-line* | - | PAPR-P1 | - |
| 50 x PEL | Air-line** | P2 | PAPR-P2 | - |
| 100 x PEL | - | P3 Air-line* | - | - |
| 100+ x PEL | - | Air-line** | PAPR-P3 | - |

* - Negative pressure demand ** - Continuous flow

Explanation of Respirator Codes:

Class 1 low to medium absorption capacity filters.

Class 2 medium absorption capacity filters.

Class 3 high absorption capacity filters.

PAPR Powered Air Purifying Respirator (positive pressure) cartridge.

Type A for use against certain organic gases and vapors.

Type AX for use against low boiling point organic compounds (less than 65°C).

Type B for use against certain inorganic gases and other acid gases and vapors.

Type E for use against sulfur dioxide and other acid gases and vapors.

Type K for use against ammonia and organic ammonia derivatives

Class P1 intended for use against mechanically generated particulates of sizes most commonly encountered in industry, e.g. asbestos, silica.

Class P2 intended for use against both mechanically and thermally generated particulates, e.g. metal fume.

Class P3 intended for use against all particulates containing highly toxic materials, e.g. beryllium.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

Use appropriate NIOSH-certified respirator based on informed professional judgement. In conditions where no reasonable estimate of exposure can be made, assume the exposure is in a concentration IDLH and use NIOSH-certified full face pressure demand SCBA with a minimum service life of 30 minutes, or a combination full facepiece pressure demand SAR with auxiliary self-contained air supply. Respirators provided only for escape from IDLH atmospheres shall be NIOSH-certified for escape from the atmosphere in which they will be used.

ENGINEERING CONTROLS

Local exhaust ventilation usually required. If risk of overexposure exists, wear an approved respirator. Correct fit is essential to obtain adequate protection an approved self contained breathing apparatus (SCBA) may be required in some situations. Provide adequate ventilation in warehouse or closed storage area.

Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

| Type of Contaminant: | Air Speed: |
|---|----------------------------------|
| solvent, vapors, degreasing etc., evaporating from tank (in still air). | 0.25-0.5 m/s (50-100 f/min.) |
| aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5-1 m/s (100-200 f/min.) |
| direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion) | 1-2.5 m/s (200-500 f/min.) |
| grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion). | 2.5-10 m/s (500-2000 f/min.) |
| Within each range the appropriate value depends on: | |
| Lower end of the range | Upper end of the range |
| 1: Room air currents minimal or favorable to capture | 1: Disturbing room air currents |
| 2: Contaminants of low toxicity or of nuisance value only. | 2: Contaminants of high toxicity |
| 3: Intermittent, low production. | 3: High production, heavy use |
| 4: Large hood or large air mass in motion | 4: Small hood-local control only |

Manganese(II) sulfate monohydrate

sc-203130



The Power is Question

Material Safety Data Sheet

Hazard Alert Code Key: **EXTREME** **HIGH** **MODERATE** **LOW**

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL PROPERTIES

Solid.

Mixes with water.

| | | | |
|---------------------------|------------------|--------------------------------|----------------|
| State | Divided solid | Molecular Weight | 169.02 |
| Melting Range (°F) | 1292 | Viscosity | Not Applicable |
| Boiling Range (°F) | Decomposes @185F | Solubility in water (g/L) | Miscible |
| Flash Point (°F) | Not applicable | pH (1% solution) | Not available |
| Decomposition Temp (°F) | 185 | pH (as supplied) | Not applicable |
| Autoignition Temp (°F) | Not applicable | Vapour Pressure (mmHG) | Not applicable |
| Upper Explosive Limit (%) | Not applicable | Specific Gravity (water=1) | 3.25 |
| Lower Explosive Limit (%) | Not applicable | Relative Vapor Density (air=1) | Not applicable |
| Volatile Component (%vol) | Not applicable | Evaporation Rate | Not applicable |

APPEARANCE

Odorless, hygroscopic powder or crystals; soluble in water. This material exists in anhydrous and hydrated forms. On heating, the tetrahydrate readily converts to the monohydrate, which in turn loses water at approximately 450 C to form the anhydrous salt. Solubility in water is 52 g/100 ml at 5 C and 70 g/100 ml at 70 C. Commercially supplied as a mixture of the tetra- and the pentahydrate forms or in the monohydrate form.

Section 10 - CHEMICAL STABILITY

CONDITIONS CONTRIBUTING TO INSTABILITY

■

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerization will not occur.

STORAGE INCOMPATIBILITY

■

- WARNING: Avoid or control reaction with peroxides. All transition metal peroxides should be considered as potentially explosive. For example transition metal complexes of alkyl hydroperoxides may decompose explosively.
- The pi-complexes formed between chromium(0), vanadium(0) and other transition metals (haloarene-metal complexes) and mono-or poly-fluorobenzene show extreme sensitivity to heat and are explosive.
- Avoid reaction with borohydrides or cyanoborohydrides

Metals and their oxides or salts may react violently with chlorine trifluoride. Chlorine trifluoride is a hypergolic oxidizer. It ignites on contact (without external source of heat or ignition) with recognized fuels - contact with these materials, following an ambient or slightly elevated temperature, is often violent and may produce ignition. The state of subdivision may affect the results.

For incompatible materials - refer to Section 7 - Handling and Storage.

Manganese(II) sulfate monohydrate

sc-203130



The Power is Question

Material Safety Data Sheet

Hazard Alert Code Key:

EXTREME

HIGH

MODERATE

LOW

Section 11 - TOXICOLOGICAL INFORMATION

manganese sulfate, hydrate

TOXICITY AND IRRITATION

■ unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

IRRITATION

Intraperitoneal (Mouse) LD50: 534 mg/kg

Not available.

Section 12 - ECOLOGICAL INFORMATION

Refer to data for ingredients, which follows:

MANGANESE SULFATE, HYDRATE:

■ Toxic to aquatic organisms.

■ Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

■ May cause long-term adverse effects in the aquatic environment.

■ Data from tap water studies with human volunteers indicate that sulfates produce a laxative effect at concentrations of 1000 - 1200 mg/litre, but no increase in diarrhoea, dehydration or weight loss. The presence of sulfate in drinking-water can also result in a noticeable taste; the lowest taste threshold concentration for sulfate is approximately 250 mg/litre as the sodium salt. Sulfate may also contribute to the corrosion of distribution systems. No health-based guideline value for sulfate in drinking water is proposed. However, there is an increasing likelihood of complaints arising from a noticeable taste as concentrations in water increase above 500 mg/litre.

Sulfates are removed from the air by both dry and wet deposition processes. Wet deposition processes including rain-out (a process that occurs within the clouds) and washout (removal by precipitation below the clouds) contribute to the removal of sulfate from the atmosphere.

In soil, the inorganic sulfates can adsorb to soil particles or leach into surface water and groundwater. Sulfates can be taken up by plants and be incorporated into the parenchyma of the plant.

Sulfate in water can also be reduced by sulfate bacteria (Thiobacilli) which use them as a source of energy.

■ For manganese and its compounds:

Environmental fate:

It has been established that while lower organisms (e.g., plankton, aquatic plants, and some fish) can significantly bioconcentrate manganese, higher organisms (including humans) tend to maintain manganese homeostasis. This indicates that the potential for biomagnification of manganese from lower trophic levels to higher ones is low.

There were two mechanisms involved in explaining the retention of manganese and other metals in the environment by soil. First, through cation exchange reactions, manganese ions and the charged surface of soil particles form manganese oxides, hydroxides, and oxyhydroxides which in turn form absorption sites for other metals. Secondly, manganese can be adsorbed to other oxides, hydroxides, and oxyhydroxides through ligand exchange reactions. When the soil solution becomes saturated, these manganese oxides, hydroxides, and oxyhydroxides can precipitate into a new mineral phase and act as a new surface to which other substances can adsorb. The tendency of soluble manganese compounds to adsorb to soils and sediments depends mainly on the cation exchange capacity and the organic composition of the soil. The soil adsorption constants (the ratio of the concentration in soil to the concentration in water) for Mn(II) span five orders of magnitude, ranging from 0.2 to 10,000 mL/g, increasing as a function of the organic content and the ion exchange capacity of the soil; thus, adsorption may be highly variable. In some cases, adsorption of manganese to soils may not be a readily reversible process. At low concentrations, manganese may be "fixed" by clays and will not be released into solution readily. At higher concentrations, manganese may be desorbed by ion exchange mechanisms with other ions in solution. For example, the discharge of waste water effluent into estuarine environments resulted in the mobilization of manganese from the bottom sediments. The metals in the effluent may have been preferentially adsorbed resulting in the release of manganese. The oxidation state of manganese in soil and sediments may be altered by microbial activity; oxidation may lead to the precipitation of manganese. Bacteria and microflora can increase the mobility of manganese.

The transport and partitioning of manganese in water is controlled by the solubility of the specific chemical form present, which in turn is determined by pH, Eh (oxidation-reduction potential), and the characteristics of the available anions. The metal may exist in water in any of four oxidation states.

Manganese(II) predominates in most waters (pH 4-7) but may become oxidized at a pH >8 or 9. The principal anion associated with Mn(II) in water is usually carbonate (CO₃²⁻), and the concentration of manganese is limited by the relatively low solubility (65 mg/L) of MnCO₃. In relatively oxidized water, the solubility of Mn(II) may be controlled by manganese oxide equilibria, with manganese being

Manganese(II) sulfate monohydrate

sc-203130



The Power is Question

Material Safety Data Sheet

Hazard Alert Code Key:

EXTREME

HIGH

MODERATE

LOW

converted to the Mn(II) or Mn(IV) oxidation states. In extremely reduced water, the fate of manganese tends to be controlled by formation of a poorly soluble sulfide. Manganese in water may undergo oxidation at high pH or Eh and is also subject to microbial activity. For example, Mn(II) in a lake was oxidized during the summer months, but this was inhibited by a microbial poison, indicating that the oxidation was mediated by bacteria. The microbial metabolism of manganese is presumed to be a function of pH, temperature, and other factors.

Manganese in water may be significantly bioconcentrated at lower trophic levels. A bioconcentration factor (BCF) relates the concentration of a chemical in plant and animal tissues to the concentration of the chemical in the water in which they live. The BCF of manganese was estimated as 2,500 - 6,300 for phytoplankton, 300 - 5,500 for marine algae, 80 - 830 for intertidal mussels, and 35 - 930 for coastal fish. Similarly, the BCF of manganese was estimated to be 10,000 - 20,000 for marine and freshwater plants, 10,000 - 40,000 for invertebrates, and 10 - 600 for fish. In general, these data indicate that lower organisms such as algae have larger BCFs than higher organisms. In order to protect consumers from the risk of manganese bioaccumulation in marine mollusks, the U.S. EPA has set a criterion for manganese at 0.1 mg/L for marine waters.

Elemental manganese and inorganic manganese compounds have negligible vapor pressures but may exist in air as suspended particulate matter derived from industrial emissions or the erosion of soils. Manganese-containing particles are mainly removed from the atmosphere by gravitational settling, with large particles tending to fall out faster than small particles. The half-life of airborne particles is usually on the order of days, depending on the size of the particle and atmospheric conditions. Some removal by washout mechanisms such as rain may also occur, although it is of minor significance in comparison to dry deposition.

■ DO NOT discharge into sewer or waterways.

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Instructions

All waste must be handled in accordance with local, state and federal regulations.

‡ Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- Reuse
- Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

DO NOT allow wash water from cleaning equipment to enter drains. Collect all wash water for treatment before disposal.

- Recycle wherever possible or consult manufacturer for recycling options.
- Consult Waste Management Authority for disposal.
- Bury residue in an authorized landfill.
- Recycle containers where possible, or dispose of in an authorized landfill.

Section 14 - TRANSPORTATION INFORMATION



DOT:

| | | | |
|-------------------------|--------|---------------------------|---|
| Symbols: | G | Hazard class or Division: | 9 |
| Identification Numbers: | UN3077 | PG: | III |
| Label Codes: | 9 | Special provisions: | 8, 146, 335, B54, IB8, IP3, N20, T1, TP33 |

Manganese(II) sulfate monohydrate

sc-203130



The Power is Question

Material Safety Data Sheet

| Hazard Alert Code Key: | | EXTREME | HIGH | MODERATE | LOW |
|--|----------|---------|------|--|----------|
| Packaging: Exceptions: | 155 | | | | 213 |
| Packaging: Exceptions: | 155 | | | Quantity limitations: Passenger aircraft/rail: | No limit |
| Quantity Limitations: Cargo aircraft only: | No limit | | | Vessel stowage: Location: | A |
| Vessel stowage: Other: | None | | | | |

Hazardous materials descriptions and proper shipping names:

Environmentally hazardous substance, solid, n.o.s

Air Transport IATA:

| | | | |
|---------------------|------|--------------------|-----|
| ICAO/IATA Class: | 9 | ICAO/IATA Subrisk: | III |
| UN/ID Number: | 3077 | Packing Group: | III |
| Special provisions: | A97 | | |

Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. *(CONTAINS MANGANESE SULFATE, HYDRATE)

Maritime Transport IMDG:

| | | | |
|---------------------|---------|---------------------|-------------|
| IMDG Class: | 9 | IMDG Subrisk: | None |
| UN Number: | 3077 | Packing Group: | III |
| EMS Number: | F-A,S-F | Special provisions: | 274 909 944 |
| Limited Quantities: | 5 kg | | |

Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.(contains manganese sulfate, hydrate)

Section 15 - REGULATORY INFORMATION

manganese sulfate, hydrate (CAS: 10101-68-5,10034-96-5,15244-36-7) is found on the following regulatory lists;

"Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS (English)", "Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS (French)", "US DOE Temporary Emergency Exposure Limits (TEELs)", "US Food Additive Database"

Section 16 - OTHER INFORMATION

LIMITED EVIDENCE

- Ingestion may produce health damage*.
- Inhalation may produce serious health damage*.
- Cumulative effects may result following exposure*.

*(limited evidence).

Ingredients with multiple CAS Nos

| Ingredient Name | CAS |
|----------------------------|------------------------------------|
| manganese sulfate, hydrate | 10101-68-5, 10034-96-5, 15244-36-7 |

Reasonable care has been taken in the preparation of this information, but the author makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The author makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. For additional technical information please call our toxicology department on +800 CHEMCALL.

- Classification of the mixture and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

Manganese(II) sulfate monohydrate

sc-203130

Material Safety Data Sheet



The Power is Question

Hazard Alert Code Key: **EXTREME** **HIGH** **MODERATE** **LOW**

A list of reference resources used to assist the committee may be found at:
www.chemwatch.net/references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: Feb-23-2008

Print Date:Apr-21-2010