



SZABO SCANDIC

Part of Europa Biosite

Produktinformation



Forschungsprodukte & Biochemikalien



Zellkultur & Verbrauchsmaterial



Diagnostik & molekulare Diagnostik



Laborgeräte & Service

Weitere Information auf den folgenden Seiten!
See the following pages for more information!



Lieferung & Zahlungsart

siehe unsere [Liefer- und Versandbedingungen](#)

Zuschläge

- Mindermengenzuschlag
- Trockeneiszuschlag
- Gefahrgutzuschlag
- Expressversand

SZABO-SCANDIC HandelsgmbH

Quellenstraße 110, A-1100 Wien

T. +43(0)1 489 3961-0

F. +43(0)1 489 3961-7

mail@szabo-scandic.com

www.szabo-scandic.com

[linkedin.com/company/szaboscandic](https://www.linkedin.com/company/szaboscandic) 

Potassium nitrate

sc-203209



The Power is Question

Material Safety Data Sheet

Hazard Alert Code Key:

EXTREME

HIGH

MODERATE

LOW

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

Potassium nitrate

STATEMENT OF HAZARDOUS NATURE

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

NFPA



SUPPLIER

Santa Cruz Biotechnology, Inc.
2145 Delaware Avenue
Santa Cruz, California 95060
800.457.3801 or 831.457.3800

EMERGENCY:

ChemWatch
Within the US & Canada: 877-715-9305
Outside the US & Canada: +800 2436 2255
(1-800-CHEMCALL) or call +613 9573 3112

SYNONYMS

K-N-O3, nitre, niter, "nitric acid, potassium salt", saltpeter, vicknite, "nitrate of potash", Merck, AnalaR, 10214, GPR, 29638, "Ikon potassium nitrate prill", "Ikon potassium nitrate fines"

Section 2 - HAZARDS IDENTIFICATION

CHEMWATCH HAZARD RATINGS

	Min	Max
Flammability:	0	
Toxicity:	2	
Body Contact:	2	
Reactivity:	2	
Chronic:	0	

Min/Nil=0
Low=1
Moderate=2
High=3
Extreme=4



CANADIAN WHMIS SYMBOLS



EMERGENCY OVERVIEW

RISK

Harmful if swallowed.
Irritating to eyes.
Harmful to aquatic organisms.

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

- Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.
- The substance and/or its metabolites may bind to hemoglobin inhibiting normal uptake of oxygen. This condition, known as "methemoglobinemia", is a form of oxygen starvation (anoxia).

EYE

- This material can cause eye irritation and damage in some persons.

SKIN

- The material is not thought to produce adverse health effects or skin irritation following contact (as classified using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.
- There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons.
- Open cuts, abraded or irritated skin should not be exposed to this material.
- Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

INHALED

- Although inhalation is not thought to produce harmful effects, the material may still produce health damage, especially where pre-existing organ (e.g. liver, kidney) damage is evident.
- There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.
- Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.

CHRONIC HEALTH EFFECTS

- Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified using animal models); nevertheless exposure by all routes should be minimized as a matter of course.
- Long term exposure to high dust concentrations may cause changes in lung function i.e. pneumoconiosis; caused by particles less than 0.5 micron penetrating and remaining in the lung.
- Chronic exposure can be harmful if material is ingested and converted to nitrites by bacterial action in the stomach.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
potassium nitrate	7757-79-1	>95

Section 4 - FIRST AID MEASURES

SWALLOWED

· IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY. · Where Medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed otherwise:

EYE

- If this product comes in contact with the eyes: · Wash out immediately with fresh running water. · Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.

SKIN

- If skin contact occurs: · Immediately remove all contaminated clothing, including footwear · Flush skin and hair with running water (and soap if available).

INHALED

· If dust is inhaled, remove from contaminated area. · Encourage patient to blow nose to ensure clear passage of breathing. · If irritation or discomfort persists seek medical attention.

NOTES TO PHYSICIAN

- The toxicity of nitrates and nitrites result from their vasodilating properties and their propensity to form methemoglobin.
- Most produce a peak effect within 30 minutes.
- Clinical signs of cyanosis appear before other symptoms because of the dark pigmentation of methemoglobin.

Section 5 - FIRE FIGHTING MEASURES

Vapour Pressure (mmHG):	Negligible
Upper Explosive Limit (%):	Not applicable
Specific Gravity (water=1):	2.11
Lower Explosive Limit (%):	Not applicable

EXTINGUISHING MEDIA

- FOR SMALL FIRE:
- USE FLOODING QUANTITIES OF WATER.
- DO NOT use dry chemicals, CO2 or foam.

FIRE FIGHTING

- Alert Emergency Responders and tell them location and nature of hazard.
 - Wear breathing apparatus plus protective gloves for fire only.
- When any large container (including road and rail tankers) is involved in a fire, consider evacuation by 800 metres in all directions.

GENERAL FIRE HAZARDS/HAZARDOUS COMBUSTIBLE PRODUCTS

- Will not burn but increases intensity of fire.
 - Heating may cause expansion or decomposition leading to violent rupture of containers.
- Decomposition may produce toxic fumes of: nitrogen oxides (NOx), metal oxides.

FIRE INCOMPATIBILITY

- Avoid storage with reducing agents.
- Avoid any contamination of this material as it is very reactive and any contamination is potentially hazardous.

PERSONAL PROTECTION

Glasses:
Full face- shield.
Gloves:
Respirator:
Particulate

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- Clean up all spills immediately.
- No smoking, naked lights, ignition sources.

MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Emergency Responders and tell them location and nature of hazard.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid personal contact and inhalation of dust, mist or vapors.
- Provide adequate ventilation.

RECOMMENDED STORAGE METHODS

- Glass container.
 - DO NOT repack. Use containers supplied by manufacturer only.
- For low viscosity materials
- Drums and jerricans must be of the non-removable head type.
 - Where a can is to be used as an inner package, the can must have a screwed enclosure.

STORAGE REQUIREMENTS

- In addition, Goods of Class 5.1, packing group III should be stored in packages and be separated from buildings, tanks, and compounds containing other dangerous goods in tanks, and from property boundaries by a distance of at least 5 metres.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION


EXPOSURE CONTROLS

Source	Material	TWA mg/m ³	Notes
--------	----------	-----------------------	-------

US - Oregon Permissible Exposure Limits (Z-3)	potassium nitrate (Inert or Nuisance Dust: Total dust)	10	(d)
US OSHA Permissible Exposure Levels (PELs) - Table Z3	potassium nitrate (Inert or Nuisance Dust: (d) Respirable fraction)	5	
US OSHA Permissible Exposure Levels (PELs) - Table Z3	potassium nitrate (Inert or Nuisance Dust: (d) Total dust)	15	
US - Hawaii Air Contaminant Limits	potassium nitrate (Particulates not otherwise regulated - Total dust)	10	
US - Hawaii Air Contaminant Limits	potassium nitrate (Particulates not otherwise regulated - Respirable fraction)	5	
US - Oregon Permissible Exposure Limits (Z-3)	potassium nitrate (Inert or Nuisance Dust: Respirable fraction)	5	(d)
US ACGIH Threshold Limit Values (TLV)	potassium nitrate (Particles (Insoluble or Poorly Soluble) [NOS] Inhalable particles)	10	See Appendix B current TLV/BEI Book
US - California Permissible Exposure Limits for Chemical Contaminants	potassium nitrate (Particulates not otherwise regulated Respirable fraction)	5	(n)
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	potassium nitrate (Particulates not otherwise regulated Respirable fraction)	5	
US - Michigan Exposure Limits for Air Contaminants	potassium nitrate (Particulates not otherwise regulated, Respirable dust)	5	
Canada - Prince Edward Island Occupational Exposure Limits	potassium nitrate (Particles (Insoluble or Poorly Soluble) [NOS] Inhalable particles)	10	See Appendix B current TLV/BEI Book
US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants	potassium nitrate (Particulates not otherwise regulated (PNOR)(f)-Respirable fraction)	5	

ENDOELTABLE

PERSONAL PROTECTION



RESPIRATOR

Particulate

Consult your EHS staff for recommendations

EYE

- Chemical goggles.
- Full face shield.

HANDS/FEET

- Wear chemical protective gloves, eg. PVC.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: such as:

- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and
- dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739).

- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended.
- When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended.
- Contaminated gloves should be replaced.

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

- DO NOT wear cotton or cotton-backed gloves.
- DO NOT wear leather gloves.
- Promptly hose all spills off leather shoes or boots or ensure that such footwear is protected with PVC over-shoes.

OTHER

- Overalls.
- PVC Apron.

- Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.
- For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets), non sparking safety footwear.

ENGINEERING CONTROLS

- Local exhaust ventilation usually required. If risk of overexposure exists, wear an approved respirator.

<\p>

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL PROPERTIES

Solid.

Mixes with water.

State	Divided solid	Molecular Weight	101.11
Melting Range (°F)	633.2	Viscosity	Not Applicable
Boiling Range (°F)	752 (decomposes)	Solubility in water (g/L)	Miscible
Flash Point (°F)	Not applicable	pH (1% solution)	7 Approx.
Decomposition Temp (°F)	752	pH (as supplied)	Not applicable
Autoignition Temp (°F)	Not available	Vapour Pressure (mmHG)	Negligible
Upper Explosive Limit (%)	Not applicable	Specific Gravity (water=1)	2.11
Lower Explosive Limit (%)	Not applicable	Relative Vapor Density (air=1)	Not available
Volatile Component (%vol)	Not available	Evaporation Rate	Non Volatile

APPEARANCE

Colourless odourless transparent prisms or white crystalline powder or crystals. Has a cooling, pungent saline taste. Slightly hygroscopic. Oxidising agent. Soluble in water and glycerine, insoluble in absolute alcohol. Solubility in water = 36% When tested to UNDG 34.4.2 Test 0.2 Test for oxidising liquids a 30% w/w aqueous solution was not a class 5.1 oxidiser. ref UNDGC 34.4.2.5.

Section 10 - CHEMICAL STABILITY

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable under normal handling conditions.

STORAGE INCOMPATIBILITY

- for metal nitrates:

- Segregate from heavy metals, phosphides, sodium acetate, lead nitrate, tartrates, trichloroethylene,
- Avoid shock and heat.
- Mixtures of metal nitrates with alkyl esters may explode due to the formation of unstable alkyl nitrates.
- Mixtures of a nitrate with phosphorous, tin(II) chloride and other reducing agents may react explosively.
- Mixtures containing nitrates and organic materials are potentially dangerous, especially if acidic materials or heavy metals are present.
- Fibrous organic material, jute, wood and similar cellulosic material can become highly combustible by nitrate impregnation
- Metal nitrates are incompatible with cyanides, thiocyanates, isothiocyanates and hypophosphites. Avoid reaction with the following which can cause an explosion: barium thiocyanate, boron phosphide, cyanides, sodium hypophosphite, sulfur and charcoal, powdered aluminium or aluminium oxide, sodium thiosulfate.
- Mixtures of metal nitrates and phosphinates may explode on heating
- A mixture of aluminium powder, water and metal nitrate may explode due to a self accelerating reaction.
- Mixtures containing nitrates, nitrites and organic materials are potentially dangerous, especially in the presence of acidic materials and heavy metals.
- Metals and their oxides or salts may react violently with chlorine trifluoride and bromine trifluoride.
- These trifluorides are hypergolic oxidisers. They ignites on contact (without external source of heat or ignition) with recognised fuels - contact with these materials, following an ambient or slightly elevated temperature, is often violent and may produce ignition.
- The state of subdivision may affect the results.
- Inorganic reducing agents react with oxidizing agents to generate heat and products that may be flammable, combustible, or otherwise reactive. Their reactions with oxidizing agents may be violent.
- Incidents involving interaction of active oxidants and reducing agents, either by design or accident, are usually very energetic and examples of so-called redox reactions.
- Avoid any contamination of this material as it is very reactive and any contamination is potentially hazardous.

Avoid storage with reducing agents.

Segregate from reducing agents, strong acids, organic substances, combustible materials, heavy metals, phosphides, sodium acetate, lead nitrate, tartrates, trichloroethylene, shock and heat.

A mixture with calcium silicide is easily ignited and burns at very high temperatures which is capable of initiating many high temperature reactions. Mixtures of potassium nitrate with: titanium, antimony, germanium or zirconium powders, antimony trisulfide, barium sulfide, calcium sulfide, arsenic disulfide, titanium disulfide, germanium monosulfide, molybdenum disulfide, powdered carbon, arsenic, white or red phosphorus, boron phosphide, copper phosphides, sodium phosphinate, sodium acetate, sodium thiosulfate, thorium dicarbide, aluminium, magnesium, sodium or iron, chromium nitride: may explode or detonate on heating, ignition or by shock.

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

POTASSIUM NITRATE

TOXICITY AND IRRITATION

POTASSIUM NITRATE:

■ unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY	IRRITATION
Oral (rat) LD50: 3750 mg/kg	Nil Reported
Oral (rabbit) LD50: 1901 mg/kg	

Section 12 - ECOLOGICAL INFORMATION

Harmful to aquatic organisms.

This material and its container must be disposed of as hazardous waste.

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
potassium nitrate	LOW		LOW	HIGH

Section 13 - DISPOSAL CONSIDERATIONS

US EPA Waste Number & Descriptions

A. General Product Information

Ignitability characteristic: use EPA hazardous waste number D001 (waste code I)

Disposal Instructions

All waste must be handled in accordance with local, state and federal regulations.

! Puncture containers to prevent re-use and bury at an authorized landfill.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- Reuse
- Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

DO NOT allow wash water from cleaning equipment to enter drains. Collect all wash water for treatment before disposal.

For small quantities of oxidizing agent:

- Cautiously acidify a 3% solution to pH 2 with sulfuric acid.
- Gradually add a 50% excess of sodium bisulfite solution with stirring.
- Recycle wherever possible or consult manufacturer for recycling options.
- Consult Waste Management Authority for disposal.

Section 14 - TRANSPORTATION INFORMATION

DOT:

Symbols: None Hazard class or Division: 5.1

Identification Numbers: UN1486 PG: III

Label Codes: 5.1 Special provisions: A1, A29,

IB8, IP3,

T1, TP33

Packaging: Exceptions: 152 Packaging: Non- bulk: 213

Packaging: Exceptions: 152 Quantity limitations: 25 kg

Passenger aircraft/rail:

Quantity Limitations: Cargo 100 kg Vessel stowage: Location: A

aircraft only:

Vessel stowage: Other: None

Hazardous materials descriptions and proper shipping names:

Potassium nitrate

Air Transport IATA:

ICAO/IATA Class: 5.1 ICAO/IATA Subrisk: None
UN/ID Number: 1486 Packing Group: III
Special provisions: None
Cargo Only
Packing Instructions: 518 Maximum Qty/Pack: 100 kg
Passenger and Cargo Passenger and Cargo
Packing Instructions: 516 Maximum Qty/Pack: 25 kg
Passenger and Cargo Limited Quantity Passenger and Cargo Limited Quantity
Packing Instructions: Y516 Maximum Qty/Pack: 10 kg
Shipping Name: POTASSIUM NITRATE

Maritime Transport IMDG:

IMDG Class: 5.1 IMDG Subrisk: None
UN Number: 1486 Packing Group: III
EMS Number: F-A , S-Q Special provisions: None
Limited Quantities: 5 kg
Shipping Name: POTASSIUM NITRATE

Section 15 - REGULATORY INFORMATION

potassium nitrate (CAS: 7757-79-1) is found on the following regulatory lists;

"Canada - Saskatchewan Industrial Hazardous Substances", "Canada Domestic Substances List (DSL)", "Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS (English)", "International Council of Chemical Associations (ICCA) - High Production Volume List", "OECD Representative List of High Production Volume (HPV) Chemicals", "US - New Jersey Right to Know Hazardous Substances", "US - Pennsylvania - Hazardous Substance List", "US - Rhode Island Hazardous Substance List", "US Department of Homeland Security Chemical Facility Anti-Terrorism Standards - Chemicals of Interest", "US DOE Temporary Emergency Exposure Limits (TEELs)", "US EPA High Production Volume Chemicals Additional List", "US Food Additive Database", "US Toxic Substances Control Act (TSCA) - Inventory", "USA: Chemical Facility Anti-Terrorism Standards - List Appendix A - 6CFR 27"

Section 16 - OTHER INFORMATION

LIMITED EVIDENCE

- Contact with air may produce sufficient heat to ignite combustible materials.*.
- May produce discomfort of the respiratory system and skin*.

* (limited evidence).

Reasonable care has been taken in the preparation of this information, but the author makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The author makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. For additional technical information please call our toxicology department on +800 CHEMCALL.

- Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:
www.chemwatch.net/references.

- The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: Jul-21-2010

Print Date: Oct-28-2010