

Produktinformation



Forschungsprodukte & Biochemikalien



Zellkultur & Verbrauchsmaterial



Diagnostik & molekulare Diagnostik



Laborgeräte & Service

Weitere Information auf den folgenden Seiten! See the following pages for more information!



Lieferung & Zahlungsart

siehe unsere Liefer- und Versandbedingungen

Zuschläge

- Mindermengenzuschlag
- Trockeneiszuschlag
- Gefahrgutzuschlag
- Expressversand

SZABO-SCANDIC HandelsgmbH

Quellenstraße 110, A-1100 Wien

T. +43(0)1 489 3961-0

F. +43(0)1 489 3961-7

mail@szabo-scandic.com

www.szabo-scandic.com

linkedin.com/company/szaboscandic in



Zinc bromide

sc-203416

Material Safety Data Sheet



Hazard Alert Code Key: EXTREME HIGH MODERATE LOW

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

Zinc bromide

STATEMENT OF HAZARDOUS NATURE

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

NFPA



SUPPLIER

Santa Cruz Biotechnology, Inc. 2145 Delaware Avenue Santa Cruz, California 95060 800.457.3801 or 831.457.3800

EMERGENCY:

ChemWatch

Within the US & Canada: 877-715-9305 Outside the US & Canada: +800 2436 2255 (1-800-CHEMCALL) or call +613 9573 3112

SYNONYMS

Zn-Br2, Br2-Zn, "zinc dibromide"

Section 2 - HAZARDS IDENTIFICATION

CHEMWATCH HAZARD RATINGS

Min Max Flammability: 0 Toxicity: 2 Min/Nil=0 **Body Contact:** 4 Reactivity: Moderate=2 0 High=3 Chronic: 3 Extreme=4





CANADIAN WHMIS SYMBOLS





EMERGENCY OVERVIEW

RISK

Causes severe burns.

Risk of serious damage to eyes.

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

- Ingestion of acidic corrosives may produce burns around and in the mouth. the throat and esophagus. <\p>.
- Accidental ingestion of the material may be damaging to the health of the individual.
- Soluble zinc salts produces irritation and corrosion of the alimentary tract with pain, and vomiting. Death can occur due to insufficiency of food intake due to severe narrowing of the esophagus and pylorus.
- Bromide poisoning causes intense vomiting so the dose is often removed. Effects include drowsiness, irritability, inco-ordination, vertigo, confusion, mania, hallucinations and coma.
- The material can produce severe chemical burns within the oral cavity and gastrointestinal tract following ingestion.

EYE

- If applied to the eyes, this material causes severe eye damage.
- Direct eye contact with acid corrosives may produce pain, tears, sensitivity to light and burns. Mild burns of the epithelia generally recover rapidly and completely. <\p>.
- The material can produce severe chemical burns to the eye following direct contact. Vapors or mists may be extremely irritating.

SKIN

- Skin contact with acidic corrosives may result in pain and burns; these may be deep with distinct edges and may heal slowly with the formation of scar tissue.
- Skin contact is not thought to have harmful health effects, however the material may still produce health damage following entry through wounds, lesions or abrasions.
- Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
- The material can produce severe chemical burns following direct contactwith the skin.

INHALED

- The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.
- Corrosive acids can cause irritation of the respiratory tract, with coughing, choking and mucous membrane damage. There may be dizziness, headache, nausea and weakness.
- Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.

CHRONIC HEALTH EFFECTS

■ Repeated or prolonged exposure to acids may result in the erosion of teeth, swelling and or ulceration of mouth lining. Irritation of airways to lung, with cough, and inflammation of lung tissue often occurs.

Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems. Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.

There is some evidence that human exposure to the material may result in developmental toxicity. This evidence is based on animal studies where effects have been observed in the absence of marked maternal toxicity, or at around the same dose levels as other toxic effects but which are not secondary non-specific consequences of the other toxic effects.

Long term exposure to high dust concentrations may cause changes in lung function i.e. pneumoconiosis; caused by particles less than 0.5 micron penetrating and remaining in the lung.

<\p>.

Chronic intoxication with ionic bromides, historically, has resulted from medical use of bromides but not from environmental or occupational exposure; depression, hallucinosis, and schizophreniform psychosis can be seen in the absence of other signs of intoxication. Bromides may also induce sedation, irritability, agitation, delirium, memory loss, confusion, disorientation, forgetfulness (aphasias), dysarthria, weakness, fatigue, vertigo, stupor, coma, decreased appetite, nausea and vomiting, diarrhoea, hallucinations, an acne like rash on the face, legs and trunk, known as bronchoderma (seen in 25-30% of case involving bromide ion), and a profuse discharge from the nostrils (coryza). Ataxia and generalised hyperreflexia have also been observed. Correlation of neurologic symptoms with blood levels of bromide is inexact. The use of substances such as brompheniramine, as antihistamines, largely reflect current day usage of bromides; ionic bromides have been largely withdrawn from therapeutic use due to their toxicity. Several cases of foetal abnormalities have been described in mothers who took large doses of bromides during pregnancy.

Welding or flame cutting of metals with zinc or zinc dust coatings may result in inhalation of zinc oxide fume; high concentrations of zinc oxide fume may result in "metal fume fever"; also known as "brass chills", an industrial disease of short duration. [I.L.O] Symptoms include malaise, fever, weakness, nausea and may appear quickly if operations occur in enclosed or poorly ventilated areas.

Pregnant women exposed to bromide poisoning may pass on symptoms to their offspring.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME CAS RN %

zinc bromide 7699-45-8 > 97

hydrolysis produces

hydrogen bromide 10035-10-6

Section 4 - FIRST AID MEASURES

SWALLOWED

· For advice, contact a Poisons Information Center or a doctor at once. · Urgent hospital treatment is likely to be needed.

FYF

■ If this product comes in contact with the eyes: · Immediately hold eyelids apart and flush the eye continuously with running water. · Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.

SKIN

■ If skin or hair contact occurs: · Immediately flush body and clothes with large amounts of water, using safety shower if available. · Quickly remove all contaminated clothing, including footwear.

INHALED

· If fumes or combustion products are inhaled remove from contaminated area. · Lay patient down. Keep warm and rested.

NOTES TO PHYSICIAN

- For acute or short term repeated exposures to strong acids:
- · Airway problems may arise from laryngeal edema and inhalation exposure. Treat with 100% oxygen initially.
- Respiratory distress may require cricothyroidotomy if endotracheal intubation is contraindicated by excessive swelling.

Treatment of intoxication by the bromide ion includes hydration, the maintenance of mild water diuresis, and sodium, or even better, ammonium chloride (10-15 gm. daily in divided doses) with an osmotic or high ceiling diuretic.

Treat symptomatically. For ingestion, give large amounts of water followed by prompt and complete gastric lavage, catharsis and demulcents. [Ajax]

| Section 5 - FIRE FIGHTING MEASURES | | | | |
|------------------------------------|-----------------|--|--|--|
| Vapour Pressure (mmHG): | Not applicable. | | | |
| Upper Explosive Limit (%): | Not applicable | | | |
| Specific Gravity (water=1): | 4.22 | | | |
| Lower Explosive Limit (%): | Not applicable | | | |

EXTINGUISHING MEDIA

- · Water spray or fog.
- · Foam.

FIRE FIGHTING

- · Alert Emergency Responders and tell them location and nature of hazard.
- · Wear full body protective clothing with breathing apparatus.

When any large container (including road and rail tankers) is involved in a fire, consider evacuation by 800 metres in all directions.

GENERAL FIRE HAZARDS/HAZARDOUS COMBUSTIBLE PRODUCTS

- · Non combustible.
- · Not considered to be a significant fire risk.

Decomposition may produce toxic fumes of: hydrogen bromide, metal oxides.

FIRE INCOMPATIBILITY

■ None known.

PERSONAL PROTECTION

Glasses:

Full face- shield.

Gloves:

Respirator:

Type B-P Filter of sufficient capacity

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- · Remove all ignition sources.
- · Clean up all spills immediately.
- · Avoid contact with skin and eyes.
- · Control personal contact by using protective equipment.
- · Use dry clean up procedures and avoid generating dust.
- · Place in a suitable, labelled container for waste disposal.

MAJOR SPILLS

- · Clear area of personnel and move upwind.
- · Alert Emergency Responders and tell them location and nature of hazard.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- \cdot Avoid all personal contact, including inhalation.
- · Wear protective clothing when risk of exposure occurs.

RECOMMENDED STORAGE METHODS

■ DO NOT use aluminum or galvanized containers.

Check regularly for spills and leaks.

Glass container.

- · Lined metal can, Lined metal pail/drum
- · Plastic pail.

For low viscosity materials

- · Drums and jerricans must be of the non-removable head type.
- · Where a can is to be used as an inner package, the can must have a screwed enclosure.

STORAGE REQUIREMENTS

- · Store in original containers.
- · Keep containers securely sealed.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

| Source | Material | TWA ppm | TWA mg/m³ | STEL ppm | STEL mg/m³ | Peak ppm | Peak mg/m³ | Notes |
|---|---|---------|-----------|----------|---------------|----------|------------|---|
| | | | | | | | | |
| US - Oregon Permissible Exposure Limits (Z-3) | zinc bromide (Inert or Nuisance Dust: Total dust) | | 10 | | | | | (d) |
| US OSHA Permissible Exposure Levels (PELs) - Table Z3 | zinc bromide (Inert or Nuisance Dust: (d) Respirable fraction) | | 5 | | | | | |
| US OSHA Permissible Exposure Levels (PELs) - Table Z3 | zinc bromide (Inert or Nuisance Dust: (d) Total dust) | | 15 | | | | | |
| US - Hawaii Air Contaminant Limits | zinc bromide (Particulates not other wise regulated - Total dust) | | 10 | | | | | |
| US - Hawaii Air Contaminant Limits | zinc bromide (Particulates not other wise regulated - Respirable fraction) | | 5 | | | | | |
| US - Oregon Permissible Exposure Limits (Z-3) | zinc bromide (Inert or Nuisance Dust: Respirable fraction) | | 5 | | | | | (d) |
| US ACGIH Threshold Limit Values (TLV) | zinc bromide (Particles (Insoluble or Poorly Soluble) [NOS] Inhalable particles) | | 10 | | | | | See Appendix B current TLV/BEI Book |
| US - California Permissible Exposure Limits for Chemical | zinc bromide (Particulates not otherwise regulated | | 5 | | | | | (n) |

| Contaminants | Respirable fraction) | | | | | |
|---|---|---|----|---|-----|--|
| US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants | zinc bromide (Particulates not otherwise regulated Respirable fraction) | | 5 | | | |
| US - Michigan Exposure Limits for Air Contaminants | zinc bromide (Particulates not otherwise regulated, Respirable dust) | | 5 | | | |
| Canada - Prince Edward Island Occupational Exposure Limits | zinc bromide (Particles (Insoluble or Poorly Soluble) [NOS] Inhalable particles) | | 10 | | | See Appendix B current TLV/BEI Book |
| US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants | otherwise | | 5 | | | |
| Canada - Alberta Occupational Exposure Limits | hydrogen bromide (Hydrogen bromide) | | | 2 | 6.6 | |
| Canada - British Columbia Occupational Exposure Limits | hydrogen bromide (Hydrogen bromide Revised 2004) | | | 2 | | |
| Canada - Ontario Occupational Exposure Limits | hydrogen bromide (Hydrogen bromide) | | | 2 | | |
| US OSHA Permissible Exposure Levels (PELs) - Table Z1 | hydrogen bromide (Hydrogen bromide) | 3 | 10 | | | |
| US ACGIH Threshold Limit Values (TLV) | hydrogen bromide (Hydrogen bromide) | | | 2 | | TLV Basis: upper respiratory tract irritation |
| US NIOSH Recommended Exposure Limits (RELs) | hydrogen bromide (Hydrogen bromide) | | | 3 | 10 | |
| US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants | hydrogen bromide (Hydrogen bromide) | | | 3 | 10 | |
| US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants | hydrogen bromide (Hydrogen bromide) | 3 | 10 | | | |
| US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants | hydrogen bromide (Hydrogen bromide) | | | 3 | 10 | |

| US - Minnesota Permissible Exposure Limits (PELs) | hydrogen bromide (Hydrogen bromide) | | | | | 3 | 10 | |
|--|---|---|-----|---|----|-----|-----|--|
| US - California Permissible Exposure Limits for Chemical Contaminants | hydrogen bromide (Hydrogen bromide) | 3 | 10 | | | С | | |
| US - Idaho - Limits for Air Contaminants | hydrogen bromide (Hydrogen bromide) | 3 | 10 | | | | | |
| US - Hawaii Air Contaminant Limits | hydrogen bromide (Hydrogen bromide) | | | | | 3 | 10 | |
| US - Alaska Limits for Air Contaminants | hydrogen bromide (Hydrogen bromide) | | | | | 3 | 10 | |
| US - Michigan Exposure Limits for Air Contaminants | hydrogen bromide (Hydrogen bromide) | | | | | 3 | 10 | |
| Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances | hydrogen bromide (Hydrogen bromide) | 3 | 10 | 3 | 10 | | | |
| US - Washington Permissible exposure limits of air contaminants | hydrogen bromide (Hydrogen bromide) | | | | | 3.0 | | |
| Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits | hydrogen bromide (Hydrogen bromide) | | | | | 2 | | |
| Canada - Prince Edward Island Occupational Exposure Limits | hydrogen bromide (Hydrogen bromide) | | | | | 2 | | TLV Basis: upper respiratory tract irritation |
| US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants | hydrogen bromide (Hydrogen bromide) | 3 | 10 | | | | | |
| Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English) | hydrogen bromide (Hydrogen bromide) | | | | | 3 | 9,9 | |
| US - Oregon Permissible Exposure Limits (Z-1) | hydrogen bromide (Hydrogen bromide) | 3 | 10 | | | | | |
| Canada - Northwest Territories Occupational Exposure Limits (English) | hydrogen bromide (Hydrogen bromide) | 3 | 9.9 | 6 | 20 | | | |
| Canada - Nova Scotia Occupational Exposure Limits ENDOELTABLE | hydrogen bromide (Hydrogen bromide) | | | | | 2 | | TLV Basis: upper respiratory tract irritation |

PERSONAL PROTECTION











RESPIRATOR

Type B-P Filter of sufficient capacity
Consult your EHS staff for recommendations

EYE

- · Chemical goggles.
- · Full face shield.

HANDS/FEET

■ Elbow length PVC gloves.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: such as:

- · frequency and duration of contact,
- · chemical resistance of glove material,
- · glove thickness and
- · dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739).

- · When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended.
- · When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended.
- · Contaminated gloves should be replaced.

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

OTHER

- · Overalls.
- · PVC Apron.

ENGINEERING CONTROLS

■ Local exhaust ventilation usually required. If risk of overexposure exists, wear an approved respirator. <\p>.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL PROPERTIES

Mixes with water.

Corrosive. Acid.

| State | DIVIDED SOLID | Molecular Weight | 225.19 |
|---------------------------|---------------------|--------------------------------|-----------------|
| Melting Range (°F) | 741.2 | Viscosity | Not Applicable |
| Boiling Range (°F) | 1286.6 (decomposes) | Solubility in water (g/L) | Miscible |
| Flash Point (°F) | Not applicable | pH (1% solution) | 4 approx. |
| Decomposition Temp (°F) | Not Applicable | pH (as supplied) | Not applicable |
| Autoignition Temp (°F) | Not applicable | Vapour Pressure (mmHG) | Not applicable. |
| Upper Explosive Limit (%) | Not applicable | Specific Gravity (water=1) | 4.22 |
| Lower Explosive Limit (%) | Not applicable | Relative Vapor Density (air=1) | Not applicable. |
| Volatile Component (%vol) | Not applicable. | Evaporation Rate | Not applicable |

APPEARANCE

Odourless white hygroscopic crystalline powder with sharp metallic taste. Soluble in water, alcohol and ether.

Section 10 - CHEMICAL STABILITY

CONDITIONS CONTRIBUTING TO INSTABILITY

- · Contact with alkaline material liberates heat.
- · Presence of incompatible materials.
- · Product is considered stable.

STORAGE INCOMPATIBILITY

- · WARNING: Avoid or control reaction with peroxides. All transition metal peroxides should be considered as potentially explosive. For example transition metal complexes of alkyl hydroperoxides may decompose explosively.
- · The pi-complexes formed between chromium(0), vanadium(0) and other transition metals (haloarene-metal complexes) and mono-or poly-fluorobenzene show extreme sensitivity to heat and are explosive.
- · Avoid reaction with borohydrides or cyanoborohydrides.
- Avoid strong bases.
- Inorganic acids are generally soluble in water with the release of hydrogen ions. The resulting solutions have pH's of less than 7.0.
- · Inorganic acids neutralize chemical bases (for example: amines and inorganic hydroxides) to form salts.
- Metals and their oxides or salts may react violently with chlorine trifluoride and bromine trifluoride.
- · These trifluorides are hypergolic oxidisers. They ignites on contact (without external source of heat or ignition) with recognised fuels contact with these materials, following an ambient or slightly elevated temperature, is often violent and may produce ignition.
- · The state of subdivision may affect the results.

Avoid storage with sodium and potassium.

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

ZINC BROMIDE

TOXICITY AND IRRITATION

- unless otherwise specified data extracted from RTECS Register of Toxic Effects of Chemical Substances.
- Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.

ZINC BROMIDE:

■ No significant acute toxicological data identified in literature search.

| TOXICITY | IRRITATION |
|----------|------------|
| | |

HYDROGEN BROMIDE:

Inhalation (rat) LC50: 2858 ppm/1h. Nil Reported

CARCINOGEN

| BROMINE COMPOUNDS (ORGANIC OR INORGANIC) | US Environmental Defense Scorecard Suspected Carcinogens | Reference(s) | P65-MC |
|--|--|--------------|--------|
| INORGANIC BROMINE COMPOUNDS | US Environmental Defense Scorecard Suspected Carcinogens | Reference(s) | P65-MC |

Section 12 - ECOLOGICAL INFORMATION

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

This material and its container must be disposed of as hazardous waste.

Avoid release to the environment.

Refer to special instructions/ safety data sheets.

GESAMP/EHS COMPOSITE LIST - GESAMP Hazard Profiles

Legend: EHS=EHS Number (EHS=GESAMP Working Group on the Evaluation of the Hazards of Harmful Substances Carried by Ships) NRT=Net Register Tonnage, A1a=Bioaccumulation log Pow, A1b=Bioaccumulation BCF, A1=Bioaccumulation, A2=Biodegradation, B1=Acuteaquatic toxicity LC/ECIC50 (mg/l), B2=Chronic aquatic toxicity NOEC (mg/l), C1=Acute mammalian oral toxicity LD50 (mg/kg), C2=Acutemammalian dermal toxicity LD50 (mg/kg), C3=Acute mammalian inhalation toxicity LC50 (mg/kg), D1=Skin irritation & corrosion, D2=Eye irritation & corrosion, D3=Long-term health effects, E1=Tainting, E2=Physical effects on wildlife & benthic habitats, E3=Interference with coastal amenities, For column A2: R=Readily biodegradable, NR=Not readily biodegradable. For column D3: C=Carcinogen, M=Mutagenic, R=Reprotoxic, S=Sensitising, A=Aspiration hazard, T=Target organ systemic toxicity, L=Lunginjury, N=Neurotoxic, I=Immunotoxic. For column E1: NT=Not tainting (tested), T=Tainting test positive. For column E2: Fp=Persistent floater, F=Floater, S=Sinking substances. The numerical scales start from 0 (no hazard), while higher numbers reflect increasing hazard. (GESAMP/EHS Composite List of Hazard Profiles - Hazard evaluation of substances transported by ships)

Section 13 - DISPOSAL CONSIDERATIONS

US EPA Waste Number & Descriptions

A. General Product Information

Corrosivity characteristic: use EPA hazardous waste number D002 (waste code C)

Disposal Instructions

All waste must be handled in accordance with local, state and federal regulations.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- · Reduction
- · Reuse
- · Recycling
- · Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

DO NOT allow wash water from cleaning equipment to enter drains. Collect all wash water for treatment before disposal.

- · Recycle wherever possible.
- · Consult manufacturer for recycling options or consult Waste Management Authority for disposal if no suitable treatment or disposal facility can be identified

Section 14 - TRANSPORTATION INFORMATION



DOT:

Symbols: None Hazard class or Division: 8 Identification Numbers: UN3260 PG: II Label Codes: 8 Special provisions: IB8, IP2,

IP4, T3, TP33

Packaging: Exceptions: 154 Packaging: Non- bulk: 212 Packaging: Exceptions: 154 Quantity limitations: 15 kg

Passenger aircraft/rail:

Quantity Limitations: Cargo 50 kg Vessel stowage: Location: B

aircraft only:

Vessel stowage: Other: None S.M.P.: YES

Hazardous materials descriptions and proper shipping names:

Corrosive solid, acidic, inorganic, n.o.s.

Air Transport IATA:

ICAO/IATA Class: 8 ICAO/IATA Subrisk: None UN/ID Number: 3260 Packing Group: II

Special provisions: A3

Cargo Only

Packing Instructions: 816 Maximum Qty/Pack: 50 kg Passenger and Cargo Passenger and Cargo Packing Instructions: 814 Maximum Qty/Pack: 15 kg

Passenger and Cargo Limited Quantity Passenger and Cargo Limited Quantity

Packing Instructions: Y814 Maximum Qty/Pack: 5 kg

Shipping Name: CORROSIVE SOLID, ACIDIC, INORGANIC, N.O.S.

*(CONTAINS ZINC BROMIDE)

Maritime Transport IMDG:

IMDG Class: 8 IMDG Subrisk: None UN Number: 3260 Packing Group: II

EMS Number: F-A, S-B Special provisions: 274 Limited Quantities: 1 kg Marine Pollutant: Yes

Shipping Name: CORROSIVE SOLID, ACIDIC, INORGANIC, N.O.S.(contains zinc bromide)

Section 15 - REGULATORY INFORMATION

zinc bromide (CAS: 7699-45-8) is found on the following regulatory lists;

"Canada Domestic Substances List (DSL)","GESAMP/EHS Composite List - GESAMP Hazard Profiles","US - California Occupational Safety and Health Regulations (CAL/OSHA) - Hazardous Substances List","US - Massachusetts Oil & Hazardous Material List","US - New Jersey Right to Know Hazardous Substances","US - Pennsylvania - Hazardous Substance List","US CWA (Clean Water Act) - List of Hazardous

Substances","US CWA (Clean Water Act) - Reportable Quantities of Designated Hazardous Substances","US Department of Transportation (DOT) List of Hazardous Substances and Reportable Quantities - Hazardous Substances Other Than Radionuclides","US Department of Transportation (DOT) Marine Pollutants - Appendix B","US DOE Temporary Emergency Exposure Limits (TEELs)","US List of Lists - Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112(r) of the Clean Air Act","US Toxic Substances Control Act (TSCA) - Inventory"

Regulations for ingredients

hydrogen bromide (CAS: 10035-10-6) is found on the following regulatory lists;

"Canada - Alberta Occupational Exposure Limits", "Canada - British Columbia Occupational Exposure Limits", "Canada - Northwest Territories Occupational Exposure Limits (English)","Canada - Nova Scotia Occupational Exposure Limits","Canada - Ontario Occupational Exposure Limits", "Canada - Prince Edward Island Occupational Exposure Limits", "Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)","Canada - Saskatchewan Industrial Hazardous Substances","Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits", "Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances", "Canada Domestic Substances List (DSL)","Canada Ingredient Disclosure List (SOR/88-64)","Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS (English)","International Council of Chemical Associations (ICCA) - High Production Volume List", "OECD Representative List of High Production Volume (HPV) Chemicals", "US - Alaska Limits for Air Contaminants", "US -California Occupational Safety and Health Regulations (CAL/OSHA) - Hazardous Substances List", "US - California Permissible Exposure Limits for Chemical Contaminants", "US - Connecticut Hazardous Air Pollutants", "US - Hawaii Air Contaminant Limits", "US - Idaho - Limits for Air Contaminants","US - Massachusetts Oil & Hazardous Material List","US - Michigan Exposure Limits for Air Contaminants","US -Minnesota Hazardous Substance List", "US - Minnesota Permissible Exposure Limits (PELs)", "US - New Jersey Right to Know Hazardous Substances","US - Oregon Hazardous Materials","US - Oregon Permissible Exposure Limits (Z-1)","US - Pennsylvania - Hazardous Substance List","US - Rhode Island Hazardous Substance List","US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants", "US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants", "US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants","US - Washington Permissible exposure limits of air contaminants","US - Wyoming List of Highly Hazardous Chemicals, Toxics and Reactives", "US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants","US ACGIH Threshold Limit Values (TLV)","US Department of Homeland Security Chemical Facility Anti-Terrorism Standards - Chemicals of Interest", "US DOE Temporary Emergency Exposure Limits (TEELs)", "US EPA Acute Exposure Guideline Levels (AEGLs) - Interim", "US EPA High Production Volume Chemicals Additional List", "US NFPA 45 Fire Protection for Laboratories Using Chemicals - Flammability Characteristics of Common Compressed and Liquefied Gases", "US NIOSH Recommended Exposure Limits (RELs)","US OSHA List of Highly Hazardous Chemicals, Toxics and Reactives","US OSHA Permissible Exposure Levels (PELs) - Table Z1","US Postal Service (USPS) Hazardous Materials Table: Postal Service Mailability Guide","US Toxic Substances Control Act (TSCA) -Inventory"

Section 16 - OTHER INFORMATION

LIMITED EVIDENCE

- Ingestion may produce health damage*.
- Cumulative effects may result following exposure*.
- May be harmful to the foetus/ embryo*.
- * (limited evidence).

Reasonable care has been taken in the preparation of this information, but the author makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The author makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. For additional technical information please call our toxicology department on +800 CHEMCALL.

- Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

 A list of reference resources used to assist the committee may be found at:

 www.chemwatch.net/references.
- The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: Feb-26-2008 Print Date:Nov-9-2010