

# Produktinformation



Forschungsprodukte & Biochemikalien
Zellkultur & Verbrauchsmaterial
Diagnostik & molekulare Diagnostik
Laborgeräte & Service

Weitere Information auf den folgenden Seiten! See the following pages for more information!



Lieferung & Zahlungsart siehe unsere Liefer- und Versandbedingungen


# Zuschläge

- Mindermengenzuschlag
- Trockeneiszuschlag
- Gefahrgutzuschlag
- Expressversand

# SZABO-SCANDIC HandelsgmbH

Quellenstraße 110, A-1100 Wien T. +43(0)1 489 3961-0 F. +43(0)1 489 3961-7 <u>mail@szabo-scandic.com</u> www.szabo-scandic.com

# Riboflavin




# SUPPLIER

Santa Cruz Biotechnology, Inc. 2145 Delaware Avenue Santa Cruz, California 95060 800.457.3801 or 831.457.3800 **EMERGENCY** ChemWatch Within the US & Canada: 877-715-9305 Outside the US & Canada: +800 2436 2255 (1-800-CHEMCALL) or call +613 9573 3112

# SYNONYMS

C17-H20-N4-O6, Riboflavine, "Vitamin G", Beflavine, Flavaxin, "Food Colour E101", "7, 8-dimethyl-10-(D-ribo-2, 3, 4, 5-tetrahydroxy-pentyl-isoalloxane", "7, 8-dimethyl-10-D-ribityl-isoalloxazine", Riboflavinequinone





#### **EMERGENCY OVERVIEW**

#### RISK

Irritating to eyes, respiratory system and skin.

# POTENTIAL HEALTH EFFECTS

# ACUTE HEALTH EFFECTS

#### SWALLOWED

■ The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.

EYE

This material can cause eye irritation and damage in some persons.

SKIN

This material can cause inflammation of the skin oncontact in some persons.

The material may accentuate any pre-existing dermatitis condition.

Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.

Open cuts, abraded or irritated skin should not be exposed to this material.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects.

Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

# INHALED

The material can cause respiratory irritation in some persons.

The body's response to such irritation can cause further lung damage.

■ Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.

If prior damage to the circulatory or nervous systems has occurred or if kidney damage has been sustained, proper screenings should be conducted on individuals who may be exposed to further risk if handling and use of the material result in excessive exposures.

# **CHRONIC HEALTH EFFECTS**

• Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems.

Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

Long term exposure to high dust concentrations may cause changes in lung function i.e. pneumoconiosis; caused by particles less than 0.5 micron penetrating and remaining in the lung. Prime symptom is breathlessness; lung shadows show on X-ray.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS									
NAME		CAS RN	%						
riboflavin		83-88-5	>90						

# Section 4 - FIRST AID MEASURES

# SWALLOWED

- Immediately give a glass of water.
- First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

EYE

If this product comes in contact with the eyes

- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Seek medical attention without delay; if pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

# SKIN

If skin contact occurs

• Immediately remove all contaminated clothing, including footwear.

- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

#### INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.

#### NOTES TO PHYSICIAN

Treat symptomatically.

# **Section 5 - FIRE FIGHTING MEASURES**

Vapour Pressure (mmHG)	Not applicable
Upper Explosive Limit (%)	Not available.
Specific Gravity (water=1)	Not available.
Lower Explosive Limit (%)	Not available.

#### EXTINGUISHING MEDIA

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

#### FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use water delivered as a fine spray to control fire and cool adjacent area.

# GENERAL FIRE HAZARDS/HAZARDOUS COMBUSTIBLE PRODUCTS

- Combustible solid which burns but propagates flame with difficulty; it is estimated that most organic dusts are combustible (circa 70%) according to the circumstances under which the combustion process occurs, such materials may cause fires and / or dust explosions.
- Avoid generating dust, particularly clouds of dust in a confined or unventilated space as dusts may form an explosive mixture with air, and any source of ignition, i.e. flame or spark, will cause fire or explosion. Dust clouds generated by the fine grinding of the solid are a particular hazard; accumulations of fine dust (420 micron or less) may burn rapidly and fiercely if ignited particles exceeding this limit will generally not form flammable dust clouds.; once initiated, however, larger particles up to 1400 microns diameter will contribute to the propagation of an explosion.
- In the same way as gases and vapours, dusts in the form of a cloud are only ignitable over a range of concentrations; in principle, the concepts of lower explosive limit (LEL) and upper explosive limit (UEL).are applicable to dust clouds but only the LEL is of practical use; - this is because of the inherent difficulty of achieving homogeneous dust clouds at high temperatures (for dusts the LEL is often called the "Minimum Explosible Concentration", MEC)
- A dust explosion may release of large quantities of gaseous products; this in turn creates a subsequent pressure rise of explosive force capable of damaging plant and buildings and injuring people.

Combustion products include carbon monoxide (CO), carbon dioxide (CO2), nitrogen oxides (NOx), other pyrolysis products typical of burning organic material.

#### May emit poisonous fumes.

May emit corrosive fumes.

#### FIRE INCOMPATIBILITY

• Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

#### Section 6 - ACCIDENTAL RELEASE MEASURES

# MINOR SPILLS

- Clean up all spills immediately.
- Avoid breathing dust and contact with skin and eyes.
- Wear protective clothing, gloves, safety glasses and dust respirator.
- Use dry clean up procedures and avoid generating dust.

# MAJOR SPILLS

Moderate hazard.

- CAUTION Advise personnel in area.
- Alert Emergency Services and tell them location and nature of hazard.
- Control personal contact by wearing protective clothing.

Prevent, by any means available, spillage from entering drains or water courses.

# Section 7 - HANDLING AND STORAGE

## **PROCEDURE FOR HANDLING**

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.

Empty containers may contain residual dust which has the potential to accumulate following settling. Such dusts may explode in the presence of an appropriate ignition source.

- Do NOT cut, drill, grind or weld such containers.
- In addition ensure such activity is not performed near full, partially empty or empty containers without appropriate workplace safety authorisation or permit.

# **RECOMMENDED STORAGE METHODS**

- Glass container is suitable for laboratory quantities
- Polyethylene or polypropylene container.
- Check all containers are clearly labelled and free from leaks.
- STORAGE REQUIREMENTS
- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.

# Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

# EXPOSURE CONTROLS

The following materials had no OELs on our records

• riboflavin CAS83-88-5

# PERSONAL PROTECTION



# RESPIRATOR

• Particulate. (AS/NZS 1716 & 1715, EN 1432000 & 1492001, ANSI Z88 or national equivalent)

#### EYE

- Safety glasses with side shields.
- · Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]

## HANDS/FEET

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include

- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and
- dexterity

Experience indicates that the following polymers are suitable as glove materials for protection against undissolved, dry solids, where abrasive particles are not present.

- polychloroprene
- nitrile rubber

- butyl rubber
- fluorocaoutchouc

#### OTHER

- Overalls.
- P.V.C. apron.
- Barrier cream.
- Skin cleansing cream.

# **ENGINEERING CONTROLS**

• Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

# Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

#### PHYSICAL PROPERTIES

Divided solid	Molecular Weight	376.4
540(dec.)	Viscosity	Not Applicable
Not available.	Solubility in water (g/L)	Immiscible
Not Available	pH (1% solution)	6~ (Satd)
554	pH (as supplied)	Not applicable
Not available.	Vapour Pressure (mmHG)	Not applicable
Not available.	Specific Gravity (water=1)	Not available.
Not available.	Relative Vapour Density (air=1)	Not applicable
Not applicable	Evaporation Rate	Not applicable
	540(dec.) Not available. Not Available 554 Not available. Not available. Not available.	540(dec.)ViscosityNot available.Solubility in water (g/L)Not AvailablepH (1% solution)554pH (as supplied)Not available.Vapour Pressure (mmHG)Not available.Specific Gravity (water=1)Not available.Relative Vapour Density (air=1)

#### **APPEARANCE**

Crystalline powder with slight odour and persistant bitter taste; does not mix well with water (13000). Darkens in presence of moisture and light.

# Section 10 - CHEMICAL STABILITY

# CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

# STORAGE INCOMPATIBILITY

• Avoid storage with reducing agents.

Avoid contamination / mixing with oxidising agents as ignition may result.

Avoid strong bases.

Avoid light and moisture. Incompatible with salts of heavy metals.

For incompatible materials - refer to Section 7 - Handling and Storage.

# Section 11 - TOXICOLOGICAL INFORMATION

# riboflavin

# TOXICITY AND IRRITATION

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a

non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound.

CARCINOGE	N															
riboflavin	ι	US - Maine Chemicals of High Concern List									Carcinogen					
				S	ection	12 - E	COLC	GICA	L INFO	ORMA	TION					
No data																
Ecotoxicity																
Ingredient		Persistence: Water/Soil				F	Persistence: Air			Bioaccumulation			Mobility			
riboflavin					HIGH			1	lo Data	Availat	ole	LOW		MED		
GESAMP/EH	s co	омро	SITE I	-IST -	GESA	MP H	azard	Profile	es							
Name / EHS 1 Cas No / RTECS No	ΓRN	A1a	A1b	A1	A2	B1	B2	C1	C2	C3	D1	D2	D3	E1	E2	E3
Poly(2+ 224 )cyclic 6 aromati cs / CAS:83- 88- 5	574	4		4	NR	(4)	NI	(1)	(1)	(2)	(1)	(1)	СМ		s	3

<sup>,00</sup> 

Legend: EHS=EHS Number (EHS=GESAMP Working Group on the Evaluation of the Hazards of Harmful Substances Carried by Ships) NRT=Net Register Tonnage, A1a=Bioaccumulation log Pow, A1b=Bioaccumulation BCF, A1=Bioaccumulation, A2=Biodegradation, B1=Acuteaquatic toxicity LC/ECIC50 (mg/l), B2=Chronic aquatic toxicity NOEC (mg/l), C1=Acute mammalian oral toxicity LD50 (mg/kg), C2=Acutemammalian dermal toxicity LD50 (mg/kg), C3=Acute mammalian inhalation toxicity LC50 (mg/kg), D1=Skin irritation & corrosion, D2=Eye irritation& corrosion, D3=Long-term health effects, E1=Tainting, E2=Physical effects on wildlife & benthic habitats, E3=Interference with coastal amenities, For column A2: R=Readily biodegradable, NR=Not readily biodegradable. For column D3: C=Carcinogen, M=Mutagenic, R=Reprotoxic, S=Sensitising, A=Aspiration hazard, T=Target organ systemic toxicity, L=Lunginjury, N=Neurotoxic, I=Immunotoxic. For column E1: NT=Not tainting (tested), T=Tainting test positive. For column E2: Fp=Persistent floater, F=Floater, S=Sinking substances. The numerical scales start from 0 (no hazard), while higher numbers reflect increasing hazard. (GESAMP/EHS Composite List of Hazard Profiles - Hazard evaluation of substances transported by ships)

#### Section 13 - DISPOSAL CONSIDERATIONS

# **Disposal Instructions**

All waste must be handled in accordance with local, state and federal regulations.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

- A Hierarchy of Controls seems to be common the user should investigate:
- Reduction
- Reuse
- Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate. In most instances the supplier of the material should be consulted.

- DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: burial in a land-fill specifically licenced to accept chemical and / or pharmaceutical wastes or Incineration in a licenced apparatus (after admixture with suitable combustible material)

• Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

# Section 14 - TRANSPORTATION INFORMATION

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: DOT, IATA, IMDG

# Section 15 - REGULATORY INFORMATION

# riboflavin (CAS: 83-88-5) is found on the following regulatory lists;

"Canada Domestic Substances List (DSL)","OECD List of High Production Volume (HPV) Chemicals","US DOE Temporary Emergency Exposure Limits (TEELs)","US FDA CFSAN Color Additive Status List 4","US FDA CFSAN GRAS Substances evaluated by the Select Committee on GRAS Substances (SCOGS)","US FDA Everything Added to Food in the United States (EAFUS)","US FDA Listing of Color Additives Exempt from Certification - Foods","US FDA Maximum Recommended Therapeutic Dose (MRTD) Database","US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory"

# Section 16 - OTHER INFORMATION

# LIMITED EVIDENCE

Cumulative effects may result following exposure\*.

\* (limited evidence).

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references. A list of reference resources used to assist the committee may be found at: www.chemwatch.net/references.

• The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

■ For detailed advice on Personal Protective Equipment, refer to the following U.S. Regulations and Standards:

OSHA Standards - 29 CFR: 1910.132 - Personal Protective Equipment - General requirements 1910.133 - Eye and face protection 1910.134 - Respiratory Protection 1910.136 - Occupational foot protection 1910.138 - Hand Protection Eye and face protection - ANSI Z87.1 Foot protection - ANSI Z41 Respirators must be NIOSH approved.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700. www.Chemwatch.net

Issue Date: Dec-2-2009 Print Date:Feb-15-2012