



# SZABO SCANDIC

Part of Europa Biosite

## Produktinformation



Forschungsprodukte & Biochemikalien



Zellkultur & Verbrauchsmaterial



Diagnostik & molekulare Diagnostik



Laborgeräte & Service

Weitere Information auf den folgenden Seiten!  
See the following pages for more information!



### Lieferung & Zahlungsart

siehe unsere [Liefer- und Versandbedingungen](#)

### Zuschläge

- Mindermengenzuschlag
- Trockeneiszuschlag
- Gefahrgutzuschlag
- Expressversand

### SZABO-SCANDIC HandelsgmbH

Quellenstraße 110, A-1100 Wien

T. +43(0)1 489 3961-0

F. +43(0)1 489 3961-7

[mail@szabo-scandic.com](mailto:mail@szabo-scandic.com)

[www.szabo-scandic.com](http://www.szabo-scandic.com)

[linkedin.com/company/szaboscandic](https://www.linkedin.com/company/szaboscandic) 

# Ammonium bicarbonate

sc-207281



The Power is Question

Material Safety Data Sheet

Hazard Alert Code Key:

EXTREME

HIGH

MODERATE

LOW

## Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

### PRODUCT NAME

Ammonium bicarbonate

### STATEMENT OF HAZARDOUS NATURE

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

### NFPA



### SUPPLIER

Santa Cruz Biotechnology, Inc.  
2145 Delaware Avenue  
Santa Cruz, California 95060  
800.457.3801 or 831.457.3800

### EMERGENCY:

ChemWatch  
Within the US & Canada: 877-715-9305  
Outside the US & Canada: +800 2436 2255  
(1-800-CHEMCALL) or call +613 9573 3112

### SYNONYMS

C-H5-N-O3, NH<sub>4</sub>HCO<sub>3</sub>, "carbonic acid monoammonium salt", "acid ammonium carbonate", "ammonium hydrogen carbonate", "monoammonium carbonate", "ammonium bicarbonate (1:1)"

## Section 2 - HAZARDS IDENTIFICATION

### CHEMWATCH HAZARD RATINGS

	Min	Max
Flammability:	0	
Toxicity:	2	
Body Contact:	2	
Reactivity:	2	
Chronic:	2	

Min/Nil=0  
Low=1  
Moderate=2  
High=3  
Extreme=4



### CANADIAN WHMIS SYMBOLS



## EMERGENCY OVERVIEW

### RISK

Harmful if swallowed.

Irritating to eyes, respiratory system and skin.

### POTENTIAL HEALTH EFFECTS

#### ACUTE HEALTH EFFECTS

#### SWALLOWED

■ Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.

■ Large doses of ammonia or injected ammonium salts may produce diarrhea and may be sufficiently absorbed to produce increased production of urine and systemic poisoning. Symptoms include weakening of facial muscle, tremor, anxiety, reduced muscle and limb control.

#### EYE

■ This material can cause eye irritation and damage in some persons.

#### SKIN

■ This material can cause inflammation of the skin on contact in some persons.

■ The material may accentuate any pre-existing dermatitis condition.

■ Open cuts, abraded or irritated skin should not be exposed to this material.

■ Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

■ Mild irritation is produced on moist skin when vapour concentrations of ammonia exceed 10000 ppm. High vapour concentrations (>30000 ppm) or direct contact with solutions produces severe pain, a stinging sensation, burns and vesiculation and possible brown stains. Extensive burning may be fatal. Vapour exposure may, rarely, produce urticaria.

#### INHALED

■ The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.

■ Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.

■ Inhalation hazard is increased at higher temperatures.

■ The highly irritant properties of ammonia vapor result as the gas dissolves in mucous fluids and forms irritant, even corrosive solutions.

#### CHRONIC HEALTH EFFECTS

■ Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems.

Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.

Long term exposure to high dust concentrations may cause changes in lung function i.e. pneumoconiosis; caused by particles less than 0.5 micron penetrating and remaining in the lung.

<p>

Prolonged or repeated minor exposure to ammonia gas/vapour may cause long-term irritation to the eyes, nose and upper respiratory tract. Repeated exposure or prolonged contact may produce dermatitis, and conjunctivitis.

Other effects may include ulcerative changes to the mouth and bronchial and gastrointestinal disturbances. Adaptation to usually irritating concentrations may result in tolerance. In animals, repeated exposures to sub-lethal levels produces adverse effects on the respiratory tract, liver, kidneys and spleen. Exposure at 675 ppm for several weeks produced eye irritation in dogs and rabbits; corneal opacity, covering between a quarter to one half of the total surface area, was evident in rabbits.

## Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
ammonium bicarbonate	1066-33-7	>99
NOTE Decomposes in moist air/ water to produce		
<a href="#">ammonia</a>	1336-21-6	

## Section 4 - FIRST AID MEASURES

#### SWALLOWED

· IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY. · Where Medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed otherwise:

#### EYE

■ If this product comes in contact with the eyes: · Wash out immediately with fresh running water. · Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.

## SKIN

- If skin contact occurs: · Immediately remove all contaminated clothing, including footwear · Flush skin and hair with running water (and soap if available).

## INHALED

- If fumes or combustion products are inhaled remove from contaminated area. · Lay patient down. Keep warm and rested.

## NOTES TO PHYSICIAN

- for irritant gas exposures:

- the presence of the agent when it is inhaled is evanescent (of short duration) and therefore, cannot be washed away or otherwise removed
- arterial blood gases are of primary importance to aid in determination of the extent of damage. Never discharge a patient significantly exposed to an irritant gas without obtaining an arterial blood sample.
- supportive measures include suctioning (intubation may be required), volume cycle ventilator support (positive and expiratory pressure (PEEP), steroids and antibiotics, after a culture is taken
- If the eyes are involved, an ophthalmologic consultation is recommended

Occupational Medicine: Third Edition; Zenz, Dickerson, Horvath 1994 Pub: Mosby.

For acute or short term repeated exposures to ammonia and its solutions:

- Mild to moderate inhalation exposures produce headache, cough, bronchospasm, nausea, vomiting, pharyngeal and retrosternal pain and conjunctivitis. Severe inhalation produces laryngospasm, signs of upper airway obstruction (stridor, hoarseness, difficulty in speaking) and, in excess, high doses, pulmonary edema.
- Warm humidified air may soothe bronchial irritation.

## Section 5 - FIRE FIGHTING MEASURES

Vapor Pressure (mmHg): 58.505 @ 25 C.

Upper Explosive Limit (%): Not available.

Specific Gravity (water=1): 1.59

Lower Explosive Limit (%): Not available.

## EXTINGUISHING MEDIA

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

## FIRE FIGHTING

- Alert Emergency Responders and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves for fire only.

## GENERAL FIRE HAZARDS/HAZARDOUS COMBUSTIBLE PRODUCTS

- Non combustible.
  - Not considered to be a significant fire risk, however containers may burn.
- Decomposition may produce toxic fumes of: nitrogen oxides (NOx).  
May emit poisonous fumes.  
May emit corrosive fumes.  
Decomposition products are combustible.  
Releases flammable and explosive ammonia gas in a fire situation.

## FIRE INCOMPATIBILITY

- None known.

## PERSONAL PROTECTION

Glasses:

Chemical goggles.

Gloves:

Respirator:

Type K-P Filter of sufficient capacity

## Section 6 - ACCIDENTAL RELEASE MEASURES

### MINOR SPILLS

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid contact with skin and eyes.
- Control personal contact by using protective equipment.
- Use dry clean up procedures and avoid generating dust.
- Place in a suitable, labelled container for waste disposal.

### MAJOR SPILLS

- Moderate hazard.
- CAUTION: Advise personnel in area.
- Alert Emergency Responders and tell them location and nature of hazard.

## Section 7 - HANDLING AND STORAGE

**PROCEDURE FOR HANDLING**

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.

**RECOMMENDED STORAGE METHODS**

- Glass container.
- Polyethylene or polypropylene container.
- Check all containers are clearly labelled and free from leaks.

**STORAGE REQUIREMENTS**

- Store in original containers.
- Keep containers securely sealed.

**Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**

**EXPOSURE CONTROLS**

Source	Material	TWA ppm	TWA mg/m <sup>3</sup>	STEL ppm	STEL mg/m <sup>3</sup>	Peak ppm	Peak mg/m <sup>3</sup>	TWA F/CC	Notes
US - California Permissible Exposure Limits for Chemical Contaminants	ammonium bicarbonate (Particulates not otherwise regulated Respirable fraction)		5						(n)
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	ammonium bicarbonate (Particulates not otherwise regulated Respirable fraction)		5						
US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants	ammonium bicarbonate (Particulates not otherwise regulated (PNOR)(f)-Respirable fraction)		5						
US - Michigan Exposure Limits for Air Contaminants	ammonium bicarbonate (Particulates not otherwise regulated, Respirable dust)		5						
Canada - Prince Edward Island Occupational Exposure Limits	ammonium bicarbonate (Particles (Insoluble or Poorly Soluble) [NOS] Inhalable particles)		10						See Appendix B current TLV/BEI Book
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	ammonia (Ammonia)	25	18	40	30				
US - Minnesota Permissible Exposure Limits (PELs)	ammonia (Ammonia)			35	27				
US ATSDR Minimal Risk Levels for Hazardous	ammonia (AMMONIA)	1.7							

Substances (MRLs)						
US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)	ammonia (AMMONIA)	0.1				
US NIOSH Recommended Exposure Limits (RELs)	ammonia (Ammonia)	25	18	35	27	
Canada - Alberta Occupational Exposure Limits	ammonia (Ammonia)	25	17	35	24	
Canada - British Columbia Occupational Exposure Limits	ammonia (Ammonia)	25		35		
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	ammonia (Ammonia)			35	27	
US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants	ammonia (Ammonia)	50	35			
US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants	ammonia (Ammonia)			35	27	
US - California Permissible Exposure Limits for Chemical Contaminants	ammonia (Ammonia)	25	18	35	27	
US - Idaho - Limits for Air Contaminants	ammonia (Ammonia)	50	35			
US ACGIH Threshold Limit Values (TLV)	ammonia (Ammonia)	25		35		TLV Basis: eye damage; upper respiratory tract irritation
US - Alaska Limits for Air Contaminants	ammonia (Ammonia)			35	27	
US - Michigan Exposure Limits for Air Contaminants	ammonia (Ammonia)			35	27	
US - Oregon Permissible Exposure Limits (Z-1)	ammonia (Ammonia)	25	18			*
US - Washington Permissible exposure limits of air contaminants	ammonia (Ammonia)	25		35		

Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	ammonia (Ammonia)	25		35	
US - Hawaii Air Contaminant Limits	ammonia (Ammonia)	25	18	35	27
Canada - Northwest Territories Occupational Exposure Limits (English)	ammonia (Ammonia)	25	17	35	24
Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)	ammonia (Ammonia)	25	17	35	24
US OSHA Permissible Exposure Levels (PELs) - Table Z1	ammonia (Ammonia)	50	35		
Canada - Nova Scotia Occupational Exposure Limits	ammonia (Ammonia)	25		35	TLV Basis: eye damage; upper respiratory tract irritation
Canada - Prince Edward Island Occupational Exposure Limits	ammonia (Ammonia)	25		35	TLV Basis: eye damage; upper respiratory tract irritation
US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants	ammonia (Ammonia)	50	35		

ENDOELTABLE

## PERSONAL PROTECTION



### RESPIRATOR

Type K-P Filter of sufficient capacity  
Consult your EHS staff for recommendations

### EYE

- Safety glasses with side shields.
- Chemical goggles.

### HANDS/FEET

■ Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: such as:

- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and
- dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739).

- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended.
- When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to

EN 374) is recommended.

· Contaminated gloves should be replaced.

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Experience indicates that the following polymers are suitable as glove materials for protection against undissolved, dry solids, where abrasive particles are not present.

· polychloroprene

· nitrile rubber

· butyl rubber

· fluorocautchouc

· polyvinyl chloride

Gloves should be examined for wear and/ or degradation constantly.

#### OTHER

· Overalls.

· P.V.C. apron.

· Barrier cream.

· Skin cleansing cream.

· Eye wash unit.

#### ENGINEERING CONTROLS

■ CARE: Explosive vapour air mixtures may be present on opening vessels which have contained liquid ammonia. Fatalities have occurred.

· Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction.

· If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered.

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

### PHYSICAL PROPERTIES

Solid.

Mixes with water.

State	Divided solid	Molecular Weight	79.06
Melting Range (°F)	95- 140 Decomposes	Viscosity	Not Applicable
Boiling Range (°F)	140 (Decomposes).	Solubility in water (g/L)	Miscible
Flash Point (°F)	Not applicable	pH (1% solution)	Not available.
Decomposition Temp (°F)	95- 140	pH (as supplied)	Not applicable
Autoignition Temp (°F)	Not available.	Vapor Pressure (mmHg)	58.505 @ 25 C.
Upper Explosive Limit (%)	Not available.	Specific Gravity (water=1)	1.59
Lower Explosive Limit (%)	Not available.	Relative Vapor Density (air=1)	0.60 (ammonia).
Volatile Component (%vol)	Not available.	Evaporation Rate	Not available

### APPEARANCE

White pow with faint odour of ammonia. Soluble in water, insoluble in alcohol. Comparatively stable at room temperature. Decomposes at temperatures above 36 deg.C and evolves highly irritating fumes of ammonia.

## Section 10 - CHEMICAL STABILITY

### CONDITIONS CONTRIBUTING TO INSTABILITY

· Presence of incompatible materials.

· Product is considered stable.

· Presence of heat source.

### STORAGE INCOMPATIBILITY

■ For ammonia:

· Ammonia forms explosive mixtures with oxygen, chlorine, bromine, fluorine, iodine, mercury, platinum and silver.

· Fire and/or explosion may follow contact with acetaldehyde, acrolein, aldehydes, alkylene oxides, amides, antimony, boron, boron halides, bromine chloride, chloric acid, chlorine monoxide, o-chloronitrobenzene, 1-chloro-2,4-nitrobenzene, chlorosilane, chloromelamine, chromium trioxide, chromyl chloride, epichlorohydrin, hexachloromelamine, hypochlorites (do NOT mix ammonia with liquid household bleach), isocyanates, nitrogen tetraoxide, nitrogen trichloride, nitryl chloride, organic anhydrides, phosphorous trioxide, potassium ferricyanide, potassium mercuric cyanide, silver chloride, stibine, tellurium halides, tellurium hypopentachloride, tetramethylammonium amide, trimethylammonium amide, trioxxygen difluoride, vinyl acetate.

· Shock-, temperature-, and pressure sensitive compounds are formed with antimony, chlorine, germanium compounds, halogens, heavy metals, hydrocarbons, mercury oxide, silver compounds (azides, chlorides, nitrates, oxides).

· Vapours or solutions of ammonia are corrosive to copper, copper alloys, galvanised metal and aluminium. Mixtures of ammonia and air lying within the explosive limits can occur above aqueous solutions of varying strengths.

· Avoid contact with sodium hydroxide, iron and cadmium.

· Several incidents involving sudden "boiling" (occasionally violent) of a concentrated solution (d, 0.880, 35 wt %) have occurred when screw-capped winchesters are opened. These are attributable to supersaturation of the solution with gas caused by increases in temperature



subsequent to preparation and bottling. The effect is particularly marked with winchesters filled in winter and opened in summer.

- Ammonia polymerises violently with ethylene oxide.
- Ammonia attacks some coatings, plastics and rubber.
- Attacks copper, bronze, brass, aluminium, steel and their alloys.
- Avoid strong acids, bases.

Avoid storage with reducing agents.

For incompatible materials - refer to Section 7 - Handling and Storage.

## Section 11 - TOXICOLOGICAL INFORMATION

AMMONIUM BICARBONATE

### TOXICITY AND IRRITATION

■ unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

■ Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.

AMMONIUM BICARBONATE:

TOXICITY	IRRITATION
Intravenous (mouse) LD50: 245 mg/kg	Nil Reported
<b>AMMONIA:</b>	
Oral (rat) LD50: 350 mg/kg	Eye (rabbit): 0.25 mg SEVERE
Oral (human) LDLo: 43 mg/kg	Eye (rabbit): 1 mg/30s SEVERE
Inhalation (human) LCLo: 5000 ppm/5m	
Inhalation (human) TCLo: 20 ppm	
Inhalation (rat) LC50: 2000 ppm/4h	
Unreported (man) LDLo: 132 mg/kg	
Oral (Human) LD: 43 mg/kg	
Inhalation (Human) LC: 5000 ppm/4h	
Inhalation (Human) TCLo: 408 ppm/4h	
Subcutaneous (Mouse) LD: 160 mg/kg	
Intravenous (Mouse) LD50: 91 mg/kg	
Oral (Cat) LD: 750 mg/kg	
Subcutaneous (Rabbit) LD: 200 mg/kg	
Intravenous (Rabbit) LD: 10 mg/kg	
■ The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.	

## Section 12 - ECOLOGICAL INFORMATION

No data

### Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
ammonia	LOW		LOW	HIGH

## Section 13 - DISPOSAL CONSIDERATIONS

## Disposal Instructions

All waste must be handled in accordance with local, state and federal regulations.

! Puncture containers to prevent re-use and bury at an authorized landfill.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- Reuse
- Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

DO NOT allow wash water from cleaning equipment to enter drains. Collect all wash water for treatment before disposal.

- Recycle wherever possible or consult manufacturer for recycling options.
- Consult Waste Management Authority for disposal.

## Section 14 - TRANSPORTATION INFORMATION

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: DOT, IATA, IMDG

## Section 15 - REGULATORY INFORMATION

**ammonium bicarbonate (CAS: 1066-33-7) is found on the following regulatory lists;**

"Canada Domestic Substances List (DSL)", "Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS (English)", "CODEX General Standard for Food Additives (GSFA) - Additives Permitted for Use in Food in General, Unless Otherwise Specified, in Accordance with GMP", "International Council of Chemical Associations (ICCA) - High Production Volume List", "OECD Representative List of High Production Volume (HPV) Chemicals", "US - California Occupational Safety and Health Regulations (CAL/OSHA) - Hazardous Substances List", "US - Massachusetts Oil & Hazardous Material List", "US - New Jersey Right to Know Hazardous Substances", "US - Pennsylvania - Hazardous Substance List", "US CWA (Clean Water Act) - List of Hazardous Substances", "US CWA (Clean Water Act) - Reportable Quantities of Designated Hazardous Substances", "US Department of Transportation (DOT) List of Hazardous Substances and Reportable Quantities - Hazardous Substances Other Than Radionuclides", "US DOE Temporary Emergency Exposure Limits (TEELs)", "US Food Additive Database", "US List of Lists - Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112(r) of the Clean Air Act", "US Toxic Substances Control Act (TSCA) - Inventory"

### Regulations for ingredients

**ammonia (CAS: 1336-21-6) is found on the following regulatory lists;**

"Canada - Saskatchewan Industrial Hazardous Substances", "Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances", "Canada Domestic Substances List (DSL)", "Canada Environmental Protection Act (CEPA) 1999 - Schedule 1 Toxic Substances List", "Canada Environmental Quality Guidelines (EQGs) Water: Aquatic life", "Canada Ingredient Disclosure List (SOR/88-64)", "Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS (English)", "CODEX General Standard for Food Additives (GSFA) - Additives Permitted for Use in Food in General, Unless Otherwise Specified, in Accordance with GMP", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "International Council of Chemical Associations (ICCA) - High Production Volume List", "International Fragrance Association (IFRA) Survey: Transparency List", "OECD Representative List of High Production Volume (HPV) Chemicals", "US - California Occupational Safety and Health Regulations (CAL/OSHA) - Hazardous Substances List", "US - Massachusetts Oil & Hazardous Material List", "US - New Jersey Right to Know Hazardous Substances", "US - Pennsylvania - Hazardous Substance List", "US CWA (Clean Water Act) - List of Hazardous Substances", "US CWA (Clean Water Act) - Reportable Quantities of Designated Hazardous Substances", "US Department of Transportation (DOT) List of Hazardous Substances and Reportable Quantities - Hazardous Substances Other Than Radionuclides", "US Department of Transportation (DOT), Hazardous Material Table", "US DOE Temporary Emergency Exposure Limits (TEELs)", "US EPA High Production Volume Chemicals Additional List", "US Food Additive Database", "US List of Lists - Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112(r) of the Clean Air Act", "US NFPA 45 Fire Protection for Laboratories Using Chemicals - Flammability Characteristics of Common Compressed and Liquefied Gases", "US Postal Service (USPS) Hazardous Materials Table: Postal Service Mailability Guide", "US Toxic Substances Control Act (TSCA) - Inventory"

## Section 16 - OTHER INFORMATION

### LIMITED EVIDENCE

■ Cumulative effects may result following exposure\*.

\* (limited evidence).

*Reasonable care has been taken in the preparation of this information, but the author makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The author makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. For additional technical information please call our toxicology department on +800 CHEMCALL.*

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

[www.chemwatch.net/references](http://www.chemwatch.net/references).

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

*This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.*

Issue Date: Jun-29-2009

Print Date:Nov-17-2010