



SZABO SCANDIC

Part of Europa Biosite

Produktinformation



Forschungsprodukte & Biochemikalien



Zellkultur & Verbrauchsmaterial



Diagnostik & molekulare Diagnostik



Laborgeräte & Service

Weitere Information auf den folgenden Seiten!
See the following pages for more information!



Lieferung & Zahlungsart

siehe unsere [Liefer- und Versandbedingungen](#)

Zuschläge

- Mindermengenzuschlag
- Trockeneiszuschlag
- Gefahrgutzuschlag
- Expressversand

SZABO-SCANDIC HandelsgmbH

Quellenstraße 110, A-1100 Wien

T. +43(0)1 489 3961-0

F. +43(0)1 489 3961-7

mail@szabo-scandic.com

www.szabo-scandic.com

[linkedin.com/company/szaboscandic](https://www.linkedin.com/company/szaboscandic) 

Aluminum sulfate

sc-214530



The Power is Question

Material Safety Data Sheet

Hazard Alert Code Key:

EXTREME

HIGH

MODERATE

LOW

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

Aluminum sulfate

STATEMENT OF HAZARDOUS NATURE

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

NFPA



SUPPLIER

Santa Cruz Biotechnology, Inc.
2145 Delaware Avenue
Santa Cruz, California 95060
800.457.3801 or 831.457.3800

EMERGENCY

ChemWatch

Within the US & Canada: 877-715-9305

Outside the US & Canada: +800 2436 2255

(1-800-CHEMCALL) or call +613 9573 3112

SYNONYMS

Al₂O₃·18H₂O, Al₂(SO₄)₃·18H₂O, octadecahydrate, Al₃(SO₄)₂·17H₂O, Al₂(SO₄)₃·17H₂O, heptadecahydrate, Al₃(SO₄)₂·8H₂O, Al₂(SO₄)₃·16H₂O, "aluminium sulphate", "aluminium sulfate, hydrated", "dialuminium sulfate", "aluminium trisulfate", "dialuminium trisulphate", "sulphuric acid, aluminium salt", "pearl Alum", "paper makers alum", "filter alum", "cake Alum", "Patent alum", "pickle alum"

Section 2 - HAZARDS IDENTIFICATION

CHEMWATCH HAZARD RATINGS

	Min	Max
Flammability:	0	
Toxicity:	2	
Body Contact:	3	
Reactivity:	1	
Chronic:	2	

Min/Nil=0
Low=1
Moderate=2
High=3
Extreme=4



CANADIAN WHMIS SYMBOLS



EMERGENCY OVERVIEW

RISK

Risk of serious damage to eyes.
Possible risk of irreversible effects.
Irritating to respiratory system and skin.

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

- Accidental ingestion of the material may be damaging to the health of the individual.
- Sulfates are not well absorbed orally, but can cause diarrhea.
- Acute toxic responses to aluminum are confined to the more soluble forms.

EYE

- If applied to the eyes, this material causes severe eye damage.

SKIN

- This material can cause inflammation of the skin on contact in some persons.
- The material may accentuate any pre-existing dermatitis condition.
- Skin contact is not thought to have harmful health effects, however the material may still produce health damage following entry through wounds, lesions or abrasions.
- Open cuts, abraded or irritated skin should not be exposed to this material.
- Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

INHALED

- The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.
- Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.
- Not normally a hazard due to non-volatile nature of product.

CHRONIC HEALTH EFFECTS

■ Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems. Strong evidence exists that the substance may cause irreversible but non-lethal mutagenic effects following a single exposure. Exposure to the material may result in a possible risk of irreversible effects. The material may produce mutagenic effects in man. This concern is raised, generally, on the basis of appropriate studies using mammalian somatic cells in vivo. Such findings are often supported by positive results from in vitro mutagenicity studies.

Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.

Long term exposure to high dust concentrations may cause changes in lung function i.e. pneumoconiosis; caused by particles less than 0.5 micron penetrating and remaining in the lung.

Exposure to large doses of Aluminum has been connected with the degenerative brain disease Alzheimer's Disease.

Repeated minor skin contact may result in numbing of fingers. Repeated minor ingestion may cause phosphate deficiency; weakening bones.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
aluminium sulfate, hydrated (filter alum)	16828-11-8	> 95
as		
aluminium sulfate	17927-65-0	
hydrolysis yields		
sulfuric acid	7664-93-9	

Section 4 - FIRST AID MEASURES

SWALLOWED

· If swallowed do NOT induce vomiting. · If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.

EYE

■ If this product comes in contact with the eyes: · Immediately hold eyelids apart and flush the eye continuously with running water. · Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.

SKIN

■ If skin contact occurs: · Immediately remove all contaminated clothing, including footwear · Flush skin and hair with running water (and soap if available).

INHALED

· If fumes or combustion products are inhaled remove from contaminated area. · Lay patient down. Keep warm and rested.

NOTES TO PHYSICIAN

· Manifestation of aluminum toxicity include hypercalcemia, anemia, Vitamin D refractory osteodystrophy and a progressive encephalopathy (mixed dysarthria-apraxia of speech, asterixis, tremulousness, myoclonus, dementia, focal seizures). Bone pain, pathological fractures and proximal myopathy can occur.

· Symptoms usually develop insidiously over months to years (in chronic renal failure patients) unless dietary aluminum loads are excessive.

Section 5 - FIRE FIGHTING MEASURES

Vapour Pressure (mmHG):	Negligible
Upper Explosive Limit (%):	Not applicable
Specific Gravity (water=1):	1.6-1.7
Lower Explosive Limit (%):	Not applicable

EXTINGUISHING MEDIA

· There is no restriction on the type of extinguisher which may be used.

Use extinguishing media suitable for surrounding area.

FIRE FIGHTING

· Alert Emergency Responders and tell them location and nature of hazard.

· Wear breathing apparatus plus protective gloves for fire only.

GENERAL FIRE HAZARDS/HAZARDOUS COMBUSTIBLE PRODUCTS

· Non combustible.

· Not considered to be a significant fire risk, however containers may burn.

Decomposition may produce toxic fumes of: sulfur oxides (SO_x), metal oxides.

May emit poisonous fumes.

May emit corrosive fumes.

FIRE INCOMPATIBILITY

■ None known.

PERSONAL PROTECTION

Glasses:

Chemical goggles.

Gloves:

Respirator:

Type E-P Filter of sufficient capacity

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

· Remove all ignition sources.

· Clean up all spills immediately.

· Avoid contact with skin and eyes.

· Control personal contact by using protective equipment.

· Use dry clean up procedures and avoid generating dust.

· Place in a suitable, labelled container for waste disposal.

MAJOR SPILLS

■ Moderate hazard.

· CAUTION: Advise personnel in area.

· Alert Emergency Responders and tell them location and nature of hazard.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

· Avoid all personal contact, including inhalation.

· Wear protective clothing when risk of exposure occurs.

RECOMMENDED STORAGE METHODS

· DO NOT use aluminium, galvanised or tin-plated containers.

· Polyethylene or polypropylene container.

· Check all containers are clearly labelled and free from leaks.

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	TWA F/CC	Notes
US - California Permissible Exposure Limits for Chemical Contaminants	aluminium sulfate, hydrated (filter alum) (Aluminum welding fumes)		5						
US - Minnesota Permissible Exposure Limits (PELs)	aluminium sulfate, hydrated (filter alum) (Aluminum (as Al) - Soluble salts)		2						
Canada - Northwest Territories Occupational Exposure Limits (English)	aluminium sulfate, hydrated (filter alum) (Aluminum soluble salts)		2		4				
US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants	aluminium sulfate, hydrated (filter alum) (Aluminum (as Al) - Soluble salts)		2						
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	aluminium sulfate, hydrated (filter alum) (Aluminum (As al) Soluble salts)		2						
US - Michigan Exposure Limits for Air Contaminants	aluminium sulfate, hydrated (filter alum) (Aluminum (as Al) Soluble salts)		2						
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	aluminium sulfate, hydrated (filter alum) (Aluminum and compounds (as Al): Soluble salts)		2		4				
US - Washington Permissible exposure limits of air contaminants	aluminium sulfate, hydrated (filter alum) (Aluminum (as Al) - Soluble salts)		2		4				
US - Alaska Limits for Air Contaminants	aluminium sulfate, hydrated (filter alum) (Aluminum metal (as Al) - Soluble salts)		2						
US - Hawaii Air Contaminant Limits	aluminium sulfate, hydrated (filter alum) (Aluminum (as Al) - Soluble salts)		2						

US NIOSH Recommended Exposure Limits (RELs)	aluminium sulfate, hydrated (filter alum) (Aluminum (soluble salts and alkyls, as Al))	2		
US - Minnesota Permissible Exposure Limits (PELs)	sulfuric acid (Sulfuric acid)	1		
Canada - British Columbia Occupational Exposure Limits	sulfuric acid (Sulfuric acid, Thoracic Revised 2004)	0.2 (M)		A2, 1
US ACGIH Threshold Limit Values (TLV)	sulfuric acid (Sulfuric acid)	0.2		TLV Basis: pulmonary function. A2 = as contained in strong inorganic acid mists
US NIOSH Recommended Exposure Limits (RELs)	sulfuric acid (Sulfuric acid)	1		
Canada - Alberta Occupational Exposure Limits	sulfuric acid (Sulphuric acid)	1	3	
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	sulfuric acid (Sulfuric acid)	1		
US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants	sulfuric acid (Sulfuric acid)	1		
US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants	sulfuric acid (Sulfuric acid)	1		
US - Idaho - Limits for Air Contaminants	sulfuric acid (Sulfuric acid)	1		
US - California Permissible Exposure Limits for Chemical Contaminants	sulfuric acid (Sulfuric acid)	1	3	
US - Hawaii Air Contaminant Limits	sulfuric acid (Sulfuric acid)	1	3	
US - Alaska Limits for Air Contaminants	sulfuric acid (Sulfuric acid)	1		
US - Michigan Exposure Limits for Air Contaminants	sulfuric acid (Sulfuric acid)	1		

Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	sulfuric acid (Sulphuric acid)	-	1	-	1	
US - Washington Permissible exposure limits of air contaminants	sulfuric acid (Sulfuric acid)		1		3	
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	sulfuric acid (Sulphuric acid, (thoracic fraction++))		0.2		0.6	T20, strong acid mists only
US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants	sulfuric acid (Sulfuric acid)		1			
Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)	sulfuric acid (Sulfuric acid)		1		3	
US OSHA Permissible Exposure Levels (PELs) - Table Z1	sulfuric acid (Sulfuric acid)		1			
Canada - Prince Edward Island Occupational Exposure Limits	sulfuric acid (Sulfuric acid)		0.2			TLV Basis: pulmonary function. A2 = as contained in strong inorganic acid mists
US - Oregon Permissible Exposure Limits (Z-1)	sulfuric acid (Sulfuric acid)	-	1			
Canada - Northwest Territories Occupational Exposure Limits (English)	sulfuric acid (Sulphuric acid)		1		3	
Canada - Nova Scotia Occupational Exposure Limits	sulfuric acid (Sulfuric acid)		0.2			TLV Basis: pulmonary function. A2 = as contained in strong inorganic acid mists

ENDOELTABLE

PERSONAL PROTECTION



RESPIRATOR

Type E-P Filter of sufficient capacity
Consult your EHS staff for recommendations

EYE

- Safety glasses with side shields.
- Chemical goggles.

HANDS/FEET

■ Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: such as:

- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and
- dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739).

- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended.
- When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended.
- Contaminated gloves should be replaced.

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Experience indicates that the following polymers are suitable as glove materials for protection against undissolved, dry solids, where abrasive particles are not present.

- polychloroprene
- nitrile rubber
- butyl rubber
- fluorocautchouc
- polyvinyl chloride

Gloves should be examined for wear and/ or degradation constantly.

OTHER

- Overalls.
- P.V.C. apron.
- Barrier cream.
- Skin cleansing cream.
- Eye wash unit.

ENGINEERING CONTROLS

- Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction.
- If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL PROPERTIES

Solid.

State	Divided solid	Molecular Weight	Not available
Melting Range (°F)	187.7	Viscosity	Not Applicable
Boiling Range (°F)	Not available.	Solubility in water (g/L)	Reacts
Flash Point (°F)	Not Applicable	pH (1% solution)	3.5
Decomposition Temp (°F)	187.7 - H2O	pH (as supplied)	Not applicable
Autoignition Temp (°F)	Not available.	Vapour Pressure (mmHG)	Negligible
Upper Explosive Limit (%)	Not applicable	Specific Gravity (water=1)	1.6-1.7
Lower Explosive Limit (%)	Not applicable	Relative Vapor Density (air=1)	Not applicable
Volatile Component (%vol)	< 1	Evaporation Rate	Non Volatile

APPEARANCE

White lustrous crystals, lumps, granules or powder. Acidic reaction. Soluble in water. Readily hydrolyses in water to acidic solutions. The dust in contact with atmospheric moisture or skin tissue forms irritant and corrosive sulfuric acid. Insoluble in alcohol. Available as commercial, iron free, technical, pure and BP grades. Commercial grades may contain traces of free sulfuric acid and may be mixtures of

different hydrates. Decomposes at 87C losing water of crystallisation.

Section 10 - CHEMICAL STABILITY

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.

STORAGE INCOMPATIBILITY

- Metals and their oxides or salts may react violently with chlorine trifluoride and bromine trifluoride.
 - These trifluorides are hypergolic oxidisers. They ignites on contact (without external source of heat or ignition) with recognised fuels - contact with these materials, following an ambient or slightly elevated temperature, is often violent and may produce ignition.
 - The state of subdivision may affect the results.
 - In presence of moisture, the material is corrosive to aluminium, zinc and tin producing highly flammable hydrogen gas.
 - NOTE: May develop pressure in containers; open carefully. Vent periodically.
- Segregate from alcohol, water.

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

aluminium sulfate, hydrated (filter alum)

TOXICITY AND IRRITATION

■ unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

■ Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.

ALUMINIUM SULFATE, HYDRATED (FILTER ALUM):

■ No significant acute toxicological data identified in literature search.

ALUMINIUM SULFATE:

TOXICITY	IRRITATION
Oral (mouse) LD50: 6207 mg/kg	Eye (rabbit): 10 mg/24h SEVERE
Intraperitoneal (Mouse) LD50: 274 mg/kg	
Oral (rat) TDLo: 10138 mg/kg/8D-C	

TOXICITY

IRRITATION

SULFURIC ACID:

Oral (rat) LD50: 2140 mg/kg

Eye
(rabbit):
1.38 mg
SEVERE

Inhalation (rat) LC50: 510 mg/m³/2h

Eye (rabbit): 5 mg/30sec SEVERE

Inhalation (human) TCLo: 3 mg/m³/24w

■ WARNING: For inhalation exposure ONLY: This substance has been classified by the IARC as Group 1: CARCINOGENIC TO HUMANS

The International Agency for Research on Cancer (IARC) has classified occupational exposures to respirable (<5 um) crystalline silica as being carcinogenic to humans . This classification is based on what IARC considered sufficient evidence from epidemiological studies of humans for the carcinogenicity of inhaled silica in the forms of quartz and cristobalite. Crystalline silica is also known to cause silicosis, a non-cancerous lung disease.

Occupational exposures to strong inorganic acid mists of sulfuric acid:

CARCINOGEN

	US - Rhode Island Hazardous Substance List	IARC	
STRONG INORGANIC ACID MISTS CONTAINING SULFURIC ACID	US Environmental Defense Scorecard Recognized Carcinogens	Reference(s)	P65

STRONG INORGANIC ACID MISTS CONTAINING SULFURIC ACID	US Environmental Defense Scorecard Suspected Carcinogens	Reference(s)	P65
VPVB_(VERY~	US - Maine Chemicals of High Concern List	Carcinogen	CA Prop 65; IARC; NTP 11th ROC

Section 12 - ECOLOGICAL INFORMATION

No data

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
aluminium sulfate, hydrated (filter alum)	HIGH		LOW	HIGH
aluminium sulfate	HIGH		LOW	HIGH
sulfuric acid			LOW	

GESAMP/EHS COMPOSITE LIST - GESAMP Hazard Profiles

Name / EHS TRN A1a A1b A1 A2 B1 B2 C1 C2 C3 D1 D2 D3 E1 E2 E3 Cas No / RTECS No _____
 _____ Aluminium 220 111 Ino Ino 2 Ino 3 1 1 (0) (3) (2) (3) D 3 sulphate 5 rg rg solution /
 CAS:16828 - 11- 8 /

Legend: EHS=EHS Number (EHS=GESAMP Working Group on the Evaluation of the Hazards of Harmful Substances Carried by Ships)
 NRT=Net Register Tonnage, A1a=Bioaccumulation log Pow, A1b=Bioaccumulation BCF, A1=Bioaccumulation, A2=Biodegradation,
 B1=Acuteaquatic toxicity LC/ECIC50 (mg/l), B2=Chronic aquatic toxicity NOEC (mg/l), C1=Acute mammalian oral toxicity LD50 (mg/kg),
 C2=Acute mammalian dermal toxicity LD50 (mg/kg), C3=Acute mammalian inhalation toxicity LC50 (mg/kg), D1=Skin irritation & corrosion,
 D2=Eye irritation & corrosion, D3=Long-term health effects, E1=Tainting, E2=Physical effects on wildlife & benthic habitats, E3=Interference
 with coastal amenities, For column A2: R=Readily biodegradable, NR=Not readily biodegradable. For column D3: C=Carcinogen,
 M=Mutagenic, R=Reprotoxic, S=Sensitising, A=Aspiration hazard, T=Target organ systemic toxicity, L=Lunginjury, N=Neurotoxic,
 I=Immunotoxic. For column E1: NT=Not tainting (tested), T=Tainting test positive. For column E2: Fp=Persistent floater, F=Floater,
 S=Sinking substances. The numerical scales start from 0 (no hazard), while higher numbers reflect increasing hazard. (GESAMP/EHS
 Composite List of Hazard Profiles - Hazard evaluation of substances transported by ships)

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Instructions

All waste must be handled in accordance with local, state and federal regulations.

! Puncture containers to prevent re-use and bury at an authorized landfill.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- Reuse
- Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

DO NOT allow wash water from cleaning equipment to enter drains. Collect all wash water for treatment before disposal.

For small quantities:

- Neutralize an aqueous solution of the material.
- Filter solids for disposal to approved land fill.
- Recycle wherever possible or consult manufacturer for recycling options.
- Consult Waste Management Authority for disposal.

Section 14 - TRANSPORTATION INFORMATION

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: DOT, IATA, IMDG

Section 15 - REGULATORY INFORMATION

aluminium sulfate, hydrated (filter alum) (CAS: 16828-11-8,17927-65-0) is found on the following regulatory lists;

"Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS (English)", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "OECD Representative List of High Production Volume (HPV) Chemicals"

Regulations for ingredients

aluminium sulfate (CAS: 17927-65-0) is found on the following regulatory lists;

"Canada Domestic Substances List (DSL)", "Canada Priority Substances List (PSL1, PSL 2)", "Canada Toxicological Index Service -

Workplace Hazardous Materials Information System - WHMIS (English),"IMO IBC Code Chapter 17: Summary of minimum requirements","IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances","International Council of Chemical Associations (ICCA) - High Production Volume List","OECD Representative List of High Production Volume (HPV) Chemicals","US - California Occupational Safety and Health Regulations (CAL/OSHA) - Hazardous Substances List","US - Massachusetts Oil & Hazardous Material List","US - New Jersey Right to Know Hazardous Substances","US - Pennsylvania - Hazardous Substance List","US CWA (Clean Water Act) - List of Hazardous Substances","US CWA (Clean Water Act) - Reportable Quantities of Designated Hazardous Substances","US Department of Transportation (DOT) List of Hazardous Substances and Reportable Quantities - Hazardous Substances Other Than Radionuclides","US DOE Temporary Emergency Exposure Limits (TEELs)","US FDA Direct Food Substances Generally Recognized as Safe","US Food Additive Database","US List of Lists - Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112(r) of the Clean Air Act","US Toxic Substances Control Act (TSCA) - Inventory"

sulfuric acid (CAS: 7664-93-9) is found on the following regulatory lists;

"Canada - Alberta Ambient Air Quality Objectives","Canada - Alberta Occupational Exposure Limits","Canada - British Columbia Occupational Exposure Limits","Canada - Northwest Territories Occupational Exposure Limits (English)","Canada - Nova Scotia Occupational Exposure Limits","Canada - Prince Edward Island Occupational Exposure Limits","Canada - Prince Edward Island Occupational Exposure Limits - Carcinogens","Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)","Canada - Saskatchewan Industrial Hazardous Substances","Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits","Canada - Saskatchewan Occupational Health and Safety Regulations - Designated Chemical Substances","Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances","Canada Controlled Drugs and Substances Act Schedule VI","Canada Domestic Substances List (DSL)","Canada Ingredient Disclosure List (SOR/88-64)","Canada National Pollutant Release Inventory (NPRI)","Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS (English)","GESAMP/EHS Composite List - GESAMP Hazard Profiles","IMO IBC Code Chapter 17: Summary of minimum requirements","IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk","International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs","International Air Transport Association (IATA) Dangerous Goods Regulations","International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List","International Council of Chemical Associations (ICCA) - High Production Volume List","OECD Representative List of High Production Volume (HPV) Chemicals","United Nations Convention Against Illicit Traffic in Narcotic Drugs and Psychotropic Substances - Table II","United Nations List of Precursors and Chemicals Frequently used in the Illicit Manufacture of Narcotic Drugs and Psychotropic Substances Under International Control - Table II","US - Alaska Limits for Air Contaminants","US - California Air Toxics ""Hot Spots"" List (Assembly Bill 2588) Substances for which emissions must be quantified","US - California Occupational Safety and Health Regulations (CAL/OSHA) - Hazardous Substances List","US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs)","US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELs)","US - California Permissible Exposure Limits for Chemical Contaminants","US - California Proposition 65 - Priority List for the Development of NSRLs for Carcinogens","US - California Toxic Air Contaminant List Category II","US - Connecticut Hazardous Air Pollutants","US - Hawaii Air Contaminant Limits","US - Idaho - Limits for Air Contaminants","US - Maine Chemicals of High Concern List","US - Massachusetts Oil & Hazardous Material List","US - Michigan Exposure Limits for Air Contaminants","US - Minnesota Hazardous Substance List","US - Minnesota Permissible Exposure Limits (PELs)","US - New Jersey Right to Know Hazardous Substances","US - Oregon Permissible Exposure Limits (Z-1)","US - Pennsylvania - Hazardous Substance List","US - Rhode Island Hazardous Substance List","US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants","US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants","US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants","US - Washington Permissible exposure limits of air contaminants","US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants","US ACGIH Threshold Limit Values (TLV)","US ACGIH Threshold Limit Values (TLV) - Carcinogens","US CWA (Clean Water Act) - List of Hazardous Substances","US CWA (Clean Water Act) - Reportable Quantities of Designated Hazardous Substances","US Department of Transportation (DOT) List of Hazardous Substances and Reportable Quantities - Hazardous Substances Other Than Radionuclides","US DOE Temporary Emergency Exposure Limits (TEELs)","US Drug Enforcement Administration (DEA) List I and II Regulated Chemicals","US EPA Acute Exposure Guideline Levels (AEGs) - Interim","US EPA High Production Volume Chemicals Additional List","US EPCRA Section 313 Chemical List","US FDA Indirect Food Additives: Adhesives and Components of Coatings - Substances for Use Only as Components of Adhesives - Adhesives","US Food Additive Database","US List of Lists - Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112(r) of the Clean Air Act","US NIOSH Recommended Exposure Limits (RELs)","US OSHA Permissible Exposure Levels (PELs) - Table Z1","US Postal Service (USPS) Hazardous Materials Table: Postal Service Mailability Guide","US SARA Section 302 Extremely Hazardous Substances","US Toxic Substances Control Act (TSCA) - Inventory"

Section 16 - OTHER INFORMATION

Ingredients with multiple CAS Nos

Ingredient Name CAS aluminium sulfate, hydrated (filter alum) 16828-11-8, 17927-65-0

Reasonable care has been taken in the preparation of this information, but the author makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The author makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. For additional technical information please call our toxicology department on +800 CHEMCALL.

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:
www.chemwatch.net/references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or

criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: Sep-14-2009

Print Date:Mar-4-2011