



SZABO SCANDIC

Part of Europa Biosite

Produktinformation



Forschungsprodukte & Biochemikalien



Zellkultur & Verbrauchsmaterial



Diagnostik & molekulare Diagnostik



Laborgeräte & Service

Weitere Information auf den folgenden Seiten!
See the following pages for more information!



Lieferung & Zahlungsart

siehe unsere [Liefer- und Versandbedingungen](#)

Zuschläge

- Mindermengenzuschlag
- Trockeneiszuschlag
- Gefahrgutzuschlag
- Expressversand

SZABO-SCANDIC HandelsgmbH

Quellenstraße 110, A-1100 Wien

T. +43(0)1 489 3961-0

F. +43(0)1 489 3961-7

mail@szabo-scandic.com

www.szabo-scandic.com

[linkedin.com/company/szaboscandic](https://www.linkedin.com/company/szaboscandic) 

2-(Tributylstannyl)thiophene

sc-223271



The Power is Question

Material Safety Data Sheet

Hazard Alert Code
Key:

EXTREME

HIGH

MODERATE

LOW

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION


PRODUCT NAME

2-(Tributylstannyl)thiophene

STATEMENT OF HAZARDOUS NATURE

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

NFPA



SUPPLIER

Company: Santa Cruz Biotechnology, Inc.

Address:

2145 Delaware Ave

Santa Cruz, CA 95060

Telephone: 800.457.3801 or 831.457.3800

Emergency Tel: CHEMWATCH: From within the US and
Canada: 877-715-9305

Emergency Tel: From outside the US and Canada: +800 2436
2255 (1-800-CHEMCALL) or call +613 9573 3112

PRODUCT USE

- Intermediate.

SYNONYMS

C16-H30-S-Sn, C16-H30-S-Sn, "tributyltin thiophene"

Section 2 - HAZARDS IDENTIFICATION

CANADIAN WHMIS SYMBOLS



EMERGENCY OVERVIEW

RISK

Toxic if swallowed.

Toxic: danger of serious damage to health by prolonged exposure through inhalation and if swallowed.

Harmful by inhalation and in contact with skin.

Irritating to eyes and skin.

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

- Toxic effects may result from the accidental ingestion of the material; animal experiments indicate that ingestion of less than

40 gram may be fatal or may produce serious damage to the health of the individual.

- Subchronic exposures to mono-, di- and tri- and tetra-substituted organotin compounds may elicit toxic response in the central nervous, immune and renal systems, the liver and bile duct and the skin.
- Some trialkyl organotin compounds cause damage to the central nervous system, consisting of swelling through the white matter. Lighter functional groups cause a more potent response. There may be severe headache, vomiting, fear of the light, psychotic disturbances and convulsions. Trialkyl organotin compounds can also impair the function of the thymus and thus incapacitate the immune system.

EYE

- This material can cause eye irritation and damage in some persons.
- Organotin compounds may be strong irritants, and acute conjunctivitis may result from eye splashes, even when followed by immediate lavage; corneal opacities have also been observed.

SKIN

- Skin contact with the material may be harmful; systemic effects may result following absorption.
- This material can cause inflammation of the skin on contact in some persons.
- The material may accentuate any pre-existing dermatitis condition.
- Irritation following contact with organotin compounds may be delayed, in certain cases chemical burns and dermatitis may result. Rate of absorption may be increased if product is in solution.
- Open cuts, abraded or irritated skin should not be exposed to this material.
- Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
- Trialkyl organotin compounds are well absorbed through the skin; healing is slow and skin burns result. The lower abdomen, thighs and groin are most often affected due to absorption by clothing.

INHALED

- Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful.
- There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.
- The acute toxicity of inhaled organotin compounds resembles that found by other means of exposure.
- Thiophene concentrations below the odour threshold level (1-2.1 mg/m³) produce light sensitivity of the human eye. Exposure of animals to thiophene produced drowsiness and generalised muscle fasciculations. Thiophene produced narcosis in mice; fatalities occurred at 2900 ppm. Symptoms of poisoning included severe nervous system effects including weakness, staggering, twitching, head tremors and jerkiness of the limbs. Cyclic sulfides may produce a prolonged comatose state.

CHRONIC HEALTH EFFECTS

■ Toxic: danger of serious damage to health by prolonged exposure through inhalation and if swallowed. This material can cause serious damage if one is exposed to it for long periods. It can be assumed that it contains a substance which can produce severe defects. This has been demonstrated via both short- and long-term experimentation. Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.

Both tributyltins (TBT) and dibutyltins (DBT) have negative effects on the reproductive system in mammals. In line with these facts, TBT and TPT were given the highest category in a European review of endocrine disrupting chemicals (BKH, 2000): "Evidence for endocrine disruption in living organisms". TBT was also classified as "Evidence of potential to cause endocrine disruption in humans".



Organotins are also toxic by other mechanisms. For instance, several organotins are strongly immunosuppressive, display developmental and reproductive effects and are neurotoxic

TPT is classified as category 3 carcinogenic in the EU, but as category 2 (probable human carcinogenic) by the USEPA (EFSA, 2004). DBT may actually be more toxic than TBT to certain enzyme systems. Immunotoxic and developmental effects in mammals may also be more sensitive to DBT than to TB. Both TBT and TPT may be classified as Persistent, Bioaccumulative and Toxic (PBT) and very Persistent, very Bioaccumulative (vPvB) substances according to certain, whereas DBT and dioctyl tin (DOT) may be classified as PBT

For human health, there are no epidemiological studies on chronic low level exposure available. It has been suggested that toxicity was equal for DBT, TBT, DOT and TPT for humans, and proposed a group TDI of 0.1 µg Sn (kg Bw and d)⁻¹.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

HAZARD RATINGS

	Min	Max	
Flammability:	1		
Toxicity:	3		 
Body Contact:	2		
Reactivity:	1		
Chronic:	2		

NAME	CAS RN	%
2-(tributylstannyl)thiophene	54663-78-4	>98

Section 4 - FIRST AID MEASURES

SWALLOWED

- IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY.
- Where Medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed otherwise:
- For advice, contact a Poisons Information Center or a doctor.
- Urgent hospital treatment is likely to be needed.

- If conscious, give water to drink.
- INDUCE vomiting with fingers down the back of the throat, ONLY IF CONSCIOUS. Lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.

NOTE: Wear a protective glove when inducing vomiting by mechanical means.

- In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patient's condition.
- If the services of a medical officer or medical doctor are readily available, the patient should be placed in his/her care and a copy of the MSDS should be provided. Further action will be the responsibility of the medical specialist.
- If medical attention is not available on the worksite or surroundings send the patient to a hospital together with a copy of the MSDS.

EYE

- If this product comes in contact with the eyes:
 - Immediately hold eyelids apart and flush the eye continuously with running water.
 - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
 - Continue flushing until advised to stop by the Poisons Information Center or a doctor, or for at least 15 minutes.
 - Transport to hospital or doctor without delay.
 - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin contact occurs:
 - Immediately remove all contaminated clothing, including footwear
 - Flush skin and hair with running water (and soap if available).
 - Seek medical attention in event of irritation.

INHALED

- - If fumes or combustion products are inhaled remove from contaminated area.
 - Lay patient down. Keep warm and rested.
 - Prosthesis such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
 - Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
 - Transport to hospital, or doctor.

NOTES TO PHYSICIAN

■ Scanty animal data indicate that BAL may be useful against dialkyl but not trialkyl organotin compounds. D-penicillamine is thought to be inactive. GOSSELIN, SMITH HODGE: Clinical Toxicology of Commercial Products, 5th Ed Dimercaprol is suggested to be an effective antidote for dialkyltin poisoning and has been reported to prevent the accumulation of alpha-keto acids produced by dialkyltin compounds. It does not however appear to protect rats from the general toxic effects of triethyltin compounds. This may be due to the fact that dialkyltin compounds, at least up to dihexyl derivatives, react readily with sulfhydryl groups and trialkyltin compounds do not. Surgical decompression was considered to be the only treatment that offered any benefit in human cases of cerebral edema caused by trialkyl compounds. Tin and Organotin Compounds: A Preliminary Review. ENVIRONMENTAL HEALTH CRITERIA: World Health Organization Geneva 1980.

Section 5 - FIRE FIGHTING MEASURES

Vapour Pressure (mmHG):	Not available
Upper Explosive Limit (%):	Not available.
Specific Gravity (water=1):	1.175
Lower Explosive Limit (%):	Not available.

EXTINGUISHING MEDIA

- - Foam.
 - Dry chemical powder.
 - BCF (where regulations permit).
 - Carbon dioxide.
 - Water spray or fog - Large fires only.

FIRE FIGHTING

- - Alert Emergency Responders and tell them location and nature of hazard.
 - Wear full body protective clothing with breathing apparatus.
 - Prevent, by any means available, spillage from entering drains or water course.
 - Use fire fighting procedures suitable for surrounding area.
 - DO NOT approach containers suspected to be hot.
 - Cool fire exposed containers with water spray from a protected location.
 - If safe to do so, remove containers from path of fire.
 - Equipment should be thoroughly decontaminated after use.

GENERAL FIRE HAZARDS/HAZARDOUS COMBUSTIBLE PRODUCTS

- - Combustible.
 - Slight fire hazard when exposed to heat or flame.
 - Heating may cause expansion or decomposition leading to violent rupture of containers.
 - On combustion, may emit toxic fumes of carbon monoxide (CO).
 - May emit acrid smoke.
 - Mists containing combustible materials may be explosive.

Combustion products include: carbon dioxide (CO₂), sulfur oxides (SO_x), metal oxides, other pyrolysis products typical of burning organic material.

May emit poisonous fumes.

FIRE INCOMPATIBILITY

■ Avoid contamination with oxidizing agents i.e. nitrates, oxidizing acids, chlorine bleaches, pool chlorine etc. as ignition may result.

PERSONAL PROTECTION

Glasses:

Chemical goggles.

Gloves:

Respirator:

Type A Filter of sufficient capacity

Section 6 - ACCIDENTAL RELEASE MEASURES


MINOR SPILLS

-
- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapors and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable labeled container for waste disposal.

MAJOR SPILLS

-
- DO NOT touch the spill material
- Clear area of personnel and move upwind.
- Alert Emergency Responders and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- Prevent, by any means available, spillage from entering drains or water course.
- Stop leak if safe to do so.
- Contain spill with sand, earth or vermiculite.
- Collect recoverable product into labeled containers for recycling.
- Neutralize/decontaminate residue.
- Collect solid residues and seal in labeled drums for disposal.
- Wash area and prevent runoff into drains.
- After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.
- If contamination of drains or waterways occurs, advise emergency services.

PROTECTIVE ACTIONS FOR SPILL



FOOTNOTES

1 PROTECTIVE ACTION ZONE is defined as the area in which people are at risk of harmful exposure. This zone assumes that random changes in wind direction confines the vapour plume to an area within 30 degrees on either side of the predominant wind direction, resulting in a crosswind protective action distance equal to the downwind protective action distance.

2 PROTECTIVE ACTIONS should be initiated to the extent possible, beginning with those closest to the spill and working away from the site in the downwind direction. Within the protective action zone a level of vapour concentration may exist resulting in nearly all unprotected persons becoming incapacitated and unable to take protective action and/or incurring serious or irreversible health effects.

3 INITIAL ISOLATION ZONE is determined as an area, including upwind of the incident, within which a high probability of localised wind reversal may expose nearly all persons without appropriate protection to life-threatening concentrations of the material.

4 SMALL SPILLS involve a leaking package of 200 litres (55 US gallons) or less, such as a drum (jerrican or box with inner containers). Larger packages leaking less than 200 litres and compressed gas leaking from a small cylinder are also considered "small spills". LARGE SPILLS involve many small leaking packages or a leaking package of greater than 200 litres, such as a cargo tank, portable tank or a "one-tonne" compressed gas cylinder.

5 Guide 153 is taken from the US DOT emergency response guide book.

6 IERG information is derived from CANUTEC - Transport Canada.

ACUTE EXPOSURE GUIDELINE LEVELS (AEGL) (in ppm)

AEGL 1: The airborne concentration of a substance above which it is predicted that the general population, including susceptible individuals, could experience notable discomfort, irritation, or certain asymptomatic nonsensory effects. However, the effects are not disabling and are transient and reversible upon cessation of exposure.

AEGL 2: The airborne concentration of a substance above which it is predicted that the general population, including susceptible individuals, could

Contaminants	oxide (as Sn)	←		
Canada - Northwest Territories Occupational Exposure Limits (English)	2-(tributylstannyl)thiophene (Tin, inorganic compounds, except SnH and SnO (as Sn))	2	4	
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	2-(tributylstannyl)thiophene (Tin, inorganic compounds, (as Sn) (except SnH4 and SnO2))	- 2	- 4	
Canada - Ontario Occupational Exposure Limits	2-(tributylstannyl)thiophene (Tin, organic compounds of (as tin))	0.1		Skin
US - Minnesota Permissible Exposure Limits (PELs)	2-(tributylstannyl)thiophene (Tin, organic compounds (as Sn))	0.1		
US ACGIH Threshold Limit Values (TLV)	2-(tributylstannyl)thiophene (Tin - Organic compounds (as Sn))	0.1	0.2	
US NIOSH Recommended Exposure Limits (RELs)	2-(tributylstannyl)thiophene (Tin (organic compounds, as Sn))	0.1		
US - California Permissible Exposure Limits for Chemical Contaminants	2-(tributylstannyl)thiophene (Tin, organic compounds, as Sn)	0.1	0.2	
US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants	2-(tributylstannyl)thiophene (Tin, organic compounds (as Sn))	0.1		
US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants	2-(tributylstannyl)thiophene (Tin, organic compounds (as Sn))	0.1		
US - Idaho - Limits for Air Contaminants	2-(tributylstannyl)thiophene (Tin (organic compounds) as (Sn))	0.1		
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	2-(tributylstannyl)thiophene (Tin, organic compounds (as Sn))	0.1		
US OSHA Permissible Exposure Levels (PELs) - Table Z1	2-(tributylstannyl)thiophene (Tin, organic compounds (as Sn))	0.1		
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	2-(tributylstannyl)thiophene (Tin, (as Sn): organic compounds)	0.1	0.2	Skin
US - Hawaii Air Contaminant Limits	2-(tributylstannyl)thiophene (Tin, organic compounds (as Sn))	0.1	0.2	
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	2-(tributylstannyl)thiophene (Tin, organic compounds (as Sn) - Skin)	- 0.1	- 0.2	
US - Washington Permissible exposure limits of air contaminants	2-(tributylstannyl)thiophene (Tin (as Sn) - Organic compounds)	0.1	0.3	
US - Alaska Limits for Air Contaminants	2-(tributylstannyl)thiophene (Tin, organic compounds (as Sn))	0.1		
Canada - Nova Scotia Occupational Exposure Limits	2-(tributylstannyl)thiophene (Tin - Organic compounds (as Sn))	0.1	0.2	
Canada - Prince Edward Island Occupational Exposure Limits	2-(tributylstannyl)thiophene (Tin - Organic compounds (as Sn))	0.1	0.2	
US - Oregon Permissible Exposure Limits (Z1)	2-(tributylstannyl)thiophene (Tin (organic compounds))	0.1		
Canada - Northwest Territories Occupational Exposure Limits (English)	2-(tributylstannyl)thiophene (Tin, organic ⁴ compounds ² (as Sn) - Skin)	0.1	0.2	
Canada - Alberta Occupational Exposure Limits	2-(tributylstannyl)thiophene (Tin, as Sn: Organic compounds)	0.1	0.2	
Canada - British Columbia Occupational Exposure Limits	2-(tributylstannyl)thiophene (Tin - Organic compounds, as Sn)	0.1	0.2	Skin
US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants	2-(tributylstannyl)thiophene (Tin, organic compounds (as Sn))	0.1		
Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)	2-(tributylstannyl)thiophene (Tin: Organic compounds (as Sn))	0.1	0.2	

EMERGENCY EXPOSURE LIMITS

Material	Revised IDLH Value (mg/m ³)	Revised IDLH Value (ppm)
2-(tributylstannyl)thiophene	25	

MATERIAL DATA

2-(TRIBUTYLSTANNYL)THIOPHENE:

■ Exposure limits with "skin" notation indicate that vapor and liquid may be absorbed through intact skin. Absorption by skin may readily exceed vapor inhalation exposure. Symptoms for skin absorption are the same as for inhalation. Contact with eyes and mucous membranes may also contribute to overall exposure and may also invalidate the exposure standard. The no/lowest-observed-adverse-effect levels (NOAELs or LOAELs) in inhalation studies involving tri-n-butyltin chloride and bromide are 0.3-0.4 ppm (2-4 mg/m³) based on changes in the lungs, heart, liver, kidneys, nervous system and reproductive system in rodents. Oral administration of organotin compounds has induced toxicity in a number of differing organ systems, organs and lungs. The LOAEL for triethyltin bromide was 0.4 mg triethyltin/kg/day as 5 ppm in drinking water. The LOAELs for the most critical organ sites in rats (i.e. the cellular immune response and CNS effects) are 0.15 and 0.23 mg/tin/kg body weight/day. Experience with ingested tri- and diethyltins in the treatment of staphylococcal infections, osteomyelitis, anthrax and acne suggests that humans react in a manner similar to rodents, but that the human is more sensitive to absorbed organic tin. The recommended TLV-TWA is thought to minimize the potential for adverse effects on immune function and the central nervous system. A STEL is also recommended to minimize acute symptoms such as eye and respiratory tract irritation, headaches and/or nausea. Based on an exposure to 0.1 mg/m³, a 70-kg worker breathing 10 m³ of air/8hr workday and assuming complete retention of the inhaled dose, would receive a daily exposure of 14.3 ug tin/kg body weight of an organotin compound. A skin notation was recommended based on animal data and the potential danger of enhanced absorption due to damaged skin present in many exposed workers.

Exposure limits with "skin" notation indicate that vapor and liquid may be absorbed through intact skin. Absorption by skin may readily exceed vapor inhalation exposure. Symptoms for skin absorption are the same as for inhalation. Contact with eyes and mucous membranes may also contribute to overall exposure and may also invalidate the exposure standard.

PERSONAL PROTECTION



Consult your EHS staff for recommendations

EYE

-
- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses pose a special hazard; soft lenses may absorb irritants and all lenses concentrate them. DO NOT wear contact lenses.

HANDS/FEET

■ Wear chemical protective gloves, eg. PVC.

Wear safety footwear or safety gumboots, eg. Rubber.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: such as:

- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and
- dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739).

- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended.
- When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended.
- Contaminated gloves should be replaced.

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

OTHER

-
- Overalls.
- Eyewash unit.
- Barrier cream.
- Skin cleansing cream.

RESPIRATOR

■ Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Breathing Zone Level ppm (volume)	Maximum Protection Factor	Half-face Respirator	Full-Face Respirator
1000	10	A-1	-
1000	50	-	A-1
5000	50	Airline*	-
5000	100	-	A-2
10000	100	-	A-3
	100+		Airline* *

* - Continuous Flow ** - Continuous-flow or positive pressure demand.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

Use appropriate NIOSH-certified respirator based on informed professional judgement. In conditions where no reasonable estimate of exposure can be made, assume the exposure is in a concentration IDLH and use NIOSH-certified full face pressure demand SCBA with a minimum service life of 30 minutes, or a combination full facepiece pressure demand SAR with auxiliary self-contained air supply. Respirators provided only for escape from IDLH atmospheres shall be NIOSH-certified for escape from the atmosphere in which they will be used.

ENGINEERING CONTROLS

Local exhaust ventilation usually required. If risk of overexposure exists, wear an approved respirator. Correct fit is essential to obtain adequate protection an approved self contained breathing apparatus (SCBA) may be required in some situations. Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapors, degreasing etc., evaporating from tank (in still air).	0.25-0.5 m/s (50-100 f/min.)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favorable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL PROPERTIES

Liquid.
Does not mix with water.
Sinks in water.

State	Liquid	Molecular Weight	373.17
Melting Range (°F)	Not available	Viscosity	Not Available
Boiling Range (°F)	311 (0.1 mm Hg)	Solubility in water (g/L)	Immiscible
Flash Point (°F)	221	pH (1% solution)	Not applicable
Decomposition Temp (°F)	Not Available	pH (as supplied)	Not applicable
Autoignition Temp (°F)	Not available.	Vapour Pressure (mmHG)	Not available
Upper Explosive Limit (%)	Not available.	Specific Gravity (water=1)	1.175
Lower Explosive Limit (%)	Not available.	Relative Vapor Density (air=1)	Not available.
Volatile Component (%vol)	Not available.	Evaporation Rate	Not available

APPEARANCE

Liquid; does not mix with water.

Section 10 - CHEMICAL STABILITY

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerization will not occur.

STORAGE INCOMPATIBILITY

- Avoid strong acids, bases.
- Avoid reaction with oxidizing agents.

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

2-(tributylstannyl)thiophene

TOXICITY AND IRRITATION

■ No significant acute toxicological data identified in literature search.

CARCINOGEN

Tin - Organic compounds (as Sn)	US ACGIH Threshold Limit Values (TLV) - Carcinogens	Carcinogen Category	A4
SKIN			
2-(tributylstannyl)thiophene	Canada - Ontario Occupational Exposure Limits - Skin	Notes	Skin
2-(tributylstannyl)thiophene	US AIHA Workplace Environmental Exposure Levels (WEELs) - Skin	Notes	Skin
2-(tributylstannyl)thiophene	US NIOSH Recommended Exposure Limits (RELs) - Skin	Skin	Yes
2-(tributylstannyl)thiophene	Canada - Quebec Permissible Exposure Values for Airborne Contaminants - Skin (French)	Notes	Skin
2-(tributylstannyl)thiophene	US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants - Skin	Skin Designation	X
2-(tributylstannyl)thiophene	US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants - Skin	Skin Designation	X
2-(tributylstannyl)thiophene	US - Washington Permissible exposure limits of air contaminants - Skin	Skin	X
2-(tributylstannyl)thiophene	US ACGIH Threshold Limit Values (TLV) - Skin	Skin Designation	Yes
2-(tributylstannyl)thiophene	Canada - British Columbia Occupational Exposure Limits - Skin	Notation	Skin
2-(tributylstannyl)thiophene	US - Minnesota Permissible Exposure Limits (PELs) - Skin	Skin Designation	X
2-(tributylstannyl)thiophene	US - Hawaii Air Contaminant Limits - Skin Designation	Skin Designation	X
2-(tributylstannyl)thiophene	ND	Skin Designation	X
2-(tributylstannyl)thiophene	US OSHA Permissible Exposure Levels (PELs) - Skin	Skin Designation	X
2-(tributylstannyl)thiophene	US - California Permissible Exposure Limits for Chemical Contaminants - Skin	Skin	X
2-(tributylstannyl)thiophene	US - California Permissible Exposure Limits for Chemical Contaminants - Skin	Skin	S
2-(tributylstannyl)thiophene	Canada - Alberta Occupational Exposure Limits - Skin	Substance Interaction	1

Section 12 - ECOLOGICAL INFORMATION

Refer to data for ingredients, which follows:

2-(TRIBUTYLSTANNYL)THIOPHENE:

Marine Pollutant:	Severe
-------------------	--------

■ Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
 ■ Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

■ Organotin compounds are characterized by a Sn4+ ion to which one to four organic ligands are attached. They are classified according to the type of organic ligand and the most common are butyltins, octyltins and phenyltins.

A large number of organotin substances are used in the society, and some of these are well-known environmental pollutants. The butyltins comprise on such group. Eco toxicity increases dramatically in the order methylbutyltin (MBT, RSn) < dibutyltin (DBT, R2Sn) < tributyltin (TBT, R3Sn) for certain endpoints.

Degradation of organotin compounds involves the breaking of the tin-carbon bond, which may occur by UV irradiation, or by biological or chemical cleavage. In water, for example, tributyltin can be degraded by photochemical and biological processes relatively rapidly; however, adsorption onto suspended particulate material in water followed by sedimentation is a key removal process. The adsorption behavior of Sn4+ ion and eight organotin species (tri-, di-, and monobutyltin; tri-, di-, and monomethyltin; and tri- and diphenyltin) were studied in a water-sediment system using artificial seawater and estuarine sediment.

Adsorption coefficients varied from 100.5 to 104.5 and showed the trend of Sn4+ > mono > di > tri in the same substituent series. Larger absorption coefficients were found for aromatic compounds than for aliphatic compounds. Releases of organotin compounds to air from various surfaces are, in general, not significant due to their low vapor pressures and rapid photodegradation at surfaces.

The speciation of organotin compounds is pH-dependent. At lower pHs, the cationic form will be the primary form, and as the pH is increased, the neutral hydroxide compounds will be the predominant species. In the environmentally relevant pH range (pH 5–9), the predominant organotin species will be the neutral hydroxide compounds (i.e., R3SnOH, R2Sn(OH)2, and RSn(OH)3). High concentrations of chloride favor the formation of chloro species. The pKa values for trimethyltin, triethyltin, tributyltin, and triphenyltin cations are approximately 6.60, 6.81, 6.25, and 5.2, respectively. Degradation of organotin compounds in sediments is much slower than in water, and half-lives have been estimated to be several years. In addition to dealkylation of organotin compounds, methylation of tin and organotin compounds by chemical and/or biological means may occur. The contribution of methylation by biotic and abiotic mechanisms is not clear. This pathway may result in fully substituted and volatile tin compounds.

At ambient temperatures, the solubilities of organotin compounds range from 0.0001 to about 50 mg/L. Organotin compounds may partition from water to aquatic organisms. The bioavailability of organotin compounds via the food chain appears to be of minor importance for tributyltin and triphenyltin when compared to uptake via the water phase. Seven-day BCF values were derived for dibutyltin dichloride, dibutyltin dilaurate, tributyltin chloride, bis(tributyltin) oxide, and triphenyltin chloride for muscle, liver, kidney, and vertebra tissue of round crucian carp. The BCF values ranged from 12 in muscle to 5,012 in liver. For all organotin compounds, liver had the highest BCF values. The highest BCFs were found for the tributyltin compounds. The use of tributyltin (TBT) in antifouling paints on ships has caused significant harm to the marine environment worldwide. Female molluscs are masculinized by TBT at levels as low as ca 1 ng/l, and this effect has severe consequences for their ability to reproduce.

Most investigations on the environmental occurrence of organotin substances have focused on TBT. However, other substances such as dibutyltin (DBT), dioctyltin and monobutyltin (MBT) are used in the society for other reasons and are found in other applications.

Most industrial organotin chemicals (OTCs) are composed of an organotin cation and one or several ligands, and most of these chemicals are reconverted to the organotin cation compounds in natural waters. The cation may form dissolved complexes with e.g. chloride in seawater.

Therefore, their environmental partitioning properties such as K_d and K_h depend in part on the balancing anion in the environment. Hydrophobicity increases with increasing number of alkyl groups, and with increasing length of the alkyl chain. Organotins are moderately hydrophobic and associate strongly to particles in natural waters. In harbour sediments, log K_d in the range 3-4.3 have been measured for various OTCs, and the particle affinity increased in the order MBT < DBT < TBT. In various soils, however, the reverse pattern of K_d was observed. In organic soils, log K_d exceeded 4.0, whereas adsorption was less strong in mineral soils. In contrast to hydrophobic pollutants such as PCBs or PAHs (that partition to lipids in organic matter), OTCs are adsorbed to the functional groups of organic matter, e.g. phenolic and carboxylic groups.

Because organotins are generally cations, long-range atmospheric transport has generally not been considered as important. It has though been demonstrated that TBT forms highly volatile chloride species in seawater. One study has actually demonstrated the presence of organotins in air from rural sites, showing that long-range atmospheric transport of butyltins and octyltins do occur. MBT was the major species in precipitation and deposition. TBT mainly occurred in the gas phase and it is speculated that the source of butyltins may have been volatile TBT species. Subsequent dealkylation in the atmosphere may convert TBT to DBT and MBT.

Organotins are progressively dealkylated in nature, for instance:

TBT → DBT → MBT → Sn⁴⁺

Dealkylation proceeds both by photolysis and through enzymatical reactions. This is important to consider when monitoring data are evaluated, since the occurrence of, e.g., DBT may be due to direct release of DBT or to release of TBT that is subsequently dealkylated. Half-lives in soils and sediments are commonly one or a few years, but may be longer under reducing conditions, whereas half-lives in natural waters may range from a few days to several weeks.

Organotin compounds have been detected in various marine organisms, from evertebrates to mammals. In fish and marine mammals, TBT and TPT bioaccumulate more strongly in liver than in muscle. Bioaccumulation is often stronger in bivalves than in fish, a consequence of lower metabolic capacity in bivalves. Trisubstituted OTCs are more strongly bioaccumulated than the less lipophilic disubstituted OTCs. Because TBT is dealkylated in many organisms, DBT may be a major species in biota but not necessarily the organotin species that was assimilated. Most studies do not suggest that TBT is biomagnified in aquatic food-chain. However, TPT appears to be biomagnified fairly strongly in the aquatic food chain. The trisubstituted substances, TPT and in particular TBT, are widely held as the most toxic organotin substances. Numerous field studies have demonstrated a direct link between TBT and imposex in certain marine organisms, mainly molluscs. Imposex means that females are masculinized and this effect is severe because it directly influences the ability for organisms to reproduce. Imposex has been demonstrated in many coastal areas. These effects occur at very low levels (ca 1 ng/l) for certain organisms. It has been shown in laboratory that TBT causes masculinization also in fish. DBT and MBT does not cause imposex, but both TBT and DBT have negative effects on the reproductive system in mammals. In line with these facts, TBT and TPT were given the highest category in a European review of endocrine disrupting chemicals: "Evidence for endocrine disruption in living organisms". TBT was also classified as "Evidence of potential to cause endocrine disruption in humans".

■ DO NOT discharge into sewer or waterways.

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Instructions

All waste must be handled in accordance with local, state and federal regulations.

! Puncture containers to prevent re-use and bury at an authorized landfill.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction,
- Reuse
- Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

DO NOT allow wash water from cleaning equipment to enter drains. Collect all wash water for treatment before disposal.

- Recycle wherever possible or consult manufacturer for recycling options.
- Consult Waste Management Authority for disposal.
- Bury or incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorized landfill.

Section 14 - TRANSPORTATION INFORMATION



DOT:

Symbols:	None	Hazard class or Division:	6.1
Identification Numbers:	UN2788	PG:	III
Label Codes:	6.1	Special provisions:	IB3, T7, TP2, TP28
Packaging: Exceptions:	153	Packaging: Non-bulk:	203
Packaging: Exceptions:	153	Quantity limitations: Passenger aircraft/rail:	60 L
Quantity Limitations: Cargo aircraft only:	220 L	Vessel stowage: Location:	A
Vessel stowage: Other:	40	S.M.P.:	Severe

Hazardous materials descriptions and proper shipping names:
Organotin compounds, liquid, n.o.s.

Air Transport IATA:

ICAO/IATA Class:	6.1	ICAO/IATA Subrisk:	None
UN/ID Number:	2788	Packing Group:	III
Special provisions:	A3		

Shipping Name: ORGANOTIN COMPOUND, LIQUID, N.O.S. *(CONTAINS 2-(TRIBUTYLSTANNYL)THIOPHENE)

Maritime Transport IMDG:

IMDG Class:	6.1	IMDG Subrisk:	None
UN Number:	2788	Packing Group:	III
EMS Number:	F-A,S-A	Special provisions:	43 223 274
Limited Quantities:	500 ml	Marine Pollutant:	Severe

Shipping Name: ORGANOTIN COMPOUND, LIQUID, N.O.S.(contains 2-(tributylstannyl)thiophene)

Section 15 - REGULATORY INFORMATION

2-(tributylstannyl)thiophene (CAS: 54663-78-4) is found on the following regulatory lists;

"US - Alaska Limits for Air Contaminants", "US - California Occupational Safety and Health Regulations (CAL/OSHA) - Hazardous Substances List", "US - Minnesota Hazardous Substance List", "US RCRA (Resource Conservation & Recovery Act) - Appendix IX to Part 264 Ground-Water Monitoring List 1", "US RCRA (Resource Conservation & Recovery Act) - List of Hazardous Inorganic and Organic Constituents 1"

Section 16 - OTHER INFORMATION

LIMITED EVIDENCE

- Cumulative effects may result following exposure*.
 - May produce discomfort of the respiratory system*.
- * (limited evidence).

Reasonable care has been taken in the preparation of this information, but the author makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The author makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. For additional technical information please call our toxicology department on +800 CHEMCALL.

- Classification of the mixture and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:
www.chemwatch.net/references.

- The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: Apr-5-2010

Print Date: Apr-22-2010