



# SZABO SCANDIC

Part of Europa Biosite

## Produktinformation



Forschungsprodukte & Biochemikalien



Zellkultur & Verbrauchsmaterial



Diagnostik & molekulare Diagnostik



Laborgeräte & Service

Weitere Information auf den folgenden Seiten!  
See the following pages for more information!



### Lieferung & Zahlungsart

siehe unsere [Liefer- und Versandbedingungen](#)

### Zuschläge

- Mindermengenzuschlag
- Trockeneiszuschlag
- Gefahrgutzuschlag
- Expressversand

### SZABO-SCANDIC HandelsgmbH

Quellenstraße 110, A-1100 Wien

T. +43(0)1 489 3961-0

F. +43(0)1 489 3961-7

[mail@szabo-scandic.com](mailto:mail@szabo-scandic.com)

[www.szabo-scandic.com](http://www.szabo-scandic.com)

[linkedin.com/company/szaboscandic](https://www.linkedin.com/company/szaboscandic) 

# Arsenic(V) oxide hydrate

sc-227277

Material Safety Data Sheet



The Power is Question

Hazard Alert Code Key:

EXTREME

HIGH

MODERATE

LOW

## Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

### PRODUCT NAME

Arsenic(V) oxide hydrate

### STATEMENT OF HAZARDOUS NATURE

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

### NFPA



### SUPPLIER

Company: Santa Cruz Biotechnology, Inc.

Address:

2145 Delaware Ave

Santa Cruz, CA 95060

Telephone: 800.457.3801 or 831.457.3800

Emergency Tel: CHEMWATCH: From within the US and Canada:

877-715-9305

Emergency Tel: From outside the US and Canada: +800 2436 2255

(1-800-CHEMCALL) or call +613 9573 3112

### PRODUCT USE

Used in production of arsenates, insecticides, weed killer, fungicides, wood preservatives, coloured glass, metal adhesives and dyeing and printing. Reagent

### SYNONYMS

As<sub>2</sub>O<sub>5</sub>, "arsenic acid anhydride", "arsenic anhydride", "arsenic oxide", "arsenic pentaoxide", "arsenic (V) oxide", "arsenic (V) oxide", "diarsenic pentoxide", Zotox

## Section 2 - HAZARDS IDENTIFICATION

### CANADIAN WHMIS SYMBOLS



### EMERGENCY OVERVIEW

#### RISK

May cause CANCER.

Toxic by inhalation and if swallowed.

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## POTENTIAL HEALTH EFFECTS

### ACUTE HEALTH EFFECTS

#### SWALLOWED

- Toxic effects may result from the accidental ingestion of the material; animal experiments indicate that ingestion of less than 40 gram may be fatal or may produce serious damage to the health of the individual.
- Ingestion may produce nausea, vomiting and diarrhea, bloody stools, shock, rapid pulse and coma. Severe gastritis or gastroenteritis may occur as a result of lesions produced by vascular damage from absorbed arsenic (and not local corrosion); symptoms may be delayed for several hours. Eventually a violent hemorrhagic gastroenteritis leads to profound loss of fluid and electrolyte resulting in shock and death. Occasionally alimentary symptoms are mild or absent in which case symptoms are usually referable to the central nervous system, headache, vertigo, muscle spasm or convulsion, delirium and, sometimes, mania. In advanced poisonings by arsenic and its inorganic salts, nervous symptoms are prominent; disorders of the brain (encephalopathies) and peripheral neuritis (more commonly) have been described. A prickling sensation (paresthesia), decreased sensitivity to sensation and pain (hypoesthesia), eventually paralysis and muscular atrophy appear, usually in the legs. "Glove and stocking" distribution of sensory loss may be prominent. The toxic moiety is presumed to be trivalent arsenic in the form of inorganic arsenious acid (arsenite) or an organic arsenoxide. Arsenites are active enzyme inhibitors. Arsenic and its compounds may damage the stem cell which acts as the precursor to components of the blood. Loss of the stem cell may result in pancytopenia (a reduction in the number of red and white blood cells and platelets) with a latency period corresponding to the lifetime of the individual blood cells. Granulocytopenia (a reduction in granular leukocytes) develops within days and thrombocytopenia (a disorder involving platelets), within 1-2 weeks, whilst loss of erythrocytes (red blood cells) need months to become clinically manifest. Aplastic anaemia develops due to complete destruction of the stem cells.

#### EYE

- Although the material is not thought to be an irritant, direct contact with the eye may cause transient discomfort characterized by tearing or conjunctival redness (as with windburn). Slight abrasive damage may also result. The material may produce foreign body irritation in certain individuals.

#### SKIN

- Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.
- There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons.
- Open cuts, abraded or irritated skin should not be exposed to this material.
- Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
- Solution of material in moisture on the skin, or perspiration, may increase irritant effects.
- Arsenic can cause skin irritation characterized by eczema, scaling, sensitization, and discoloration and thickening of the palms and soles.

#### INHALED

- Inhalation of dusts, generated by the material, during the course of normal handling, may produce toxic effects.
- There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.
- Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.
- Inhaling materials containing arsenic can cause severe irritation to the nose, throat and lungs. Prolonged exposure can cause severe structural damage to the nose.

### CHRONIC HEALTH EFFECTS

- There is sufficient evidence to suggest that this material directly causes cancer in humans.

Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.

There is limited evidence that, skin contact with this product is more likely to cause a sensitization reaction in some persons compared to the general population.

Long term exposure to high dust concentrations may cause changes in lung function i.e. pneumoconiosis; caused by particles less than 0.5 micron penetrating and remaining in the lung. Prime symptom is breathlessness; lung shadows show on X-ray.

Long-term exposure to arsenic and its inorganic salts may produce loss of appetite, nausea and vomiting, low fever, persistent headache, pallor, weakness and phlegm. Skin effects include redness, eczema, pigmentation, diffuse hair loss, scaling of the palms and soles, sloughing, brittle nails, white lines or bands on the nails, loss of hair and nails, and localized swelling. Kidney damage can occur and liver enlargement with jaundice may develop into cirrhosis (hardening of the liver), with fluid in the abdomen. Nervous system effects involving the extremities (numbness, tingling, burning pain, weakness, inco-ordination) may also occur. Arsenic is well-known to cause cancer in humans.

## Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

### HAZARD RATINGS

	Min	Max
Flammability:	0	■
Toxicity:	3	■
Body Contact:	2	■
Reactivity:	0	■
Chronic:	4	■

Min/Nil=0  
Low=1  
Moderate=2  
High=3  
Extreme=4



NAME	CAS RN	%
------	--------	---

## Section 4 - FIRST AID MEASURES

### SWALLOWED

.

- IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY.
- Where Medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed otherwise:
  - For advice, contact a Poisons Information Center or a doctor.
  - Urgent hospital treatment is likely to be needed.
  - If conscious, give water to drink.
  - INDUCE vomiting with fingers down the back of the throat, ONLY IF CONSCIOUS. Lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.

NOTE: Wear a protective glove when inducing vomiting by mechanical means.

- In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patient's condition.
- If the services of a medical officer or medical doctor are readily available, the patient should be placed in his/her care and a copy of the MSDS should be provided. Further action will be the responsibility of the medical specialist.
- If medical attention is not available on the worksite or surroundings send the patient to a hospital together with a copy of the MSDS.

### EYE

- If this product comes in contact with the eyes:
  - Immediately hold eyelids apart and flush the eye continuously with running water.
  - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
  - Continue flushing until advised to stop by the Poisons Information Center or a doctor, or for at least 15 minutes.
  - Transport to hospital or doctor without delay.
  - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

### SKIN

- If skin contact occurs:
  - Immediately remove all contaminated clothing, including footwear
  - Flush skin and hair with running water (and soap if available).
  - Seek medical attention in event of irritation.

### INHALED

.

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor, without delay.

### NOTES TO PHYSICIAN

- For acute or short term repeated exposures to arsenic, soluble compounds: Treat as per arsenic poisoning.
- Acute skin lesions such as contact dermatitis usually do not require other treatment than removal from exposure.
- If more severe symptoms of the respiratory system, the skin or the gastro-intestinal tract occur, British Anti-Lewisite (BAL, dimercaprol) may be given. Prompt administration in such cases is vital; to obtain maximum benefit such treatment should be administered within 4 hours of poisoning.
- In addition, general treatment such as prevention of further absorption from the gastro-intestinal tract are mandatory.
- General supportive therapy such as maintenance of respiration and circulation, maintenance of water and electrolyte balance and control of nervous system effects, as well as elimination of absorbed poison through dialysis and exchange transfusion, may be used if feasible.
- Dimercaprol is given by deep intramuscular injection as a 5% solution in peanut oil (or a 10% solution with benzyl-benzoate in vegetable oil). It is usually given in a dose of 3 mg/kg, 4-hourly, for the first two days, or twice daily for up to seven days. [ILO Encyclopedia]
- BAL Therapy is effective for hematological manifestations of chronic arsenic poisoning but not for neurological symptoms. Watch for side effects (e.g. urticaria, burning sensation in the lips, mouth and throat, fever, conjunctivitis etc).
- Some relief results from administration of diphenhydramine (Benadryl) (1.5 mg/kg intramuscularly or by mouth every 6 hour). [Ellenhorn and Barceloux: Medical Toxicology]

### BIOLOGICAL EXPOSURE INDEX - BEI (Notice of Intent to Establish)

BEIs represent the levels of determinants which are most likely to be observed in specimens collected from a healthy worker who has been exposed to chemicals to the same extent as a worker with inhalation exposure to the

Exposure Standard (ES or TLV):

Determinant	Index	Sampling Time	Comments
Inorganic arsenic metabolites in urine	35 ug/gm creatinine	End of workweek	B

B: Background levels occur in specimens collected from subjects NOT exposed

Consult specific documentation.

\* Preplacement and periodic medical examinations are essential for workers exposed to arsenic on a regular basis. Preplacement physical examinations should give particular attention to allergic and chronic skin lesions, eye disease, psoriasis, chronic eczematous dermatitis, hyperpigmentation of the skin, keratosis and warts, baseline weight, baseline blood and haemoglobin counts, baseline urinary arsenic

determinations.

Annual physical examinations should give attention to general health, weight, skin condition, and any evidence of excessive exposure or absorption of arsenic.

## Section 5 - FIRE FIGHTING MEASURES

Vapour Pressure (mmHG):	Negligible.
Upper Explosive Limit (%):	Not applicable
Specific Gravity (water=1):	4.32
Lower Explosive Limit (%):	Not applicable

### EXTINGUISHING MEDIA

.

- Water spray or fog.
- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

### FIRE FIGHTING

.

- Alert Emergency Responders and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- Prevent, by any means available, spillage from entering drains or water course.
- Use fire fighting procedures suitable for surrounding area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

### GENERAL FIRE HAZARDS/HAZARDOUS COMBUSTIBLE PRODUCTS

.

- Non combustible.
  - Not considered to be a significant fire risk, however containers may burn.
- Decomposition may produce toxic fumes of: metal oxides, arsenic compounds.  
May emit poisonous fumes.

### FIRE INCOMPATIBILITY

- None known.

### PERSONAL PROTECTION

Glasses:

Chemical goggles.

Gloves:

Respirator:

Particulate

## Section 6 - ACCIDENTAL RELEASE MEASURES

### MINOR SPILLS

.

- Clean up waste regularly and abnormal spills immediately.
- Avoid breathing dust and contact with skin and eyes.
- Wear protective clothing, gloves, safety glasses and dust respirator.
- Use dry clean up procedures and avoid generating dust.
- Vacuum up or sweep up. NOTE: Vacuum cleaner must be fitted with an exhaust micro filter (HEPA type) (consider explosion-proof machines designed to be grounded during storage and use).
- Dampen with water to prevent dusting before sweeping.
- Place in suitable containers for disposal.


### MAJOR SPILLS

.

- Clear area of personnel and move upwind.
- Alert Emergency Responders and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- Prevent, by all means available, spillage from entering drains or water courses.
- Consider evacuation (or protect in place).
- No smoking, naked lights or ignition sources.
- Increase ventilation.
- Stop leak if safe to do so.

- Water spray or fog may be used to disperse / absorb vapour.
- Contain or absorb spill with sand, earth or vermiculite.
- Collect recoverable product into labelled containers for recycling.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.
- If contamination of drains or waterways occurs, advise emergency services.

## PROTECTIVE ACTIONS FOR SPILL



## FOOTNOTES

- 1 PROTECTIVE ACTION ZONE is defined as the area in which people are at risk of harmful exposure. This zone assumes that random changes in wind direction confines the vapour plume to an area within 30 degrees on either side of the predominant wind direction, resulting in a crosswind protective action distance equal to the downwind protective action distance.
- 2 PROTECTIVE ACTIONS should be initiated to the extent possible, beginning with those closest to the spill and working away from the site in the downwind direction. Within the protective action zone a level of vapour concentration may exist resulting in nearly all unprotected persons becoming incapacitated and unable to take protective action and/or incurring serious or irreversible health effects.
- 3 INITIAL ISOLATION ZONE is determined as an area, including upwind of the incident, within which a high probability of localised wind reversal may expose nearly all persons without appropriate protection to life-threatening concentrations of the material.
- 4 SMALL SPILLS involve a leaking package of 200 litres (55 US gallons) or less, such as a drum (jerrican or box with inner containers). Larger packages leaking less than 200 litres and compressed gas leaking from a small cylinder are also considered "small spills". LARGE SPILLS involve many small leaking packages or a leaking package of greater than 200 litres, such as a cargo tank, portable tank or a "one-tonne" compressed gas cylinder.
- 5 Guide 151 is taken from the US DOT emergency response guide book.
- 6 IERG information is derived from CANUTEC - Transport Canada.

## ACUTE EXPOSURE GUIDELINE LEVELS (AEGL) (in ppm)

AEGL 1: The airborne concentration of a substance above which it is predicted that the general population, including susceptible individuals, could experience notable discomfort, irritation, or certain asymptomatic nonsensory effects. However, the effects are not disabling and are transient and reversible upon cessation of exposure.

AEGL 2: The airborne concentration of a substance above which it is predicted that the general population, including susceptible individuals, could experience irreversible or other serious, long-lasting adverse health effects or an impaired ability to escape.

AEGL 3: The airborne concentration of a substance above which it is predicted that the general population, including susceptible individuals, could experience life-threatening health effects or death.

## Section 7 - HANDLING AND STORAGE

### PROCEDURE FOR HANDLING

- 
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- DO NOT allow material to contact humans, exposed food or food utensils.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.

- Launder contaminated clothing before re-use.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

### RECOMMENDED STORAGE METHODS

- Glass container.
- Lined metal can, Lined metal pail/drum
- Plastic pail
- Polyliner drum
- Packing as recommended by manufacturer.
- Check all containers are clearly labeled and free from leaks.

For low viscosity materials

- Drums and jerricans must be of the non-removable head type.
- Where a can is to be used as an inner package, the can must have a screwed enclosure.

For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.):


- Removable head packaging;
- Cans with friction closures and
- low pressure tubes and cartridges may be used.

- Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packages \* . - In addition, where inner packagings are glass and contain liquids of packing group I and II there must be sufficient inert absorbent to absorb any spillage \* . - \* unless the outer packaging is a close fitting molded plastic box and the substances are not incompatible with the plastic. All inner and sole packagings for substances that have been assigned to Packaging Groups I or II on the basis of inhalation toxicity criteria, must be hermetically sealed.

### STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

### SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



X: Must not be stored together

O: May be stored together with specific preventions

+: May be stored together

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m <sup>3</sup>	STEL ppm	STEL mg/m <sup>3</sup>	Peak ppm	Peak mg/m <sup>3</sup>	TWA F/CC	Notes
US ACGIH Threshold Limit Values (TLV)	arsenic pentoxide (Arsenic pentoxide)		0.01						TLV Basis: lung cancer. Measured as As
Canada - Prince Edward Island Occupational Exposure Limits	arsenic pentoxide (Arsenic pentoxide)		0.01						TLV Basis: lung cancer. Measured as As
Canada - Nova Scotia Occupational Exposure Limits	arsenic pentoxide (Arsenic pentoxide)		0.01						TLV Basis: lung cancer. Measured as As
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	arsenic pentoxide (Arsenic and compounds (as As))	-	0.5	-	0.5				
US - California Permissible Exposure Limits for Chemical Contaminants	arsenic pentoxide (Arsenic and inorganic arsenic compounds; see also Section 5214)		0.01						

US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants	arsenic pentoxide (Arsenic, inorganic compounds (as As); see 1910.1018.)	Varies with compound		
Canada - British Columbia Occupational Exposure Limits	arsenic pentoxide (Arsenic and inorganic compounds, as As)	0.01		A1, 1
US - Hawaii Air Contaminant Limits	arsenic pentoxide (Arsenic, inorganic compounds, (as As))	0.01		See °12-202-31
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	arsenic pentoxide (Arsenic, and inorganic compounds, (as As))	0.01	0.03	T20
US - Washington Permissible exposure limits of air contaminants	arsenic pentoxide (Arsenic, inorganic compounds (as As) (when use is covered by chapter 296-848 WAC))	0.01		
US - Washington Permissible exposure limits of air contaminants	arsenic pentoxide (Arsenic, inorganic compounds (as As) (when use is not covered by chapter 296-848 WAC))	0.2	0.6	
US NIOSH Recommended Exposure Limits (RELs)	arsenic pentoxide (Arsenic (inorganic compounds, as As))			0.002
Canada - Alberta Occupational Exposure Limits	arsenic pentoxide (Arsenic, elemental & inorganic compounds as As)	0.01		
US OSHA Permissible Exposure Levels (PELs) - Table Z1	arsenic pentoxide (Arsenic, inorganic compounds (as As); see 1910.1018)	0.01		
US - Michigan Exposure Limits for Air Contaminants	arsenic pentoxide (Arsenic, inorganic compounds (as As); see R 325.51601 et seq.F)	0.01		
US - Oregon Permissible Exposure Limits (Z1)	arsenic pentoxide (Arsenic, Inorganic Compounds (as As))	0.01		(TWA (See 1910.1018))
Canada - Northwest Territories Occupational Exposure Limits (English)	arsenic pentoxide (Arsenic & soluble compounds (as As))	0.2	0.6	
US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants	arsenic pentoxide (Arsenic, organic compounds (as As))	0.5		
Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)	arsenic pentoxide (Arsenic, elemental, and inorganic compounds (except Arsine), (as As))	0.1		

#### EMERGENCY EXPOSURE LIMITS

Material	Revised IDLH Value (mg/m3)	Revised IDLH Value (ppm)
arsenic pentoxide	5	

#### MATERIAL DATA

##### ARSENIC PENTOXIDE:

• Inorganic arsenic compounds appear to produce an increased incidence of skin and lung cancers following their use in medicine, after drinking arsenic-contaminated water, or after occupational exposure. Cancers at other sites have been described but a clear association has, as yet, to be determined.

Use control measures / protective gear to avoid any personal contact. The ES-TWA is based solely on the prevention of systemic effects due to inhalation and is not protective against the substantial risk of cancer produced by exposure to inorganic arsenic. Some jurisdictions require health surveillance be performed on occupationally exposed workers.

Such surveillance should emphasize

- demography, occupational and medical history and health advice
- physical examination with emphasis on the peripheral nervous system and skin.
- urinary total arsenic



- records of personal exposure

(measured as inhalable fraction of the aerosol).

Currently available analytical methods for monitoring workplace concentrations in most cases yield total levels of the elements arsenic, nickel or cobalt in the substances analyzed. The differentiation of the type of chemical compound, which is necessary from a toxicological standpoint, is frequently not possible without special analytical measures. Because of such difficulties in the identification of individual compounds of these elements, it is recommended that the threshold values be applied in general for the relevant element and its compounds as a basis for meeting safety precautions, even if it has not been analytically proved that carcinogenic compounds of these elements are present in the work area.

It is recommended that this TRK value also be used as a basis for protective measures for arsenic and all its compounds which are not mentioned here (with the exception of arsine).

The threshold value is based on analysis of metal content.

The technical exposure limit, TRK (Technische Richtkonzentrationen), defines the airborne concentration of named carcinogenic materials which is the minimum possible given the state of current technologies. TRK values are assigned only for materials for which there is no current MAK (German exposure standard). Observance of the TRK value is intended to reduce the risk of adverse effects on health but does NOT completely eliminate it. Since no threshold doses can be determined for carcinogens, health considerations require that the exposure limits be kept as far as possible below the TRK and that the TRK value be gradually reduced. The limitation of exposure peaks is regulated as follows; Short-term exposure limit: 5 x TRK Short-term exposure duration: 15 min/average Frequency per work shift: 5 times Interval: 1 hour. Report No. 35 1999, Deutsche Forschungsgemeinschaft.

TRK: 0.1 mg/m<sup>3</sup>

## PERSONAL PROTECTION



Consult your EHS staff for recommendations

### EYE

.

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses pose a special hazard; soft lenses may absorb irritants and all lenses concentrate them. DO NOT wear contact lenses.

### HANDS/FEET

• Wear chemical protective gloves, eg. PVC.

Wear safety footwear or safety gumboots, eg. Rubber.

NOTE: The material may produce skin sensitization in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: such as:

- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and
- dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739).

- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended.
- When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended.
- Contaminated gloves should be replaced.

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

### OTHER

.

- Prior to each exit from an area containing confirmed human carcinogens, employees should be required to remove and leave protective clothing and equipment at the point of exit and at the last exit of the day, to place used clothing and equipment in impervious containers at the point of exit for purposes of decontamination or disposal. The contents of such impervious containers must be identified with suitable labels. For maintenance and decontamination activities, authorized employees entering the area should be provided with and required to wear clean, impervious garments, including gloves, boots and continuous-air supplied hood.
- Prior to removing protective garments the employee should undergo decontamination and be required to shower upon removal of the garments and hood.
- Employees working with confirmed human carcinogens should be provided with, and be required to wear, clean, full body protective clothing (smocks, coveralls, or long-sleeved shirt and pants), shoe covers and gloves prior to entering the regulated area.
- Employees engaged in handling operations involving carcinogens should be provided with, and required to wear and use half-face filter-type respirators with filters for dusts, mists and fumes, or air purifying canisters or cartridges. A respirator affording higher levels of protection may be substituted.
- Emergency deluge showers and eyewash fountains, supplied with potable water, should be located near, within sight of, and on the same level with locations where direct exposure is likely.
- Overalls.
- Eyewash unit.

- Barrier cream.
- Skin cleansing cream.
- 
- Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.
- The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).
- Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory . These may be government mandated or vendor recommended.
- Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.
- Use approved positive flow mask if significant quantities of dust becomes airborne.
- Try to avoid creating dust conditions.

## RESPIRATOR

Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
10 x PEL	P1	-	PAPR-P1
	Air-line*	-	-
50 x PEL	Air-line**	P2	PAPR-P2
100 x PEL	-	P3	-
	-	Air-line*	-
100+ x PEL	-	Air-line**	PAPR-P3

\* - Negative pressure demand \*\* - Continuous flow

Explanation of Respirator Codes:

Class 1 low to medium absorption capacity filters.

Class 2 medium absorption capacity filters.

Class 3 high absorption capacity filters.

PAPR Powered Air Purifying Respirator (positive pressure) cartridge.

Type A for use against certain organic gases and vapors.

Type AX for use against low boiling point organic compounds (less than 65°C).

Type B for use against certain inorganic gases and other acid gases and vapors.

Type E for use against sulfur dioxide and other acid gases and vapors.

Type K for use against ammonia and organic ammonia derivatives

Class P1 intended for use against mechanically generated particulates of sizes most commonly encountered in industry, e.g. asbestos, silica.

Class P2 intended for use against both mechanically and thermally generated particulates, e.g. metal fume.

Class P3 intended for use against all particulates containing highly toxic materials, e.g. beryllium.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

Use appropriate NIOSH-certified respirator based on informed professional judgement. In conditions where no reasonable estimate of exposure can be made, assume the exposure is in a concentration IDLH and use NIOSH-certified full face pressure demand SCBA with a minimum service life of 30 minutes, or a combination full facepiece pressure demand SAR with auxiliary self-contained air supply. Respirators provided only for escape from IDLH atmospheres shall be NIOSH-certified for escape from the atmosphere in which they will be used.

## ENGINEERING CONTROLS

- Employees exposed to confirmed human carcinogens should be authorized to do so by the employer, and work in a regulated area.
- Work should be undertaken in an isolated system such as a "glove-box" . Employees should wash their hands and arms upon completion of the assigned task and before engaging in other activities not associated with the isolated system.
- Within regulated areas, the carcinogen should be stored in sealed containers, or enclosed in a closed system, including piping systems, with any sample ports or openings closed while the carcinogens are contained within.
- Open-vessel systems are prohibited.
- Each operation should be provided with continuous local exhaust ventilation so that air movement is always from ordinary work areas to the operation.
- Exhaust air should not be discharged to regulated areas, non-regulated areas or the external environment unless decontaminated. Clean make-up air should be introduced in sufficient volume to maintain correct operation of the local exhaust system.
- For maintenance and decontamination activities, authorized employees entering the area should be provided with and required to wear clean, impervious garments, including gloves, boots and continuous-air supplied hood. Prior to removing protective garments the employee should undergo decontamination and be required to shower upon removal of the garments and hood.
- Except for outdoor systems, regulated areas should be maintained under negative pressure (with respect to non-regulated areas).
- Local exhaust ventilation requires make-up air be supplied in equal volumes to replaced air.
- Laboratory hoods must be designed and maintained so as to draw air inward at an average linear face velocity of 150 feet/ min. with a minimum of 125 feet/ min. Design and construction of the fume hood requires that insertion of any portion of the employees body, other than hands and arms, be disallowed.

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

### PHYSICAL PROPERTIES

Solid.

Mixes with water.

State	Divided solid	Molecular Weight	229.84
Melting Range (°F)	599 (decomposes)	Viscosity	Not Applicable
Boiling Range (°F)	Not available.	Solubility in water (g/L)	Miscible
Flash Point (°F)	Not applicable	pH (1% solution)	Not available.
Decomposition Temp (°F)	Not Available	pH (as supplied)	Not applicable
Autoignition Temp (°F)	Not applicable	Vapour Pressure (mmHG)	Negligible.
Upper Explosive Limit (%)	Not applicable	Specific Gravity (water=1)	4.32
Lower Explosive Limit (%)	Not applicable	Relative Vapor Density (air=1)	Not Applicable
Volatile Component (%vol)	Not available.	Evaporation Rate	Not Applicable

## APPEARANCE

White, deliquescent, amorphous lumps or powder. Freely soluble in water. Soluble in alcohol. Combines very slowly with water to form arsenic acid. May be shipped as a concentrated water solution.

## Section 10 - CHEMICAL STABILITY

### CONDITIONS CONTRIBUTING TO INSTABILITY

- 
- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerization will not occur.

### STORAGE INCOMPATIBILITY

- 
- Contact with acids produces toxic fumes

Arsine, an extremely poisonous (lethal) gas with a garlic odour can be generated when the material reacts with acids, alkalis or water in the presence of an active metal (zinc, aluminium, magnesium, sodium, iron etc.).

- Avoid strong acids, bases.

Metals and their oxides or salts may react violently with chlorine trifluoride. Chlorine trifluoride is a hypergolic oxidizer. It ignites on contact (without external source of heat or ignition) with recognized fuels - contact with these materials, following an ambient or slightly elevated temperature, is often violent and may produce ignition. The state of subdivision may affect the results.

For incompatible materials - refer to Section 7 - Handling and Storage.

## Section 11 - TOXICOLOGICAL INFORMATION

arsenic pentoxide

### TOXICITY AND IRRITATION

• unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY	IRRITATION
Oral (rat) LD50: 8 mg/kg	Nil Reported
Oral (mouse) LD50: 55 mg/kg	

• Arsenic compounds are classified by the European Union as toxic by inhalation and ingestion and toxic to aquatic life and long lasting in the environment. IARC classify arsenic indrinikng water as a confirmed human carcinogen (IARC 1).

Tenth Annual Report on Carcinogens: Substance known to be Carcinogenic  
[National Toxicology Program: U.S. Dep. of Health and Human Services 2002].

Paternal effects recorded

WARNING: Arsenic pentoxide has been listed by IARC as possessing  
Human Sufficient Evidence leading to the conclusion that it  
may be carcinogenic.

### CARCINOGEN

Arsenic and arsenic compounds (NB: This evaluation applies to the group of compounds as a whole and not necessarily to all individual compounds within the group)	International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs	Group	1
Arsenic, inorganic	ND	Carcinogenicity	A
Arsenic, inorganic	ND	Carcinogen Category	A
Arsenic pentoxide	ND	Carcinogen Category	A1
ARSENIC PENTOXIDE	US Environmental Defense Scorecard Recognized Carcinogens	Reference(s)	P65-MC

INORGANIC ARSENIC COMPOUNDS	US Environmental Defense Scorecard Recognized Carcinogens	Reference(s)	P65
ARSENIC PENTOXIDE	US Environmental Defense Scorecard Suspected Carcinogens	Reference(s)	P65-MC
INORGANIC ARSENIC COMPOUNDS	US Environmental Defense Scorecard Suspected Carcinogens	Reference(s)	P65
ARSENIC COMPOUNDS	US Environmental Defense Scorecard Suspected Carcinogens	Reference(s)	HAZMAP, IARC
Arsenic and its compounds (Inorganic) (as As)	ND	Carcinogen	Ca

### SKIN

arsenic pentoxide	ND		Skin	X
arsenic pentoxide	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants - Skin		Skin Designation	X
arsenic pentoxide	US - Washington Permissible exposure limits of air contaminants - Skin		Skin	X
arsenic pentoxide	US - Hawaii Air Contaminant Limits - Skin Designation		Skin Designation	X
arsenic pentoxide	US - California Permissible Exposure Limits for Chemical Contaminants - Skin		Skin	X

## Section 12 - ECOLOGICAL INFORMATION

Refer to data for ingredients, which follows:

#### ARSENIC PENTOXIDE:

• Hazardous Air Pollutant:	Yes
• Fish LC50 (96hr.) (mg/l):	0.01
• Daphnia magna EC50 (48hr.) (mg/l):	1.4 (3 wee

- Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

- Speciation of arsenic is an important consideration in the fate, movement, and action of this substance. Chemical and biochemical transformations of arsenic include oxidation, reduction and methylation which affects its volatilization, adsorption, dissolution and biological disposition. The transport of arsenic in the environment is largely controlled by absorption/ desorption processes in soils and sediments. Sediment movement is responsible for transport of arsenic soil residues to their ultimate sinks in deep ocean sediments. The clay fraction, plus ferrous and aluminum oxides which coat clay particles, adsorb arsenicals which then undergo transformation as discussed earlier. Conversions of arsenic to volatile alkylarsines leads to air transport losses from soil. Inorganic arsenic occurs in water in different oxidation states depending on the pH and Eh of the water. Arsenate is apparently reduced by bacteria to arsenite in marine environments because the ratio of total arsenate to total arsenic is much lower than that predicted thermodynamically. Methylation of arsenic occurs in both freshwater and marine systems where arsenate occurs as arsenate, arsenite, methanearsonic acid and dimethylarsinic acid. Arsenate predominates because this is the most stable form.

Bioaccumulation occurs in some aquatic species such as seaweeds, freshwater algae and crustaceans. Some arsenic in water flea (Daphnia Magna) and algae occurs as arseno-analogues of phospholipids leading to the mistaken impression that accumulation and utilization of arsenic takes place at the expense of phosphate. Crabs, lobsters and other marine organisms accumulate organo-arsenicals in the food chain. Although human activity may alter the local picture of environmental arsenic there is little evidence that this affects the global scale arsenic cycle.

Airborne concentrations of arsenic in urban areas may range from a few nanograms to a few tenths of a microgram per cubic meter; airborne arsenic is generally inorganic. In oxygenated soils inorganic arsenic is present in pentavalent form; under reducing conditions it occurs as the trivalent form.

Drinking Water Standards:

arsenic: 50 ug/l (UK max.) 0.01mg/L (WHO provisional guideline)

chloride:400 mg/l (UK max.)

250 mg/l (WHO guideline)

Soil Guideline:

Dutch Criteria: 29 mg/kg (target)

55 mg/kg (intervention)

Air Quality Standard:

No safe levels recommended due to carcinogenic properties (WHO guideline).

- DO NOT discharge into sewer or waterways.

#### Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
arsenic pentoxide			LOW	

## Section 13 - DISPOSAL CONSIDERATIONS

### US EPA Waste Number & Descriptions

#### A. General Product Information

Toxicity characteristic: use EPA hazardous waste number D004 (waste code E) if this substance, in a solid waste, produces an extract containing greater than 5 mg/L of arsenic.

#### B. Component Waste Numbers

When arsenic pentoxide is present as a solid waste as a discarded commercial chemical product, off-specification species, as a container residue, or a spill residue, use EPA waste number P011 (waste code T).

### Disposal Instructions

All waste must be handled in accordance with local, state and federal regulations.

- Puncture containers to prevent re-use and bury at an authorized landfill.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- Reuse
- Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

DO NOT allow wash water from cleaning equipment to enter drains. Collect all wash water for treatment before disposal.

- Recycle wherever possible or consult manufacturer for recycling options.
- Consult Waste Management Authority for disposal.
- Bury residue in an authorized landfill.
- Recycle containers where possible, or dispose of in an authorized landfill.

## Section 14 - TRANSPORTATION INFORMATION



DOT:

Symbols:	None	Hazard class or Division:	6.1
Identification Numbers:	UN1559	PG:	II
Label Codes:	6.1	Special provisions:	IB8, IP2, IP4, T3, TP33
Packaging: Exceptions:	153	Packaging: Non-bulk:	212
Packaging: Exceptions:	153	Quantity limitations: Passenger aircraft/rail:	25 kg
Quantity Limitations: Cargo aircraft only:	100 kg	Vessel stowage: Location:	A
Vessel stowage: Other:	None		

Hazardous materials descriptions and proper shipping names:

Arsenic pentoxide

### Air Transport IATA:

ICAO/IATA Class:	6.1	ICAO/IATA Subrisk:	None
UN/ID Number:	1559	Packing Group:	II
Special provisions:	None		

Shipping Name: ARSENIC PENTOXIDE

### Maritime Transport IMDG:

IMDG Class:	6.1	IMDG Subrisk:	None
UN Number:	1559	Packing Group:	II
EMS Number:	F-A,S-A	Special provisions:	None

Limited Quantities: 500 g

Shipping Name: ARSENIC PENTOXIDE

## Section 15 - REGULATORY INFORMATION

**arsenic pentoxide (CAS: 1303-28-2,12044-50-7) is found on the following regulatory lists;**

"Canada - Nova Scotia Occupational Exposure Limits", "Canada - Prince Edward Island Occupational Exposure Limits", "Canada Domestic Substances List (DSL)", "Canada Ingredient Disclosure List (SOR/88-64)", "Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS (English)", "Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS (French)", "International Chemical Secretariat (ChemSec) REACH SIN\* List (\*Substitute It Now!) 1.0", "US - California Occupational Safety and Health Regulations (CAL/OSHA) - Hazardous Substances List", "US - Connecticut Hazardous Air Pollutants", "US - Maine Chemicals of High Concern List", "US - Massachusetts Oil & Hazardous Material List", "US - New Jersey Right to Know Hazardous Substances", "US - Pennsylvania - Hazardous Substance List", "US - Vermont Hazardous Constituents", "US - Vermont Hazardous Waste - Acutely Hazardous Wastes", "US - Washington Discarded Chemical Products List - ""P"" Chemical Products", "US ACGIH Threshold Limit Values (TLV)", "US ACGIH Threshold Limit Values (TLV) - Carcinogens", "US CWA (Clean Water Act) - List of Hazardous Substances", "US CWA (Clean Water Act) - Reportable Quantities of Designated Hazardous Substances", "US Department of Transportation (DOT) List of Hazardous Substances and Reportable Quantities - Hazardous Substances Other Than Radionuclides", "US DOE Temporary Emergency Exposure Limits (TEELs)", "US EPA Acute Exposure Guideline Levels (AEGs) - Holding", "US List of Lists - Consolidated List of Chemicals Subject to the Emergency Planning and Community Right-to-Know Act (EPCRA) and Section 112(r) of the Clean Air Act", "US RCRA (Resource Conservation & Recovery Act) - Hazardous Constituents - Appendix VIII to 40 CFR 261", "US RCRA (Resource Conservation & Recovery Act) - List of Hazardous Wastes", "US SARA Section 302 Extremely Hazardous Substances", "US Toxic Substances Control Act (TSCA) - Inventory"

**Section 16 - OTHER INFORMATION**

**LIMITED EVIDENCE**

- Skin contact may produce health damage\*.
- Cumulative effects may result following exposure\*.
- May produce discomfort of the respiratory system and skin\*.
- Possible skin sensitizer\*.

\* (limited evidence).

**Ingredients with multiple CAS Nos**

Ingredient Name	CAS
arsenic pentoxide	1303-28-2, 12044-50-7

*Reasonable care has been taken in the preparation of this information, but the author makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The author makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. For additional technical information please call our toxicology department on +800 CHEMCALL.*

• Classification of the mixture and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:  
[www.chemwatch.net/references](http://www.chemwatch.net/references).

• The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

*This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.*

Issue Date: Jun-7-2008

Print Date: Jun-8-2010