



SZABO SCANDIC

Part of Europa Biosite

Produktinformation



Forschungsprodukte & Biochemikalien



Zellkultur & Verbrauchsmaterial



Diagnostik & molekulare Diagnostik



Laborgeräte & Service

Weitere Information auf den folgenden Seiten!
See the following pages for more information!



Lieferung & Zahlungsart

siehe unsere [Liefer- und Versandbedingungen](#)

Zuschläge

- Mindermengenzuschlag
- Trockeneiszuschlag
- Gefahrgutzuschlag
- Expressversand

SZABO-SCANDIC HandelsgmbH

Quellenstraße 110, A-1100 Wien

T. +43(0)1 489 3961-0

F. +43(0)1 489 3961-7

mail@szabo-scandic.com

www.szabo-scandic.com

[linkedin.com/company/szaboscandic](https://www.linkedin.com/company/szaboscandic) 

Chloro(pyridine)bis(dimethylglyoximato)cobalt(III)

sc-234319



The Power is Question

Material Safety Data Sheet

Hazard Alert Code
Key:

EXTREME

HIGH

MODERATE

LOW

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION


PRODUCT NAME

Chloro(pyridine)bis(dimethylglyoximato)cobalt(III)

STATEMENT OF HAZARDOUS NATURE

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

NFPA



SUPPLIER

Company: Santa Cruz Biotechnology, Inc.

Address:

2145 Delaware Ave

Santa Cruz, CA 95060

Telephone: 800.457.3801 or 831.457.3800

Emergency Tel: CHEMWATCH: From within the US and
Canada: 877-715-9305

Emergency Tel: From outside the US and Canada: +800 2436
2255 (1-800-CHEMCALL) or call +613 9573 3112

PRODUCT USE

- Reagent.

SYNONYMS

C13-H19-Cl-Co-N5-O4, "chloro(pyridine)cobaloxime (III)", "chloro(pyridine)cobaloxime (III)"

Section 2 - HAZARDS IDENTIFICATION

CANADIAN WHMIS SYMBOLS



EMERGENCY OVERVIEW

RISK

Irritating to eyes, respiratory system and skin.

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

- Accidental ingestion of the material may be damaging to the health of the individual.
- In toxic doses soluble cobalt salts produce stomach pain and vomiting, flushing of the face and ears, rash, ringing in the ears, nervous deafness and reduced blood flow to the extremities.

EYE

- This material can cause eye irritation and damage in some persons.

SKIN

- This material can cause inflammation of the skin on contact in some persons.
- The material may accentuate any pre-existing dermatitis condition.
- Skin contact is not thought to have harmful health effects, however the material may still produce health damage following entry through wounds, lesions or abrasions.
- Open cuts, abraded or irritated skin should not be exposed to this material.
- Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

INHALED

- The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.
- Inhalation of dusts, generated by the material during the course of normal handling, may be damaging to the health of the individual.
- Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.
- Cobalt poisoning can cause inflammation of the terminal airways (bronchioles), and cause lethargy and death within hours.

CHRONIC HEALTH EFFECTS

- Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems.






Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.

Long term exposure to high dust concentrations may cause changes in lung function i.e. pneumoconiosis; caused by particles less than 0.5 micron penetrating and remaining in the lung. Prime symptom is breathlessness; lung shadows show on X-ray.


Inhalation of cobalt powder can induce asthma, chest tightness and chronic inflammation of the bronchi. Chronic exposure to cobalt causes increase in blood hemoglobin, increased production of cells in the blood marrow and thyroid gland, discharge from around the heart and damage to the alpha cells of the pancreas. Long-term administration has caused goiter (overactivity of the thyroid) and reduced thyroid activity. Allergic inflammation of the skin may appear following exposure to cobalt, usually exhibited as red patches. Injection of cobalt can cause cancer at the site of entry.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

HAZARD RATINGS

	Min	Max	
Flammability:	1		
Toxicity:	2		
Body Contact:	2		
Reactivity:	1		
Chronic:	2		

Min/Nil=0
Low=1
Moderate=2
High=3
Extreme=4



NAME	CAS RN	%
chloro(pyridine)bis(dimethylglyoximate)cobalt(III)	23295-32-1	>98

Section 4 - FIRST AID MEASURES

SWALLOWED

-
- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Seek medical advice.

EYE

- If this product comes in contact with the eyes:
 - Wash out immediately with fresh running water.
 - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
 - If pain persists or recurs seek medical attention.
 - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin contact occurs:
 - Immediately remove all contaminated clothing, including footwear.
 - Flush skin and hair with running water (and soap if available).
 - Seek medical attention in event of irritation.

INHALED

-
- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket

- mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor, without delay.

NOTES TO PHYSICIAN

- Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES

Vapour Pressure (mmHG):	Negligible
Upper Explosive Limit (%):	Not available.
Specific Gravity (water=1):	Not available
Lower Explosive Limit (%):	Not available

EXTINGUISHING MEDIA

-
- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog - Large fires only.

FIRE FIGHTING

-
- Alert Emergency Responders and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- Use water delivered as a fine spray to control fire and cool adjacent area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

GENERAL FIRE HAZARDS/HAZARDOUS COMBUSTIBLE PRODUCTS

-
- Combustible solid which burns but propagates flame with difficulty.
- Avoid generating dust, particularly clouds of dust in a confined or unventilated space as dusts may form an explosive mixture with air, and any source of ignition, i.e. flame or spark, will cause fire or explosion. Dust clouds generated by the fine grinding of the solid are a particular hazard; accumulations of fine dust may burn rapidly and fiercely if ignited.
- Dry dust can be charged electrostatically by turbulence, pneumatic transport, pouring, in exhaust ducts and during transport.
- Build-up of electrostatic charge may be prevented by bonding and grounding.
- Powder handling equipment such as dust collectors, dryers and mills may require additional protection measures such as explosion venting.

Combustion products include: carbon monoxide (CO), carbon dioxide (CO₂), hydrogen chloride, phosgene, nitrogen oxides (NO_x), metal oxides, other pyrolysis products typical of burning organic material.

May emit poisonous fumes.

May emit corrosive fumes.

FIRE INCOMPATIBILITY

- Avoid contamination with oxidizing agents i.e. nitrates, oxidizing acids, chlorine bleaches, pool chlorine etc. as ignition may result.

PERSONAL PROTECTION

Glasses:

Chemical goggles.

Gloves:

Respirator:

Particulate

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

-
- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid contact with skin and eyes.
- Control personal contact by using protective equipment.
- Use dry clean up procedures and avoid generating dust.
- Place in a suitable, labelled container for waste disposal.

MAJOR SPILLS

- Moderate hazard.
- CAUTION: Advise personnel in area.
- Alert Emergency Responders and tell them location and nature of hazard.
- Control personal contact by wearing protective clothing.
- Prevent, by any means available, spillage from entering drains or water courses.
- Recover product wherever possible.
- IF DRY: Use dry clean up procedures and avoid generating dust. Collect residues and place in sealed plastic bags or other containers for disposal. IF WET: Vacuum/shovel up and place in labelled containers for disposal.
- ALWAYS: Wash area down with large amounts of water and prevent runoff into drains.

- If contamination of drains or waterways occurs, advise emergency services.

ACUTE EXPOSURE GUIDELINE LEVELS (AEGL) (in ppm)

AEGL 1: The airborne concentration of a substance above which it is predicted that the general population, including susceptible individuals, could experience notable discomfort, irritation, or certain asymptomatic nonsensory effects. However, the effects are not disabling and are transient and reversible upon cessation of exposure.

AEGL 2: The airborne concentration of a substance above which it is predicted that the general population, including susceptible individuals, could experience irreversible or other serious, long-lasting adverse health effects or an impaired ability to escape.

AEGL 3: The airborne concentration of a substance above which it is predicted that the general population, including susceptible individuals, could experience life-threatening health effects or death.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- DO NOT allow material to contact humans, exposed food or food utensils.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Launder contaminated clothing before re-use.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

Empty containers may contain residual dust which has the potential to accumulate following settling. Such dusts may explode in the presence of an appropriate ignition source.

- Do NOT cut, drill, grind or weld such containers
- In addition ensure such activity is not performed near full, partially empty or empty containers without appropriate workplace safety authorisation or permit.

RECOMMENDED STORAGE METHODS

- Glass container.
- Polyethylene or polypropylene container.
- Check all containers are clearly labelled and free from leaks.

STORAGE REQUIREMENTS

-
- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



X: Must not be stored together

O: May be stored together with specific preventions

+: May be stored together

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	TWA F/CC	Notes
--------	----------	---------	-----------------------	----------	------------------------	----------	------------------------	----------	-------

Canada - Yukon

Permissible Concentrations for Airborne Contaminant Substances	chloro(pyridine)bis(dimethylglyoximato)cobalt(III) (Cobalt metal, dust and fume (as Co))	0.05	0.15
US - Washington Permissible exposure limits of air contaminants	chloro(pyridine)bis(dimethylglyoximato)cobalt(III) (Cobalt, metal fume & dust (as Co))	0.05	0.15
US OSHA Permissible Exposure Levels (PELs) - Table Z3	chloro(pyridine)bis(dimethylglyoximato)cobalt(III) (Inert or Nuisance Dust: (d) Total dust)	15	
US OSHA Permissible Exposure Levels (PELs) - Table Z3	chloro(pyridine)bis(dimethylglyoximato)cobalt(III) (Inert or Nuisance Dust: (d) Respirable fraction)	5	
US - Hawaii Air Contaminant Limits	chloro(pyridine)bis(dimethylglyoximato)cobalt(III) (Particulates not other wise regulated - Respirable fraction)	5	
US - Hawaii Air Contaminant Limits	chloro(pyridine)bis(dimethylglyoximato)cobalt(III) (Particulates not other wise regulated - Total dust)	10	
US - Oregon Permissible Exposure Limits (Z3)	chloro(pyridine)bis(dimethylglyoximato)cobalt(III) (Inert or Nuisance Dust: (d) Total dust)	10	*
US - Oregon Permissible Exposure Limits (Z3)	chloro(pyridine)bis(dimethylglyoximato)cobalt(III) (Inert or Nuisance Dust: (d) Respirable fraction)	5	*
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	chloro(pyridine)bis(dimethylglyoximato)cobalt(III) (Particulates not otherwise regulated Respirable fraction)	5	
US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants	chloro(pyridine)bis(dimethylglyoximato)cobalt(III) (Particulates not otherwise regulated (PNOR)(f)-Respirable fraction)	5	
US - Michigan Exposure Limits for Air Contaminants	chloro(pyridine)bis(dimethylglyoximato)cobalt(III) (Particulates not otherwise regulated, Respirable dust)	5	

MATERIAL DATA

CHLORO(PYRIDINE)BIS(DIMETHYLGLYOXIMATO)COBALT(III):

■ In view of the serious effects seen in experimental animals after a relatively short exposure period at 0.1 mg/m³ the recommended TLV-TWA is thought to reduce the significant risk of material impairment of health posed by respiratory disease and pulmonary sensitization which have been shown to occur at higher levels of exposure. The value does not apply generally to cobalt compounds. A significant increase in the risk of lung cancer was reported among workers involved in cobalt production (with concomitant exposure to nickel and arsenic) and hard-metal workers with documented exposure to cobalt-containing dusts. A significant increase in lung cancer risk has been observed in workers whose exposure began more than 20 years previously. A number of single cases of malignant tumors, mostly sarcomas, have been reported at the site, following implant of cobalt-containing orthopedic implants. TRK: 0.5 mg/m³ (in the form of cobalt metal, cobalt oxide, and cobalt sulfide) during production of cobalt powder and catalysts: hard metal (tungsten carbide) and magnet production (processing of powder, machine pressing and mechanical processing of unsintered articles) : 0.1 mg/m³ (others) measured as inhalable fraction of the aerosol. The technical exposure limit, TRK (Technische Richtkonzentrationen), defines the airborne concentration of named carcinogenic materials which is the minimum possible given the state of current technologies. TRK values are assigned only for materials for which there is no current MAK (German exposure standard). Observance of the TRK value is intended to reduce the risk of adverse effects on health but does NOT completely eliminate it. Since no threshold doses can be determined for carcinogens, health considerations require that the exposure limits be kept as far as possible below the TRK and that the TRK value be gradually reduced. The limitation of exposure peaks is regulated as follows; Short-term exposure limit: 5 x TRK Short-term exposure duration: 15 min/average Frequency per work shift: 5 times Interval: 1 hour. Report No. 35 1999, Deutsche Forschungsgemeinschaft.

PERSONAL PROTECTION



Consult your EHS staff for recommendations

EYE

-
- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses pose a special hazard; soft lenses may absorb irritants and all lenses concentrate them. DO NOT wear contact lenses.

HANDS/FEET

- Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: such as:
 - frequency and duration of contact,
 - chemical resistance of glove material,
 - glove thickness and
 - dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739).

- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended.
- When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended.
- Contaminated gloves should be replaced.

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Experience indicates that the following polymers are suitable as glove materials for protection against undissolved, dry solids, where abrasive particles are not present.

- polychloroprene
- nitrile rubber
- butyl rubber
- fluorocautchouc
- polyvinyl chloride

Gloves should be examined for wear and/ or degradation constantly.

OTHER

-
- Overalls.
- P.V.C. apron.
- Barrier cream.
- Skin cleansing cream.
- Eye wash unit.
-
- Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.
- The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).
- Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory . These may be government mandated or vendor recommended.
- Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.
- Use approved positive flow mask if significant quantities of dust becomes airborne.
- Try to avoid creating dust conditions.

RESPIRATOR

Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
10 x PEL	P1	-	PAPR-P1
	Air-line*	-	-
50 x PEL	Air-line**	P2	PAPR-P2
100 x PEL	-	P3	-
	-	Air-line*	-
100+ x PEL	-	Air-line**	PAPR-P3

* - Negative pressure demand ** - Continuous flow

Explanation of Respirator Codes:

Class 1 low to medium absorption capacity filters.

Class 2 medium absorption capacity filters.

Class 3 high absorption capacity filters.

PAPR Powered Air Purifying Respirator (positive pressure) cartridge.

Type A for use against certain organic gases and vapors.

Type AX for use against low boiling point organic compounds (less than 65°C).

Type B for use against certain inorganic gases and other acid gases and vapors.

Type E for use against sulfur dioxide and other acid gases and vapors.

Type K for use against ammonia and organic ammonia derivatives

Class P1 intended for use against mechanically generated particulates of sizes most commonly encountered in industry, e.g. asbestos, silica.

Class P2 intended for use against both mechanically and thermally generated particulates, e.g. metal fume.

Class P3 intended for use against all particulates containing highly toxic materials, e.g. beryllium.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

Use appropriate NIOSH-certified respirator based on informed professional judgement. In conditions where no reasonable estimate of exposure can be made, assume the exposure is in a concentration IDLH and use NIOSH-certified full face pressure demand SCBA with a minimum service life of 30 minutes, or a combination full facepiece pressure demand SAR with auxiliary self-contained air supply. Respirators provided only for escape from IDLH atmospheres shall be NIOSH-certified for escape from the atmosphere in which they will be used.

ENGINEERING CONTROLS

-
- Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively

large, a certain proportion will be powdered by mutual friction.

- Exhaust ventilation should be designed to prevent accumulation and recirculation of particulates in the workplace.
- If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered. Such protection might consist of:
 - (a): particle dust respirators, if necessary, combined with an absorption cartridge;
 - (b): filter respirators with absorption cartridge or canister of the right type;
 - (c): fresh-air hoods or masks
- Build-up of electrostatic charge on the dust particle, may be prevented by bonding and grounding.
- Powder handling equipment such as dust collectors, dryers and mills may require additional protection measures such as explosion venting.

Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to efficiently remove the contaminant.

Type of Contaminant:	Air Speed:
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favorable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 4-10 m/s (800-2000 f/min) for extraction of crusher dusts generated 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL PROPERTIES

Solid.

Does not mix with water.

State	Divided solid	Molecular Weight	403.71
Melting Range (°F)	455 (decomposes)	Viscosity	Not Applicable
Boiling Range (°F)	Not applicable	Solubility in water (g/L)	Partly miscible
Flash Point (°F)	Not available	pH (1% solution)	Not applicable
Decomposition Temp (°F)	455	pH (as supplied)	Not applicable
Autoignition Temp (°F)	Not available	Vapour Pressure (mmHG)	Negligible
Upper Explosive Limit (%)	Not available.	Specific Gravity (water=1)	Not available
Lower Explosive Limit (%)	Not available	Relative Vapor Density (air=1)	Not Applicable
Volatile Component (%vol)	Negligible	Evaporation Rate	Not applicable

APPEARANCE

Green powder; does not mix well with water.

Section 10 - CHEMICAL STABILITY

CONDITIONS CONTRIBUTING TO INSTABILITY

-
- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerization will not occur.

STORAGE INCOMPATIBILITY

- Avoid reaction with oxidizing agents.

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

chloro(pyridine)bis(dimethylglyoximate)cobalt(III)

TOXICITY AND IRRITATION

- unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.
- Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production. These "dusts" have little adverse effect on the lungs and do not produce toxic effects or organic disease. Although there is no dust which does not evoke some cellular response at sufficiently high concentrations, the cellular response caused by P.N.O.C.s has the following characteristics:

- the architecture of the air spaces remain intact,
- scar tissue (collagen) is not synthesised to any degree,
- tissue reaction is potentially reversible.

Extensive concentrations of P.N.O.C.s may:

- seriously reduce visibility,
- cause unpleasant deposits in the eyes, ears and nasal passages,
- contribute to skin or mucous membrane injury by chemical or mechanical action, per se, or by the rigorous skin cleansing procedures necessary for their removal. [ACGIH]

This limit does not apply:

- to brief exposures to higher concentrations
- nor does it apply to those substances that may cause physiological impairment at lower concentrations but for which a TLV has as yet to be determined.

This exposure standard applies to particles which

- are insoluble or poorly soluble* in water or, preferably, in aqueous lung fluid (if data is available) and
- have a low toxicity (i.e.. are not cytotoxic, genotoxic, or otherwise chemically reactive with lung tissue, and do not emit ionizing radiation, cause immune sensitization, or cause toxic effects other than by inflammation or by a mechanism of lung overload)

CARCINOGEN

Cobalt and cobalt compounds (NB: Evaluated as a group)	International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs	Group	2B
COBALT COMPOUNDS	US Environmental Defense Scorecard Suspected Carcinogens	Reference(s)	IARC, P65-MC

Section 12 - ECOLOGICAL INFORMATION

Refer to data for ingredients, which follows:

CHLORO(PYRIDINE)BIS(DIMETHYLGLYOXIMATE)COBALT(III):

■ for cobalt compounds:

Environmental Fate:

Cobalt strongly binds to humic substances naturally present in aquatic environments. Humic acids can be modified by UV light and bacterial decomposition, which may change their binding characteristics over time. The lability of the complexes is strongly influenced by pH, the nature of the humic material, and the metal-to-humic substance ratio. The lability of cobalt-humate complexes decreases in time ("aging effect"). The "aging effect" indicates that after a period of time (~12 hours), complexes that were initially formed are transformed into stronger ones from which the metal ion is less readily dislodged.

Between 45 and 100% of dissolved cobalt was found to occur in very strong complexes. The distribution coefficient of cobalt may vary considerably in the same sediment in response to conditions affecting the pH, redox conditions, ionic strength, and amount of dissolved organic matter. Uptake of ⁶⁰Co from the water by sediment increased rapidly as the pH was increased from 5 to 7 -7.5 and then slightly decrease. Therefore, pH would be an important factor affecting the migration of cobalt in surface water. Uptake was little affected by changes in liquid-to-solids ratio and ionic strength. ⁶⁰Co is more mobile in anaerobic marine aquatic environments than in freshwater aerobic ones. In seawater sediment systems under anaerobic conditions ⁶⁰Co was 250 times more mobile than ⁶⁰Co in freshwater sediment systems under aerobic conditions. Under anaerobic conditions, 30% of the ⁶⁰Co added to a sediment-freshwater system was "exchangeable" and therefore potentially mobile, while under aerobic conditions, 98% of the ⁶⁰Co was permanently fixed. Most of the mobile ⁶⁰Co produced under anaerobic conditions in seawater consisted of nonionic cobalt associated with low molecular weight organic substances that were stable to changes in pH; the exchangeable ⁶⁰Co appeared to be mostly ionic.

The mobility of cobalt in soil is inversely related to how strongly it is adsorbed by soil constituents. Cobalt may be retained by mineral oxides such as iron and manganese oxide, crystalline materials such as aluminosilicate and goethite, and natural organic substances in soil. Sorption of cobalt to soil occurs rapidly (within 1-2 hours). Soil-derived oxide materials were found to adsorb greater amounts of cobalt than other materials examined, although substantial amounts were also adsorbed by organic materials.

Clay minerals sorbed relatively smaller amounts of cobalt. In addition, little cobalt was desorbed from soil oxides while

substantial amounts desorbed from humic acids and montorillonite. In clay soil, adsorption may be due to ion exchange at the cationic sites on clay with either simple ionic cobalt or hydrolysed ionic species such as CoOH^+ . Adsorption of cobalt onto iron and manganese increases with pH. In addition, as pH increases, insoluble hydroxides or carbonates may form, which would also reduce cobalt mobility. Conversely, sorption onto mobile colloids would enhance its mobility. In most soils, cobalt is more mobile than lead, chromium (II), zinc, and nickel, but less mobile than cadmium. In several studies, the K_d of cobalt in a variety of soils ranged from 0.2 to 3,800. The soil properties showing the highest correlation with K_d were exchangeable calcium, pH, water content, and cation exchange capacity. Organic complexing agents such as ethylenediaminetetraacetic acid (EDTA), which are used for decontamination operations at nuclear facilities, greatly enhance the mobility of cobalt in soil. Other organic complexing agents, such as those obtained from plant decay, may also increase cobalt mobility in soil. However, both types of complexes decrease cobalt uptake by plants. Addition of sewage sludge to soil also increases the mobility of cobalt, perhaps due to organic complexation of cobalt.

Cobalt may be taken up from soil by plants. Surface deposition of cobalt on leaves of plants from airborne particles may also occur. Elevated levels of cobalt have been found in the roots of sugar beets and potato tubers in soils with high cobalt concentrations (e.g., fly ash-amended soil) due to absorption of cobalt from soil. However, the translocation of cobalt from roots to above-ground parts of plants is not significant in most soils, as indicated by the lack of cobalt in seeds of barley, oats, and wheat grown in high-cobalt soil. However, in highly acidic soil (pH as low as 3.3), significantly higher than normal concentrations of cobalt were found in rye grass foliage, oats, and barley. For example, cobalt concentrations in rye grass grown in unlimed soil (pH<5.0) was 19.7 mg/kg compared with 1.1 mg/kg in rye grass grown in limed soil (pH>5.0). Soil and plant samples taken in the 30-km zone around Chernobyl indicated that ^{60}Co was not accumulated by plants and mushrooms. Studies investigating the uptake of ^{60}Co by tomato plants watered with ^{60}Co contaminated water showed that tomato plants absorbed <2% of the activity available from the soil.

^{60}Co is taken up by phytoplankton and unicellular algae (*Senenastrum capricornutum*) with concentration factors (dry weight) ranging from 15,000 to 40,000 and 2,300 to 18,000, respectively. Elimination experiments with the algae indicate a two component biological half-life, 1 hour and 11 days, respectively, and suggest that the cobalt might be absorbed not only on the surface, but also intracellularly. Since these organisms are at the bottom of the food chain, they could play an important role in the trophic transfer of ^{60}Co released into waterways by nuclear facilities. However, cobalt levels generally diminish with increasing trophic levels in a food chain. The low levels of cobalt in fish may also reflect cobalt's strong binding to particles and sediment. The bioaccumulation factors (dry weight basis) for cobalt in marine and freshwater fish are ~100-4,000 and <10-1,000, respectively; accumulation in the muscle of marine fish is 5- 500.

Cobalt largely accumulates in the viscera and on the skin, as opposed to the edible parts of the fish. In carp, accumulation from water accounted for 75% of ^{60}Co accumulated from both water and food; accumulation from water and food was additive. Depuration half-lives were 53 and 87 days for fish contaminated from food and water, respectively. In the case of an accidental release of ^{60}Co into waterways, the implication is that effects would manifest themselves rapidly since the primary route of exposure is from water rather than food. Uptake of ^{60}Co was very low in whitefish, with concentrations being highest in kidney and undetectable in muscle. Similarly, while accumulation of ^{60}Co by carp from food was dependent on food type, the transfer factor was very low, approximately 0.01, and no long-term bioaccumulation of the radionuclide occurred.

Concentration factors have also been reported for various other aquatic organisms. Freshwater mollusks have concentration factors of 100-14,000 (~1-300 in soft tissue). Much of the cobalt taken up by mollusks and crustacea from water or sediment is adsorbed to the shell or exoskeleton; very little cobalt is generally accumulated in the edible parts. A concentration factor for ^{60}Co of 265 mL/g (wet weight) was determined for *Daphnia magna* in laboratory studies. The rapid decrease in radioactivity during the depuration phase indicated that adsorption to the surface was the major contamination process. However, the digestive glands of crustaceans, which are sometimes eaten by humans, may accumulate high levels of ^{60}Co . The shell accounted for more than half of the body burden. Among the soft tissue, the gills and viscera had the highest concentrations factors and the muscle had the lowest.

In mussels, higher absorption efficiencies and lower efflux rates were obtained for cobalamins than for inorganic cobalt, suggesting that it is a more bioavailable form of cobalt.

Vitamin B12, which contains cobalt, is synthesized by 58 species of seven genera of bacteria as well as blue-green algae and actinomycetes (mold-like bacteria). Consequently, vitamin B12 levels in marine water range from very low levels in some open ocean water to much higher levels in some coastal waters. Freshwater environments have comparable levels of vitamin B12. The high level of cobalamins in coastal water appears to be related to the occurrence of macrophytes in these areas with their high concentrations of vitamin B12. Cobalamins are released into the water when the organisms die.

Some female birds sequester metals into their eggs under certain conditions, a phenomenon that may jeopardize the developing embryos.

■ DO NOT discharge into sewer or waterways.

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
chloro(pyridine)bis(dimethylglyoximate)cobalt(III)	HIGH		LOW	LOW

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Instructions

All waste must be handled in accordance with local, state and federal regulations.

‡ Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- Reuse
- Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

DO NOT allow wash water from cleaning equipment to enter drains. Collect all wash water for treatment before disposal.

- Recycle wherever possible.
- Consult manufacturer for recycling options or consult Waste Management Authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: Burial in a licensed land-fill or Incineration in a licensed apparatus (after admixture with suitable combustible material)
- Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

Section 14 - TRANSPORTATION INFORMATION

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: DOT, IATA, IMDG

Section 15 - REGULATORY INFORMATION

chloro(pyridine)bis(dimethylglyoximate)cobalt(III) (CAS: 23295-32-1) is found on the following regulatory lists;

"Canada - Saskatchewan Occupational Health and Safety Regulations - Designated Chemical Substances","Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances","International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs","US - California Air Toxics ""Hot Spots"" List (Assembly Bill 2588) Substances for which emissions must be quantified","US - California Environmental Health Standards for the Management of Hazardous Waste - List of Inorganic Persistent and Bioaccumulative Toxic Substances and Their STLC & TTLC Values","US - California Toxic Air Contaminant List Category II","US - Washington Permissible exposure limits of air contaminants","US Clean Air Act - Hazardous Air Pollutants","US List of Lists - Consolidated List of Chemicals Subject to the Emergency Planning and Community Right-to-Know Act (EPCRA) and Section 112(r) of the Clean Air Act","US RCRA (Resource Conservation & Recovery Act) - Appendix IX to Part 264 Ground-Water Monitoring List 1","US RCRA (Resource Conservation & Recovery Act) - List of Hazardous Inorganic and Organic Constituents 1"

Section 16 - OTHER INFORMATION

LIMITED EVIDENCE

- Inhalation and/or ingestion may produce health damage*.
- Cumulative effects may result following exposure*.

* (limited evidence).

Reasonable care has been taken in the preparation of this information, but the author makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The author makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. For additional technical information please call our toxicology department on +800 CHEMCALL.

- Classification of the mixture and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:
www.chemwatch.net/references.

- The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: Jan-21-2010

Print Date:Apr-21-2010