

# Produktinformation



Forschungsprodukte & Biochemikalien



Zellkultur & Verbrauchsmaterial



Diagnostik & molekulare Diagnostik



Laborgeräte & Service

Weitere Information auf den folgenden Seiten! See the following pages for more information!



# Lieferung & Zahlungsart

siehe unsere Liefer- und Versandbedingungen

# Zuschläge

- Mindermengenzuschlag
- Trockeneiszuschlag
- Gefahrgutzuschlag
- Expressversand

# SZABO-SCANDIC HandelsgmbH

Quellenstraße 110, A-1100 Wien

T. +43(0)1 489 3961-0

F. +43(0)1 489 3961-7

mail@szabo-scandic.com

www.szabo-scandic.com

linkedin.com/company/szaboscandic in



# **Ammonium thiosulfate**

# sc-239243

**Material Safety Data Sheet** 



The Power to Oscotion

Hazard Alert Code Key:

**EXTREME** 

HIGH

MODERATE

LOW

# Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

## **PRODUCT NAME**

Ammonium thiosulfate

## STATEMENT OF HAZARDOUS NATURE

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

## **NFPA**



## **SUPPLIER**

Santa Cruz Biotechnology, Inc. 2145 Delaware Avenue Santa Cruz, California 95060 800.457.3801 or 831.457.3800

# EMERGENCY

ChemWatch

Within the US & Canada: 877-715-9305 Outside the US & Canada: +800 2436 2255 (1-800-CHEMCALL) or call +613 9573 3112

### SYNONYMS

H8-N2-O3-S2, "ammonium hyposulphite", "ammonium hyposulfite", "ammonium thiosulfate", "diammonium thiosulphate", "thiosulphuric acid, diammonium salt", "thiosulphuric acid, diammonium salt", "ammonium hypo"

# **Section 2 - HAZARDS IDENTIFICATION**

### **CHEMWATCH HAZARD RATINGS**

		Min	Max
Flammability:	0		
Toxicity:	2		
Body Contact:	2		Min/Nil=0 Low=1
Reactivity:	0		Moderate=2
Chronic:	2		High=3 Extreme=4

# **CANADIAN WHMIS SYMBOLS**



### **EMERGENCY OVERVIEW**

#### **RISK**

Harmful by inhalation.

Danger of cumulative effects.

Irritating to eyes, respiratory system and skin.

### **POTENTIAL HEALTH EFFECTS**

### **ACUTE HEALTH EFFECTS**

#### **SWALLOWED**

- Accidental ingestion of the material may be damaging to the health of the individual.
- Thiosulfate salts are poorly absorbed and stimulate the emptying of thebowel.
- Large doses of ammonia or injected ammonium salts may produce diarrhea and may be sufficiently absorbed to produce increased production of urine and systemic poisoning.

Symptoms include weakening of facial muscle, tremor, anxiety, reduced muscle and limb control.

#### **EYE**

■ This material can cause eye irritation and damage in some persons.

#### SKIN

- This material can cause inflammation of the skin oncontact in some persons.
- The material may accentuate any pre-existing dermatitis condition.
- Open cuts, abraded or irritated skin should not be exposed to this material.
- Solution of material in moisture on the skin, or perspiration, mayincrease irritant effects.
- Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects.

Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

#### **INHALED**

- Inhalation of dusts, generated by the material, during the course of normalhandling, may be harmful.
- The material can cause respiratory irritation in some persons.

The body's response to such irritation can cause further lung damage.

■ Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.

#### **CHRONIC HEALTH EFFECTS**

■ Repeated or long-term occupational exposure is likely to produce cumulative health effects involving organs or biochemical systems. Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems. Long term exposure to high dust concentrations may cause changes in lung function i.e. pneumoconiosis; caused by particles less than 0.5 micron penetrating and remaining in the lung.

### Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
diammonium thiosulfate	7783-18-8	> 97

### **Section 4 - FIRST AID MEASURES**

# **SWALLOWED**

· If swallowed do NOT induce vomiting. · If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.

### EYE

■ If this product comes in contact with the eyes: · Wash out immediately with fresh running water. · Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.

### SKIN

■ If skin contact occurs: · Immediately remove all contaminated clothing, including footwear · Flush skin and hair with running water (and soap if available).

# INHALED

· If fumes or combustion products are inhaled remove from contaminated area. · Lay patient down. Keep warm and rested.

# **NOTES TO PHYSICIAN**

■ Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES			
Vapor Pressure (mmHg):	129.986 @ 26.7 C		
Upper Explosive Limit (%):	Not applicable		
Specific Gravity (water=1):	1.679		
Lower Explosive Limit (%):	Not applicable		

### **EXTINGUISHING MEDIA**

· There is no restriction on the type of extinguisher which may be used.

Use extinguishing media suitable for surrounding area.

#### **FIRE FIGHTING**

- · Alert Emergency Responders and tell them location and nature of hazard.
- · Wear breathing apparatus plus protective gloves for fire only.

## GENERAL FIRE HAZARDS/HAZARDOUS COMBUSTIBLE PRODUCTS

· Non combustible.

· Not considered to be a significant fire risk, however containers may burn.

Decomposition may produce toxic fumes of: nitrogen oxides (NOx), sulfur oxides (SOx).

May emit poisonous fumes.

May emit corrosive fumes.

#### FIRE INCOMPATIBILITY

■ None known.

# **PERSONAL PROTECTION**

Glasses:

Chemical goggles.

Gloves:

Respirator:

Particulate

## **Section 6 - ACCIDENTAL RELEASE MEASURES**

# MINOR SPILLS

- · Remove all ignition sources.
- · Clean up all spills immediately.
- · Avoid contact with skin and eyes.
- · Control personal contact by using protective equipment.
- · Use dry clean up procedures and avoid generating dust.
- · Place in a suitable, labelled container for waste disposal.

### **MAJOR SPILLS**

- Moderate hazard.
- · CAUTION: Advise personnel in area.
- · Alert Emergency Responders and tell them location and nature of hazard.

# Section 7 - HANDLING AND STORAGE

### PROCEDURE FOR HANDLING

- · Avoid all personal contact, including inhalation.
- · Wear protective clothing when risk of exposure occurs.

# RECOMMENDED STORAGE METHODS

- Glass container.
- · Polyethylene or polypropylene container.
- · Check all containers are clearly labelled and free from leaks.

## STORAGE REQUIREMENTS

 $\blacksquare$  Observe manufacturer's storing and handling recommendations.

# Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

# **EXPOSURE CONTROLS**

Source	Material	TWA ppm	TWA mg/m³	STEL ppm	STEL mg/m³	Peak ppm	Peak mg/m³	TWA F/CC	Notes
Canada - Ontario Occupational Exposure Limits	diammonium thiosulfate (Particles (Insoluble or Poorly Soluble) Not Otherwise)		10 (I)						
Canada - British Columbia Occupational Exposure Limits	diammonium thiosulfate (Particles (Insoluble or Poorly Soluble) Not Otherwise Classified		10 (N)						

(PNOC)) diammonium thiosulfate (Specified (PNOS)/ Canada - Ontario Occupational Particules 3 (R) **Exposure Limits** (insolubles ou peu solubles) non précisées par ailleurs) diammonium US - Tennessee thiosulfate Occupational (Particulates not Exposure Limits otherwise 5 Limits For Air regulated Contaminants Respirable fraction) diammonium US - California thiosulfate Permissible (Particulates not **Exposure Limits** otherwise 5 (n) for Chemical regulated Contaminants Respirable fraction) **Bold print** identifies substances for which the diammonium Oregon Permissible thiosulfate US - Oregon (Particulates not Exposure Permissible otherwise 10 Limits (PELs) **Exposure Limits** are different regulated (Z-1)(PNOR) (f) Total than the federal Limits. Dust) PNOR means "particles not otherwise regulated." diammonium US - Michigan thiosulfate **Exposure Limits** (Particulates not 5 for Air otherwise Contaminants regulated, Respirable dust) Bold print identifies substances for which the diammonium Oregon thiosulfate Permissible US - Oregon (Particulates not Exposure Permissible otherwise 5 Limits (PELs) **Exposure Limits** regulated are different (PNOR) (f) (Z-1)than the Respirable federal Limits. Fraction) PNOR means "particles not otherwise regulated." diammonium US - Wyoming thiosulfate Toxic and (Particulates not Hazardous otherwise Substances 5 regulated Table Z1 Limits (PNOR)(f)for Air Respirable Contaminants fraction)

Canada - Prince Edward Island Occupational Exposure Limits diammonium
thiosulfate
(Particles
(Insoluble or 10
Poorly Soluble)
[NOS] Inhalable

See Appendix B current TLV/BEI Book

### **ENDOELTABLE**

### PERSONAL PROTECTION

particles)









### **RESPIRATOR**

· particulate.

Consult your EHS staff for recommendations

#### EYE

- · Safety glasses with side shields.
- · Chemical goggles.

### HANDS/FEET

- Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: such as:
- · frequency and duration of contact,
- · chemical resistance of glove material,
- · glove thickness and
- · dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739).

- · When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended.
- · When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended.
- · Contaminated gloves should be replaced.

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Experience indicates that the following polymers are suitable as glove materials for protection against undissolved, dry solids, where abrasive particles are not present.

- · polychloroprene
- $\cdot \ \text{nitrile rubber}$
- · butyl rubber
- · fluorocaoutchouc
- · polyvinyl chloride

Gloves should be examined for wear and/ or degradation constantly.

# **OTHER**

- · Overalls.
- · P.V.C. apron.
- · Barrier cream.
- · Skin cleansing cream.
- · Eye wash unit.

# **ENGINEERING CONTROLS**

■ Local exhaust ventilation usually required. If risk of overexposure exists, wear an approved respirator.

## **Section 9 - PHYSICAL AND CHEMICAL PROPERTIES**

### **PHYSICAL PROPERTIES**

Solid.

Mixes with water.

State	Divided solid	Molecular Weight	148.21
Melting Range (°F)	302 (Decomposes)	Viscosity	Not Applicable
Boiling Range (°F)	Not available.	Solubility in water (g/L)	Miscible
Flash Point (°F)	Not Applicable	pH (1% solution)	Not available.
Decomposition Temp (°F)	302	pH (as supplied)	Not applicable
Autoignition Temp (°F)	Not available.	Vapor Pressure (mmHg)	129.986 @ 26.7 C

Upper Explosive Limit (%)	Not applicable	Specific Gravity (water=1)	1.679
Lower Explosive Limit (%)	Not applicable	Relative Vapor Density (air=1)	0.597 (of ammonia)
Volatile Component (%vol)	53	Evaporation Rate	Not applicable

### **APPEARANCE**

White crystals or colourless crystals with ammoniacal odour. Very soluble in water. Insoluble in alcohol, ether.

### Section 10 - CHEMICAL STABILITY

## **CONDITIONS CONTRIBUTING TO INSTABILITY**

- · Presence of incompatible materials.
- · Product is considered stable.

#### STORAGE INCOMPATIBILITY

- For inorganic thiosulfates
- · Avoid storage with acids, metal nitrites, sodium nitrite, halogens and oxidizing agents.
- · Forms explosive product with potassium nitrate, sodium nitrate
- · Reacts with acids, forming sulfur dioxide
- · Incompatible with halogens, lead, silver and mercury salts. iodine.

For incompatible materials - refer to Section 7 - Handling and Storage.

### Section 11 - TOXICOLOGICAL INFORMATION

diammonium thiosulfate

#### **TOXICITY AND IRRITATION**

DIAMMONIUM THIOSULFATE:

■ unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY IRRITATION

Oral (Rat) LD50: 2890 mg/kg Nil Reported

Inhalation (Rat) LC: >2260 mg/m³/4h

Oral (Mouse) LD50: 2100 mg/kg

Inhalation (Mouse) LC: >1800 mg/m³/4h

Oral (Guinea pig) LD50: 1098 mg/kg

■ Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.

# **Section 12 - ECOLOGICAL INFORMATION**

No data

**Ecotoxicity** 

Ingredient Persistence: Water/Soil Persistence: Air Bioaccumulation Mobility

diammonium thiosulfate No Data Available No Data Available LOW

### **GESAMP/EHS COMPOSITE LIST - GESAMP Hazard Profiles**

Ammonium 312 124 Ino 0 Ino 1 NI 0 (0) (1) (1) D 1 thiosulph rg rg ate solution (60% or less) /

CAS:7783- 18- 8 /

Legend: EHS=EHS Number (EHS=GESAMP Working Group on the Evaluation of the Hazards of Harmful Substances Carried by Ships) NRT=Net Register Tonnage, A1a=Bioaccumulation log Pow, A1b=Bioaccumulation BCF, A1=Bioaccumulation, A2=Biodegradation, B1=Acuteaquatic toxicity LC/ECIC50 (mg/l), B2=Chronic aquatic toxicity NOEC (mg/l), C1=Acute mammalian oral toxicity LD50 (mg/kg), C2=Acutemammalian dermal toxicity LD50 (mg/kg), C3=Acute mammalian inhalation toxicity LC50 (mg/kg), D1=Skin irritation & corrosion, D2=Eye irritation& corrosion, D3=Long-term health effects, E1=Tainting, E2=Physical effects on wildlife & benthic habitats, E3=Interference with coastal amenities, For column A2: R=Readily biodegradable, NR=Not readily biodegradable. For column D3: C=Carcinogen, M=Mutagenic, R=Reprotoxic, S=Sensitising, A=Aspiration hazard, T=Target organ systemic toxicity, L=Lunginjury, N=Neurotoxic, I=Immunotoxic. For column E1: NT=Not tainting (tested), T=Tainting test positive. For column E2: Fp=Persistent floater, F=Floater, S=Sinking substances. The numerical scales start from 0 (no hazard), while higher numbers reflect increasing hazard. (GESAMP/EHS Composite List of Hazard Profiles - Hazard evaluation of substances transported by ships)

### Section 13 - DISPOSAL CONSIDERATIONS

# **Disposal Instructions**

All waste must be handled in accordance with local, state and federal regulations.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- · Reduction
- · Reuse
- · Recycling
- · Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

DO NOT allow wash water from cleaning equipment to enter drains. Collect all wash water for treatment before disposal.

- · Recycle wherever possible or consult manufacturer for recycling options.
- · Consult Waste Management Authority for disposal.

## **Section 14 - TRANSPORTATION INFORMATION**

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: DOT, IATA, IMDG

## **Section 15 - REGULATORY INFORMATION**

# diammonium thiosulfate (CAS: 7783-18-8) is found on the following regulatory lists;

"Canada Domestic Substances List (DSL)", "Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS (English)", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "International Council of Chemical Associations (ICCA) - High Production Volume List", "OECD Representative List of High Production Volume (HPV) Chemicals", "US - Massachusetts Oil & Hazardous Material List", "US - Pennsylvania - Hazardous Substance List", "US DOE Temporary Emergency Exposure Limits (TEELs)", "US EPA High Production Volume Chemicals Additional List", "US FDA Indirect Food Additives: Adhesives and Components of Coatings - Substances for Use Only as Components of Adhesives - Adhesives", "US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory"

## **Section 16 - OTHER INFORMATION**

### LIMITED EVIDENCE

- Ingestion may produce health damage\*.
- \* (limited evidence).

Reasonable care has been taken in the preparation of this information, but the author makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The author makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. For additional technical information please call our toxicology department on +800 CHEMCALL.

- Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

  A list of reference resources used to assist the committee may be found at:

  www.chemwatch.net/references
- The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: Feb-12-2011 Print Date:Jun-9-2011