

Produktinformation



Forschungsprodukte & Biochemikalien
Zellkultur & Verbrauchsmaterial
Diagnostik & molekulare Diagnostik
Laborgeräte & Service

Weitere Information auf den folgenden Seiten! See the following pages for more information!



Lieferung & Zahlungsart siehe unsere Liefer- und Versandbedingungen


Zuschläge

- Mindermengenzuschlag
- Trockeneiszuschlag
- Gefahrgutzuschlag
- Expressversand

SZABO-SCANDIC HandelsgmbH


Quellenstraße 110, A-1100 Wien T. +43(0)1 489 3961-0 F. +43(0)1 489 3961-7 <u>mail@szabo-scandic.com</u> www.szabo-scandic.com

Bis(dibenzylideneacetone)palladium(0)



SYNONYMS

C34-H28-O2-Pd, (C6H5CH=CHCOCH=CHC6H5)2Pd, "palladium(0) bis(dibenzylideneacetone)", "palladium, bis[(1, 2, 4, 5-eth)-1, 5-diphenyl-1, 4-pentadien-3-one)palladium", bis(benzylideneacetone)palladium, "palladium catalyst"





EMERGENCY OVERVIEW RISK

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Although ingestion is not thought to produce harmful effects, the material may still be damaging to the health of the individual following ingestion, especially where pre-existing organ (e.g. liver, kidney) damage is evident.

Considered an unlikely route of entry in commercial/industrial environments.

EYE

Although the material is not thought to be an irritant, direct contact with the eye may produce transient discomfort characterized by tearing or conjunctival redness (as with windburn).

SKIN

■ The material is not thought to produce adverse health effects or skin irritation following contact (as classified using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.

INHALED

■ The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.

Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.

CHRONIC HEALTH EFFECTS

Principal routes of exposure are usually by skin contact/absorption and inhalation of generated dust.

Colloidal palladium is reported to increase body temperature, producediscoloration and tissue death at the site of injection, decreasebodyweight and cause some destruction of blood cells.

There is a weak association between palladium chloride and tumor productionon the basis of a single study.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

| NAME | CAS RN | % |
|---------------------------------------|------------|-----|
| bis(dibenzylideneacetone)palladium(0) | 32005-36-0 | >98 |

Section 4 - FIRST AID MEASURES

SWALLOWED

· Immediately give a glass of water. · First aid is not generally required. If in doubt, contact a Poisons Information Center or a doctor. **EYE**

■ If this product comes in contact with the eyes: · Wash out immediately with fresh running water. · Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.

SKIN

■ If skin contact occurs: · Immediately remove all contaminated clothing, including footwear · Flush skin and hair with running water (and soap if available).

INHALED

· If dust is inhaled, remove from contaminated area. · Encourage patient to blow nose to ensure clear passage of breathing. · If irritation or discomfort persists seek medical attention.

NOTES TO PHYSICIAN

■ Treat symptomatically.

| Section 5 - FIRE FIGHTING MEASURES | | | |
|------------------------------------|----------------|--|--|
| Upper Explosive Limit (%): | Not available. | | |
| Specific Gravity (water=1): | Not available | | |
| Lower Explosive Limit (%): | Not available | | |
| Relative Vapor Density (air=1): | >1 | | |

EXTINGUISHING MEDIA

· Foam.

· Dry chemical powder.

FIRE FIGHTING

 \cdot Use water delivered as a fine spray to control fire and cool adjacent area.

· DO NOT approach containers suspected to be hot.

GENERAL FIRE HAZARDS/HAZARDOUS COMBUSTIBLE PRODUCTS

· Solid which exhibits difficult combustion or is difficult to ignite.

• Avoid generating dust, particularly clouds of dust in a confined or unventilated space as dusts may form an explosive mixture with air, and any source of ignition, i.e. flame or spark, will cause fire or explosion. Dust clouds generated by the fine grinding of the solid are a particular hazard; accumulations of fine dust may burn rapidly and fiercely if ignited.

Combustion products include: carbon monoxide (CO).

FIRE INCOMPATIBILITY

Avoid contamination with strong oxidizing agents as ignition may result.

PERSONAL PROTECTION

Glasses: Safety Glasses. Gloves: Respirator: Particulate

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- · Clean up all spills immediately.
- · Avoid contact with skin and eyes.

MAJOR SPILLS

- · Clear area of personnel and move upwind.
- · Alert Emergency Responders and tell them location and nature of hazard.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- · Limit all unnecessary personal contact.
- \cdot Wear protective clothing when risk of exposure occurs.
- · Use in a well-ventilated area.
- \cdot When handling DO NOT eat, drink or smoke.
- · Always wash hands with soap and water after handling.
- · Avoid physical damage to containers.
- · Use good occupational work practice.
- · Observe manufacturer's storing and handling recommendations.

RECOMMENDED STORAGE METHODS

· Polyethylene or polypropylene container.

· Packing as recommended by manufacturer.

STORAGE REQUIREMENTS

· Keep dry.

- · Store in original containers.
- · Keep containers securely sealed.
- · No smoking, naked lights or ignition sources.
- · Store in a cool, dry, well-ventilated area.
- · Store away from incompatible materials.
- · Protect containers against physical damage.
- · Check regularly for leaks.
- · Observe manufacturer's storing and handling recommendations.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

| Source | Material | TWA ppm | TWA mg/m³ | STEL ppm | STEL mg/m³ | Peak ppm | Peak mg/m³ | TWA F/CC | Notes |
|--|---|------------|--------------|-------------|---------------|-------------|---------------|-------------|---|
| US - Oregon Permissible Exposure Limits (Z-3) | bis(dibenzylideneacetone)palladium(0) (Inert or Nuisance Dust: (d) Total dust) | | 10 | | | | | | Oregon Permissible Exposure Limits (PELs) are |

| | | | different than the federal limits. |
|---|---|--------|--|
| US OSHA Permissible Exposure Levels (PELs) - Table Z3 | bis(dibenzylideneacetone)palladium(0) (Inert or Nuisance Dust: (d) Respirable fraction) | 5 | |
| US OSHA Permissible Exposure Levels (PELs) - Table Z3 | bis(dibenzylideneacetone)palladium(0) (Inert or Nuisance Dust: (d) Total dust) | 15 | |
| US - Hawaii Air Contaminant Limits | bis(dibenzylideneacetone)palladium(0) (Particulates not other wise regulated - Total dust) | 10 | |
| US - Hawaii Air Contaminant Limits | bis(dibenzylideneacetone)palladium(0) (Particulates not other wise regulated - Respirable fraction) | 5 | |
| US - Oregon Permissible Exposure Limits (Z-3) | bis(dibenzylideneacetone)palladium(0) (Inert or Nuisance Dust:(d) Respirable fraction) | 5 | Oregon Permissible Exposure Limits (PELs) are different than the federal limits. |
| Canada - British Columbia Occupational Exposure Limits | bis(dibenzylideneacetone)palladium(0) (Particles (Insoluble or Poorly Soluble) Not Otherwise Classified (PNOC)) | 10 (N) | |
| US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants | bis(dibenzylideneacetone)palladium(0) (Particulates not otherwise regulated (PNOR)(f)- Respirable fraction) | 5 | |
| US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants | bis(dibenzylideneacetone)palladium(0) (Particulates not otherwise regulated Respirable fraction) | 5 | |
| US - California Permissible Exposure Limits for Chemical Contaminants | bis(dibenzylideneacetone)palladium(0) (Particulates not otherwise regulated Respirable fraction) | 5 | (n) |
| US - Oregon Permissible Exposure Limits (Z-1) | bis(dibenzylideneacetone)palladium(0) (Particulates not otherwise regulated (PNOR) (f) Total Dust) | 10 | Bold print identifies substances for which the Oregon Permissible Exposure Limits |

| | | | (PELs) are different than the federal Limits. PNOR means "particles not otherwise regulated." |
|------------------------|---|----|---|
| | deneacetone)palladium(0) not otherwise regulated, lust) | 5 | |
| Island (Particles (In | deneacetone)palladium(0) soluble or Poorly Soluble) able particles) | 10 | See Appendix B current TLV/BEI Book |
| Exposure (Particulates | deneacetone)palladium(0) not otherwise regulated - Respirable Fraction) | 5 | Bold print identifies substances for which the Oregon Permissible Exposure Limits (PELs) are different than the federal Limits. PNOR means "particles not otherwise regulated." |
| ENDUELIABLE | | | |



RESPIRATOR

Particulate Consult your EHS staff for recommendations

EYE

· Safety glasses.

· Safety glasses with side shields.

HANDS/FEET

■ Wear general protective gloves, e.g.. light weight rubber gloves.

OTHER

Overalls.

- \cdot Impervious protective clothing.
- · Eyewash unit.

ENGINEERING CONTROLS

General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear an approved respirator.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL PROPERTIES

| Solid. Does not mix with water. | | | |
|------------------------------------|----------------|---------------------------|----------------|
| State | Divided solid | Molecular Weight | 575.00 |
| Melting Range (°F) | 302 | Boiling Range (°F) | Not available |
| Solubility in water (g/L) | Immiscible | Flash Point (°F) | Not available |
| pH (1% solution) | Not applicable | Decomposition Temp (°F) | Not available. |
| pH (as supplied) | Not applicable | Autoignition Temp (°F) | Not available |
| Vapour Pressure (mmHG) | Negligible | Upper Explosive Limit (%) | Not available. |
| Specific Gravity (water=1) | Not available | Lower Explosive Limit (%) | Not available |
| Relative Vapor Density (air=1) | >1 | Volatile Component (%vol) | Negligible |
| Evaporation Rate | Not applicable | | |

APPEARANCE

Brown powder; does not mix well with water.

Section 10 - CHEMICAL STABILITY

CONDITIONS CONTRIBUTING TO INSTABILITY

 \cdot Presence of incompatible materials.

· Product is considered stable.

STORAGE INCOMPATIBILITY

Avoid reaction with oxidizing agents.

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

bis(dibenzylideneacetone)palladium(0)

TOXICITY AND IRRITATION

BIS(DIBENZYLIDENEACETONE)PALLADIUM(0):

■ No significant acute toxicological data identified in literature search.

Section 12 - ECOLOGICAL INFORMATION

No data

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Instructions

All waste must be handled in accordance with local, state and federal regulations.

 \cdot Consult manufacturer for recycling options and recycle where possible .

· Consult Waste Management Authority for disposal.

Section 14 - TRANSPORTATION INFORMATION

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: DOT, IATA, IMDG

Section 15 - REGULATORY INFORMATION

bis(dibenzylideneacetone)palladium(0) (CAS: 32005-36-0) is found on the following regulatory lists;

"US - Hawaii Air Contaminant Limits", "US - Oregon Permissible Exposure Limits (Z-3)", "US OSHA Permissible Exposure Levels (PELs) - Table Z3"

Section 16 - OTHER INFORMATION

Reasonable care has been taken in the preparation of this information, but the author makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The author makes no

representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. For additional technical information please call our toxicology department on +800 CHEMCALL.

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references. A list of reference resources used to assist the committee may be found at: www.chemwatch.net/references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: Feb-19-2008 Print Date:Mar-10-2011