

Printing date 01/25/2022


Revision date 01/25/2022

Page 1/10

1 Identification

- · Product identifier
- Trade name: <u>(±)12-HpETE</u>
- · Article number: 10138
- **Application of the substance / the mixture** This product is for research use - Not for human or veterinary diagnostic or therapeutic use.
- · Details of the supplier of the safety data sheet
- **Manufacturer/Supplier:** Cayman Chemical Co. 1180 E. Ellsworth Rd. Ann Arbor, MI 48108 USA
- Information department: Product safety department
 Emergency telephone number: During normal opening times: +1 (734) 971-3335 US/CANADA: 800-424-9300 Outside US/CANADA: 703-741-5970

2 Hazard(s) identification



US

US

Safety Data Sheet acc. to OSHA HCS

Printing date 01/25/2022

Revision date 01/25/2022

Trade name: (±)12-HpETE

	(Contd. from page 1)
· Signal word Da	anger
· Hazard-determ	nining components of labeling:
ethanol	
 Hazard statem 	ents
H225 Highly fla	mmable liquid and vapor.
H350 May caus	
 Precautionary 	statements
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
	353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P370+P378	In case of fire: Use CO2, powder or water spray to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
· Classification	system:
· NFPA ratings ((scale 0 - 4)
Н	ealth = 0
	re = 3

Fire = 3 Reactivity = 0

· HMIS-ratings (scale 0 - 4)

HEALTH *0	Health = *0
	Fire = 3
REACTIVITY 0	Reactivity = 0

· Other hazards

0

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 64-17-5 RTECS: KQ6300000	ethanol	99.99%
	(Contd.	. on page 3)

Printing date 01/25/2022

Revision date 01/25/2022

Trade name: (±)12-HpETE

0.01%

(Contd. from page 2)

· Other ingredients

71030-35-8 (+/-)12-HpETE

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- **Most important symptoms and effects, both acute and delayed** May cause anemia, cough, CNS depression, drowsiness, headache, heart damage, lassitude (weakness, exhaustion), liver damage, narcosis, reproductive effects, teratogenic effects.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Environmental precautions: Dilute with plenty of water. 	
Do not allow to enter sewers/ surface or ground water.	
• Methods and material for containment and cleaning up:	
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, saw	dust).
Dispose contaminated material as waste according to item 13.	
Ensure adequate ventilation.	
Reference to other sections	
See Section 7 for information on safe handling.	
See Section 8 for information on personal protection equipment.	
See Section 13 for disposal information.	
Protective Action Criteria for Chemicals	
· PAC-1:	
64-17-5 ethanol	1,800 ppm
· PAC-2:	
64-17-5 ethanol	3300* ppm
	(Contd. on page 4)

Printing date 01/25/2022

64-17-5 ethanol

Revision date 01/25/2022

Trade name: (±)12-HpETE

(Contd. from page 3)

15000* ppm

7 Handling and storage

· Handling:

· PAC-3:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Keep receptacle tightly sealed. Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

• Components with limit values that require monitoring at the workplace:

64-17-5 ethanol

- PEL Long-term value: 1900 mg/m³, 1000 ppm
- REL Long-term value: 1900 mg/m³, 1000 ppm
- TLV Short-term value: 1000 ppm
 - A3

• Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work.

Store protective clothing separately.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

Printing date 01/25/2022

Revision date 01/25/2022

Trade name: (±)12-HpETE

(Contd. from page 4)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

Information on basic physical and o	chemical properties
General Information	
Appearance:	
Form:	Fluid
Color:	Colorless
Odor:	Alcohol-like
Structural Formula	C20H32O4
Molecular Weight	336.5 g/mol
Odor threshold:	Not determined.
Formulation	A solution in ethanol
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	-114.5 °C (-174.1 °F)
Boiling point/Boiling range:	78 °C (172.4 °F)
Flash point:	13 °C (55.4 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	425 °C (797 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air vapor mixtures are possible.
Explosion limits:	
Lower:	3.5 Vol %
Upper:	15 Vol %
Vapor pressure at 20 °C (68 °F):	59 hPa (44.3 mm Hg)

Printing date 01/25/2022

Revision date 01/25/2022

Trade name: (±)12-HpETE

	(Contd. from page 5
[·] Density at 20 °C (68 °F): [·] Relative density [·] Vapor density [·] Evaporation rate	0.79 g/cm³ (6.59255 lbs/gal) Not determined. Not determined. Not determined.
· Solubility in / Miscibility with Water at 20 °C (68 °F):	1,000 g/l
· Partition coefficient (n-octanol/wa	ater): Not determined.
[·] Viscosity: Dynamic at 20 °C (68 °F): Kinematic: SOLUBILITY	1.2 mPas Not determined. 0.1 M Na2CO3: 2 mg/ml; PBS (pH 7.2): .5 mg/ml; DMF DMSO;Ethanol
 Solvent content: Organic solvents: VOC content: 	100.0 % 99.99 % 999.9 g/l / 8.34 lb/gal
Solids content:	0.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

· Reactivity No further relevant information available.

· Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: strong oxidizing agents
- Hazardous decomposition products: carbon dioxide, carbon monoxide

11 Toxicological information · Information on toxicological effects • Acute toxicity: · LD/LC50 values that are relevant for classification: 64-17-5 ethanol Oral 1.14 ml/kg (man) TDLO LD50 7,060 mg/kg (rat) TDLO 650 (man) 40,000 mg/kg (rat) Dermal LD50 Inhalative LC50/4 h 5,900 mg/m³ (rat) 20,000 mg/m3/10h (rat) LC50 TCLO 1,800 mg/m³/30m (hmn) LCLO 29,300 mg/m³/7h (mouse) (Contd. on page 7) 115

Printing date 01/25/2022

Revision date 01/25/2022

Trade name: (±)12-HpETE

		(Contd. from page 6
	TCLO	1,800 (hmn)
	LC50	10 h - 20,000 mg/m³ (rat)
	LD50 Inhalation TCLO	1,800 mg/m³/30m (hmn)
	LC50/4 h	20,000 mg/l (rat)
Irritation of skin	Irritation	20 mg/24h (rabbit)
	TDLO	1,800 mg/kg (wmn)
Irritation of eyes	Irritation	500 mg/24h (rabbit)
	Intraperitoneal LD50	280 mg/kg (rat)
	Data	500 mg/24h (rabbit)
• on the eye: No in • Sensitization: N		own.
 Sensitization: N Additional toxic 	lo sensitizing effects kno cological information:	own. ers according to internally approved calculation methods fo
 Sensitization: N Additional toxic The product shot 	lo sensitizing effects kno cological information: bws the following dang	
 Sensitization: N Additional toxic The product sho preparations: Carcinogenic ca IARC (Internation) 	lo sensitizing effects kno cological information: ows the following dang ategories onal Agency for Resea	ers according to internally approved calculation methods for
 Sensitization: N Additional toxic The product sho preparations: Carcinogenic ca 	lo sensitizing effects kno cological information: ows the following dang ategories onal Agency for Resea	ers according to internally approved calculation methods for
 Sensitization: N Additional toxic The product sho preparations: Carcinogenic ca IARC (Internation 64-17-5 ethanol 	lo sensitizing effects kno cological information: ows the following dang ategories onal Agency for Resea	ers according to internally approved calculation methods for
 Sensitization: N Additional toxic The product sho preparations: Carcinogenic ca IARC (Internation 64-17-5 ethanol 	lo sensitizing effects kno cological information: ows the following dang ategories onal Agency for Resea	ers according to internally approved calculation methods for

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- **vPvB:** Not applicable.
- Other adverse effects No further relevant information available.

(Contd. on page 8)

Printing date 01/25/2022

Revision date 01/25/2022

Trade name: (±)12-HpETE

(Contd. from page 7)

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.
- Recommended cleansing agent: Water, if necessary with cleansing agents.

· UN-Number · DOT, IMDG, IATA	UN1170
UN proper shipping name DOT IMDG IATA	Ethanol solutions ETHANOL SOLUTION (ETHYL ALCOH) SOLUTION) Ethanol solution
Transport hazard class(es)	
DOT	
Class	3 Flammable liquids
Label	3
Class	3 Flammable liquids
Label	3
Packing group DOT, IMDG, IATA	II
Environmental hazards:	Not applicable.
Special precautions for user Hazard identification number (Kemler code	
EMS Number: Stowage Category	F-E,S-D A
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.

Printing date 01/25/2022

Revision date 01/25/2022

Trade name: (±)12-HpETE

(Contd. from page 8
On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
1L
Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml
When sold in quantities of less than or equal to 1 mL or 1 g, with an Excepted Quantity Code of E1, E2, E4, or E5, this item meets the De Minimis Quantities exemption, per IATA 2.6.10. Therefore packaging does not have to be labeled as Dangerous Goods/Excepted Quantity.
UN 1170 ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION), 3, II

15 Regulatory information

 $^{\cdot}$ Safety, health and environmental regulations/legislation specific for the substance or mixture $^{\cdot}$ Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

• TSCA (Toxic Substances Control Act):

64-17-5 ethanol

ACTIVE

• Hazardous Air Pollutants None of the ingredients is listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

64-17-5 ethanol

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

(Contd. on page 10)

US

Printing date 01/25/2022

Revision date 01/25/2022

(Contd. from page 9)

A3

Trade name: (±)12-HpETE

TLV (Threshold Limit Value)

64-17-5 ethanol

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· National regulations:

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

All chemicals may pose unknown hazards and should be used with caution. This SDS applies only to the material as packaged. If this product is combined with other materials, deteriorates, or becomes contaminated, it may pose hazards not mentioned in this SDS. Cayman Chemical Company assumes no responsibility for incidental or consequential damages, including lost profits, arising from the use of these data. It shall be the user's responsibility to develop proper methods of handling and personal protection based on the actual conditions of use. While this SDS is based on technical data judged to be reliable, Cayman Chemical Company assumes no responsibility for the completeness or accuracy of the information contained herein.

· Department issuing SDS: Environment protection department.

· Contact: -

· Date of preparation / last revision 01/25/2022 / -

Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety **OSHA: Occupational Safety & Health** TLV: Threshold Limit Value PEL: Permissible Exposure Limit **REL: Recommended Exposure Limit** Flam. Liq. 2: Flammable liquids - Category 2 Carc. 1A: Carcinogenicity - Category 1A

US -