

Printing date 01/03/2022

Revision date 01/03/2022

Page 1/10

1 Identification

- · Product identifier
- · Trade name: (±)13-HpODE
- · Article number: 10704
- Application of the substance / the mixture This product is for research use - Not for human or veterinary diagnostic or therapeutic use. It is the responsibility of the purchaser to determine suitability for other applications.
- Details of the supplier of the safety data sheet
 Manufacturer/Supplier: Cayman Chemical Co.
 1180 E. Ellsworth Rd. Ann Arbor, MI 48108 USA
- · Information department: Product safety department
- Emergency telephone number: During normal opening times: +1 (734) 971-3335 US/CANADA: 800-424-9300 Outside US/CANADA: 703-741-5970

2 Hazard(s) identification

	tion of the substance or mixture GHS02 Flame
	2 H225 Highly flammable liquid and vapor. GHS08 Health hazard
Carc. 1A	H350 May cause cancer.
• Label eler • GHS label The produ	

Printing date 01/03/2022

Revision date 01/03/2022

Trade name: (±)13-HpODE

· Hazard pictogr	(Contd. from page 1)
GHS02 GHS0	18
· Signal word Da	
-	ining components of labeling:
ethanol	ining components of labeling.
· Hazard stateme	ents
	nmable liquid and vapor.
H350 May cause	
Precautionary	
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P233 P240	Keep container tightly closed.
P240 P241	Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
	53 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with
	water/shower.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P370+P378	In case of fire: Use CO2, powder or water spray to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international
	regulations.
· Classification	
· NFPA ratings (scale 0 - 4)

Health = 0 Fire = 3 Reactivity = 0

· HMIS-ratings (scale 0 - 4)

HEALTH *0	Health = *0
	Fire = 3
REACTIVITY 0	Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· **Description:** Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 3)

[—] US

Printing date 01/03/2022

Revision date 01/03/2022

Trade name: (±)13-HpODE

			(Contd. from page 2)
· Dangerous compon	ents:		
CAS: 64-17-5 RTECS: KQ6300000	ethanol		99.95%
· Other ingredients			
23017-93-8 (±)13-Hp	ODE		0.05%

4 First-aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed May cause anemia, cough, CNS depression, drowsiness, headache, heart damage, lassitude (weakness, exhaustion), liver damage, narcosis, reproductive effects, teratogenic effects.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. · Environmental precautions: Dilute with plenty of water. Do not allow to enter sewers/ surface or ground water. • Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. · Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information. Protective Action Criteria for Chemicals · PAC-1: 64-17-5 ethanol 1,800 ppm

(Contd. on page 4)

US

Printing date 01/03/2022

Revision date 01/03/2022

Trade name: (±)13-HpODE

(Contd. from page 3)

3300* ppm

15000* ppm

PAC-3:

· PAC-2:

64-17-5 ethanol

64-17-5 ethanol

7 Handling and storage

· Handling:

- Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed. Store in cool, dry conditions in well sealed receptacles. • Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

64-17-5 ethanol

- PEL Long-term value: 1900 mg/m³, 1000 ppm
- REL Long-term value: 1900 mg/m³, 1000 ppm
- Short-term value: 1000 ppm TLV A3

• Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 5)

Printing date 01/03/2022

Revision date 01/03/2022

(Contd. from page 4)

Trade name: (±)13-HpODE

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

d chemical properties
Liquid
Colorless
Alcohol-like
C18H32O4
312.4 g/mol
Not determined.
A solution in ethanol
Not determined.
-114.5 °C (-174.1 °F)
78 °C (172.4 °F)
13 °C (55.4 °F)
Not applicable.
425 °C (797 °F)
Not determined.
Product is not selfigniting.
Product is not explosive. However, formation of explosive air, vapor mixtures are possible.

US

Safety Data Sheet acc. to OSHA HCS

Printing date 01/03/2022

Revision date 01/03/2022

Trade name: (±)13-HpODE

	(Contd. from page 5
· Explosion limits:	
Lower:	3.5 Vol %
Upper:	15 Vol %
· Vapor pressure at 20 °C (68 °F):	59 hPa (44.3 mm Hg)
· Density at 20 °C (68 °F):	0.79 g/cm³ (6.59255 lbs/gal)
Relative density	Not determined.
· Vapor density	Not determined.
• Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water at 20 °C (68 °F):	1,000 g/l
· Partition coefficient (n-octanol/wat	er): Not determined.
· Viscosity:	
Dynamic at 20 °C (68 °F):	1.2 mPas
Kinematic:	Not determined.
SOLUBILITY	DMF: 50 mg/ml; DMSO: 50 mg/ml; Ethanol: 50 mg/ml; PBS
	(pH 7.2): 1 mg/ml
· Solvent content:	
Organic solvents:	100.0 %
VOC content:	99.95 %
	999.5 g/l / 8.34 lb/gal
Solids content:	0.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: strong oxidizing agents
- · Hazardous decomposition products: carbon dioxide, carbon monoxide

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

LD/LC50 values that are relevant for classification: 64-17-5 ethanol Orol TDLO 114 ml/kg (man)

Oral	TDLO	1.14 ml/kg (man)	
	LD50	7,060 mg/kg (rat)	
	TDLO	650 (man)	
Dermal	LD50	40,000 mg/kg (rat)	
	•		(Contd. on page 7)

Printing date 01/03/2022

Revision date 01/03/2022

Trade name: (±)13-HpODE

		(Contd. from page 6)		
Inhalative	LC50/4 h	5,900 mg/m ³ (rat)		
	LC50	20,000 mg/m³/10h (rat)		
	TCLO	1,800 mg/m³/30m (hmn)		
	LCLO	29,300 mg/m³/7h (mouse)		
	TCLO	1,800 (hmn)		
	LC50	10 h - 20,000 mg/m³ (rat)		
	LD50 Inhalation TCLO	1,800 mg/m³/30m (hmn)		
	LC50/4 h	20,000 mg/l (rat)		
Irritation of skin	Irritation	20 mg/24h (rabbit)		
	TDLO	1,800 mg/kg (wmn)		
Irritation of eyes	Irritation	500 mg/24h (rabbit)		
	Intraperitoneal LD50	280 mg/kg (rat)		
	Data	500 mg/24h (rabbit)		
	· Primary irritant effect:			
on the skin: No				
• on the eye: No i	rritating effect. Io sensitizing effects kno			
	cological information:	JWII.		
The product shows the following dangers according to internally approved calculation methods for				
preparations:				
· Carcinogenic categories				
· IARC (International Agency for Research on Cancer)				
64-17-5 ethanol 1				
NTP (National Toxicology Program)				
None of the ingredients is listed.				
· OSHA-Ca (Occupational Safety & Health Administration)				

None of the ingredients is listed.

12 Ecological information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

(Contd. on page 8)

Printing date 01/03/2022

Revision date 01/03/2022

Trade name: (±)13-HpODE

(Contd. from page 7)

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.
- Recommended cleansing agent: Water, if necessary with cleansing agents.

· UN-Number · DOT, IMDG, IATA	UN1170
· UN proper shipping name · DOT · IMDG · IATA	Ethanol solutions ETHANOL SOLUTION (ETHYL ALCOH) SOLUTION) Ethanol solution
Transport hazard class(es)	
DOT	
RAMARIE LOUD	
Class	3 Flammable liquids
· Label	3
Class	3 Flammable liquids
· Label	3
· Packing group · DOT, IMDG, IATA	II
Environmental hazards:	Not applicable.
 Special precautions for user Hazard identification number (Kemler code) 	Warning: Flammable liquids): 33
EMS Number:	F-E,S-D
· Stowage Category	A
 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code 	Not applicable.

Printing date 01/03/2022

Revision date 01/03/2022

Trade name: (±)13-HpODE

	(Contd. from page 8
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
ΙΑΤΑ	
Remarks:	When sold in quantities of less than or equal to 1 mL or 1 g, with an Excepted Quantity Code of E1, E2, E4, or E5, this item meets the De Minimis Quantities exemption, per IATA 2.6.10. Therefore packaging does not have to be labeled as Dangerous Goods/Excepted Quantity.
UN "Model Regulation":	UN 1170 ETHANOL SOLUTION (ETHYL ALCOHO) SOLUTION), 3, II

15 Regulatory information

 $^{\cdot}$ Safety, health and environmental regulations/legislation specific for the substance or mixture $^{\cdot}$ Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

• TSCA (Toxic Substances Control Act):

64-17-5 ethanol

ACTIVE

• Hazardous Air Pollutants None of the ingredients is listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

64-17-5 ethanol

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

(Contd. on page 10)

US

Printing date 01/03/2022

Revision date 01/03/2022

(Contd. from page 9)

A3

Trade name: (±)13-HpODE

TLV (Threshold Limit Value)

64-17-5 ethanol

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· National regulations:

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

All chemicals may pose unknown hazards and should be used with caution. This SDS applies only to the material as packaged. If this product is combined with other materials, deteriorates, or becomes contaminated, it may pose hazards not mentioned in this SDS. Cayman Chemical Company assumes no responsibility for incidental or consequential damages, including lost profits, arising from the use of these data. It shall be the user's responsibility to develop proper methods of handling and personal protection based on the actual conditions of use. While this SDS is based on technical data judged to be reliable, Cayman Chemical Company assumes no responsibility for the completeness or accuracy of the information contained herein.

· Department issuing SDS: Environment protection department.

· Contact: -

· Date of preparation / last revision 01/03/2022 / -

Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety **OSHA: Occupational Safety & Health** TLV: Threshold Limit Value PEL: Permissible Exposure Limit **REL: Recommended Exposure Limit** Flam. Liq. 2: Flammable liquids - Category 2 Carc. 1A: Carcinogenicity - Category 1A

US -