

Page 1/10

Safety Data Sheet acc. to OSHA HCS

Printing date 04/02/2021

Revision date 04/02/2021

1 Identification

· Product identifier

- · Trade name: (±)5-HETE methyl ester
- · Synonym (±)5-hydroxy-6E,8Z,11Z,14Z-eicosatetraenoic acid, methyl ester
- · Article number: 34220, 013466
- · Application of the substance / the mixture For research use only, not for human or veterinary use.

· Details of the supplier of the safety data sheet

- Manufacturer/Supplier: Cayman Chemical Co. 1180 E. Ellsworth Rd. Ann Arbor, MI 48108 USA
- Information department: Product safety department
 Emergency telephone number: During normal opening times: +1 (734) 971-3335 US/CANADA: 800-424-9300 Outside US/CANADA: 703-741-5970

2 Hazard(s) identification

Classification of the substance or mixture



Flam. Liq. 2 H225 Highly flammable liquid and vapor.

· Label elements

- · GHS label elements
- The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



- · Signal word Danger
- · Hazard statements
- H225 Highly flammable liquid and vapor.
- Precautionary statements
- Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

In case of fire: Use for extinction: CO2, powder or water spray.

(Contd. on page 2)

Printing date 04/02/2021

Revision date 04/02/2021

Trade name: (±)5-HETE methyl ester

(Contd. from page 1) Store in a well-ventilated place. Keep cool. Dispose of contents/container in accordance with local/regional/national/international regulations. · Classification system: NFPA ratings (scale 0 - 4) Health = 0Fire = 3 Reactivity = 0 · HMIS-ratings (scale 0 - 4) HEALTH 0 Health = 0 3 Fire = 3 FIRE Reactivity = 0 REACTIVITY 0 · Other hazards · Results of PBT and vPvB assessment • **PBT:** Not applicable. · vPvB: Not applicable. **3** Composition/information on ingredients Chemical characterization: Mixtures • **Description:** Mixture of the substances listed below with nonhazardous additions. · Dangerous components:

CAS: 64-17-5 Ethyl alcohol RTECS: KQ6300000

99.99%

0.01%

Other ingredients

73279-38-6 (±) 5-HETE methyl ester

4 First-aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed May cause anemia, cough, CNS depression, drowsiness, headache, heart damage, lassitude
- (weakness, exhaustion), liver damage, narcosis, reproductive effects, teratogenic effects. Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

(Contd. on page 3)

Printing date 04/02/2021

Revision date 04/02/2021

rade name: (±)5-HETE methyl ester	
 Special hazards arising from the substance or mixture Can release vapors that form explosive mixtures at temperatures at or above the Container explosion may occur under fire conditions. Emits toxic fumes under fire conditions. Sensitive to static discharge. Vapors can travel to a source of ignition and flash back. Advice for firefighters Protective equipment: No special measures required. 	(Contd. from page 2) ne flashpoint.
6 Accidental release measures	
 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Environmental precautions: Dilute with plenty of water. Do not allow to enter sewers/ surface or ground water. Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal bind Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information. Protective Action Criteria for Chemicals 	ders, sawdust).
• PAC-1: 64-17-5 Ethyl alcohol	1,800 ppm
• PAC-2:	.,
64-17-5 Ethyl alcohol	3300* ppm
PAC-3:	
64-17-5 Ethyl alcohol	15000* ppm
7 Handling and storage • Handling: • Precautions for safe handling	

Precautions for safe handling
 No special precautions are necessary if used correctly.
 Avoid breathing dust/fume/gas/mist/vapours/spray.
 Avoid prolonged or repeated exposure.
 Keep away from sources of ignition.
 Take precautionary measures against static discharge.re.

Information about protection against explosions and fires:
 Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.

· Conditions for safe storage, including any incompatibilities

· Storage:

- Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

(Contd. on page 4)

US

Printing date 04/02/2021

Revision date 04/02/2021

Trade name: (±)5-HETE methyl ester

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

64-17-5 Ethyl alcohol

PEL Long-term value: 1900 mg/m³, 1000 ppm

- REL Long-term value: 1900 mg/m³, 1000 ppm
- TLV Short-term value: 1880 mg/m³, 1000 ppm

• Additional information: The lists that were valid during the creation were used as basis.

- Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work.
- · Breathing equipment: Not required.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

(Contd. on page 5)

(Contd. from page 3)

Printing date 04/02/2021

Revision date 04/02/2021

Trade name: (±)5-HETE methyl ester

(Contd. from page 4)

Information on basic physical and	chemical properties
 General Information Appearance: Form: Color: Odor: Structural Formula 	Liquid According to product specification Characteristic C21H34O3
 Molecular Weight Odor threshold: Formulation 	334.5 Not determined. A solution in ethanol
· pH-value:	Not determined.
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	-114.5 °C (-174.1 °F) 78 °C (172.4 °F)
· Flash point:	13 °C (55.4 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	425 °C (797 °F)
Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
[.] Danger of explosion:	Product is not explosive. However, formation of explosive ai vapor mixtures are possible.
· Explosion limits: Lower: Upper:	3.5 Vol % 15 Vol %
· Vapor pressure at 20 °C (68 °F):	59 hPa (44.3 mm Hg)
 Density at 20 °C (68 °F): Relative density Vapor density Evaporation rate 	0.79 g/cm³ (6.59255 lbs/gal) Not determined. Not determined. Not determined.
 Solubility in / Miscibility with Water at 20 °C (68 °F): 	1,000 g/l
· Partition coefficient (n-octanol/wat	er): Not determined.
[.] Viscosity: Dynamic at 20 °C (68 °F): Kinematic:	1.2 mPas Not determined.
 Solvent content: Organic solvents: VOC content: 	100.0 % 99.99 % 999.9 g/l / 8.34 lb/gal
Solids content:	0.0 %

Printing date 04/02/2021

Revision date 04/02/2021

(Contd. from page 5)

Trade name: (±)5-HETE methyl ester

• Other information

No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- · Incompatible materials: No further relevant information available.
- Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:

LD/LC30 values	that are relevant for c	
64-17-5 Ethyl al	cohol	
Oral	TDLO	1.14 ml/kg (man)
	LD50	7,060 mg/kg (rat)
	TDLO	650 (man)
Dermal	LD50	40,000 mg/kg (rat)
Inhalative	LC50/4 h	5,900 mg/m³ (rat)
	LC50	20,000 mg/m³/10h (rat)
	TCLO	1,800 mg/m³/30m (hmn)
	LCLO	29,300 mg/m³/7h (mouse)
	TCLO	1,800 (hmn)
	LC50	10 h - 20,000 mg/m³ (rat)
	LD50 Inhalation TCLO	1,800 mg/m³/30m (hmn)
	LC50/4 h	20,000 mg/l (rat)
Irritation of skin	Irritation	20 mg/24h (rabbit)
	TDLO	1,800 mg/kg (wmn)
Irritation of eyes	Irritation	500 mg/24h (rabbit)
	Intraperitoneal LD50	280 mg/kg (rat)
	Data	500 mg/24h (rabbit)
Primary irritant	effect:	
on the skin: No		
• on the eye: No i		
	lo sensitizing effects kno cological information:	JWII.
Carcinogenic ca	alegories	

· IARC (International Agency for Research on Cancer)

64-17-5 Ethyl alcohol

(Contd. on page 7)

1

US -

Printing date 04/02/2021

Revision date 04/02/2021

(Contd. from page 6)

Trade name: (±)5-HETE methyl ester

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Results of PBT and vPvB assessment

- · **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number	
DOT, IMDG, IATA	UN1170
UN proper shipping name	
DOT	Ethanol solutions
IMDG	ETHANOL SOLUTION (ETHYL ALCOHO
	SOLUTION)
IATA	Ethanol solution

Printing date 04/02/2021

Revision date 04/02/2021

Trade name: (±)5-HETE methyl ester

	(Contd. from page
Transport hazard class(es)	
DOT	
RAMARE LOUD	
Class	3 Flammable liquids
Label	3
IMDG, IATA	
Class	3 Flammable liquids
Label	3
Packing group DOT, IMDG, IATA	11
Environmental hazards:	
	Not applicable.
Special precautions for user Hazard identification number (Kemler code):	Warning: Flammable liquids 33
EMS Number:	F-E,S-D
Stowage Category	A
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
IMDG	
Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E2
LACOPIEU quantities (LW)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
ΙΑΤΑ	
Remarks:	When sold in quantities of less than or equal to 1 m
	or 1 g, with an Excepted Quantity Code of E1, E2, E4, or E5, this item meets the De Minim
	Quantities exemption, per IATA 2.6.10.
	Therefore packaging does not have to be labeled
	Dangerous Goods/Excepted Quantity.
UN "Model Regulation":	UN 1170 ETHANOL SOLUTION (ETHYL ALCOHO
	SOLUTION), 3, II

(Contd. on page 9)

Printing date 04/02/2021

Revision date 04/02/2021

Trade name: (±)5-HETE methyl ester

(Contd. from page 8)

Safety, health and environme No further relevant information Sara	ental regulations/legislation specific for the substance or mixture available.
Section 355 (extremely hazar	rdous substances):
None of the ingredients is listed	d.
Section 313 (Specific toxic cl	hemical listings):
None of the ingredients is listed	d.
TSCA (Toxic Substances Co	ntrol Act):
64-17-5 Ethyl alcohol	ACTIVE
Hazardous Air Pollutants	
None of the ingredients is listed	d.
Proposition 65	
Chemicals known to cause c	ancer:
None of the ingredients is listed	d.
Chemicals known to cause re	eproductive toxicity for females:
None of the ingredients is listed	d.
Chemicals known to cause re	eproductive toxicity for males:
None of the ingredients is listed	d.
Chemicals known to cause d	levelopmental toxicity:
64-17-5 Ethyl alcohol	
Carcinogenic categories	
EPA (Environmental Protecti	on Agency)
None of the ingredients is listed	d.
TLV (Threshold Limit Value)	
64-17-5 Ethyl alcohol	A
NIOSH-Ca (National Institute	for Occupational Safety and Health)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: -
- Date of preparation / last revision 04/02/2021 / -
- · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

- DOT: US Department of Transportation
- IATA: International Air Transport Association
- EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- NFPA: National Fire Protection Association (USA)
- HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU)

Printing date 04/02/2021

Revision date 04/02/2021

Trade name: (±)5-HETE methyl ester

(Contd. from page 9)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flam. Liq. 2: Flammable liquids – Category 2