

Safety Data Sheet acc. to OSHA HCS

Printing date 11/02/2021

Revision date 11/02/2021

1 Identification

- **Product identifier**
- **Trade name: Catalase Formaldehyde Standard**
- **Article number:** 707014
- **Application of the substance / the mixture**
This product is for research use - Not for human or veterinary diagnostic or therapeutic use. It is the responsibility of the purchaser to determine suitability for other applications.
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Cayman Chemical Co.
1180 E. Ellsworth Rd.
Ann Arbor, MI 48108
USA
- **Information department:** Product safety department
- **Emergency telephone number:**
During normal opening times: +1 (734) 971-3335
US/CANADA: 800-424-9300
Outside US/CANADA: 703-741-5970

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS06 Skull and crossbones

Acute Tox. 3 H331 Toxic if inhaled.



GHS08 Health hazard

Muta. 2 H341 Suspected of causing genetic defects.

Carc. 1B H350 May cause cancer.

STOT SE 2 H371 May cause damage to the central nervous system and the visual organs.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/02/2021

Revision date 11/02/2021

Trade name: **Catalase Formaldehyde Standard**

(Contd. from page 1)



GHS07

Acute Tox. 4 H302 Harmful if swallowed.
 Skin Irrit. 2 H315 Causes skin irritation.
 Eye Irrit. 2A H319 Causes serious eye irritation.
 Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS06 GHS07 GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

Formaldehyde
 Methanol

- **Hazard statements**

H225 Highly flammable liquid and vapor.
 H302 Harmful if swallowed.
 H331 Toxic if inhaled.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H317 May cause an allergic skin reaction.
 H341 Suspected of causing genetic defects.
 H350 May cause cancer.
 H371 May cause damage to the central nervous system and the visual organs.

- **Precautionary statements**

P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 P240 Ground/bond container and receiving equipment.
 P241 Use explosion-proof electrical/ventilating/lighting/equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P260 Do not breathe dust/fume/gas/mist/vapors/spray.
 P264 Wash thoroughly after handling.
 P270 Do not eat, drink or smoke when using this product.
 P271 Use only outdoors or in a well-ventilated area.
 P272 Contaminated work clothing must not be allowed out of the workplace.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P301+P312 If swallowed: Call a poison center/doctor if you feel unwell.
 P330 Rinse mouth.
 P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 3)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/02/2021

Revision date 11/02/2021

Trade name: Catalase Formaldehyde Standard

(Contd. from page 2)

P308+P313	IF exposed or concerned: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P321	Specific treatment (see on this label).
P337+P313	If eye irritation persists: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.
P370+P378	In case of fire: Use CO ₂ , powder or water spray to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



Health = 2
Fire = 3
Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = *2
Fire = 3
Reactivity = 0

- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 50-00-0 RTECS: LP8925000	Formaldehyde	12.4–12.7%
CAS: 67-56-1 RTECS: PC1400000	Methanol	3.5–5.2%

- **Other ingredients**

CAS: 7732-18-5 RTECS: ZC0110000	Water	82.1–83.8%
------------------------------------	-------	------------

4 First-aid measures

- **Description of first aid measures**

- **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Remove breathing apparatus only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/02/2021

Revision date 11/02/2021

Trade name: Catalase Formaldehyde Standard

(Contd. from page 3)

- **After inhalation:**
Supply fresh air or oxygen; call for doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
May cause anemia, cough, CNS depression, drowsiness, headache, heart damage, lassitude (weakness, exhaustion), liver damage, narcosis, reproductive effects, teratogenic effects.
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture**
67-56-1 During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

PAC-1:

50-00-0	Formaldehyde	0.90 ppm
67-56-1	Methanol	530 ppm

PAC-2:

50-00-0	Formaldehyde	14 ppm
67-56-1	Methanol	2,100 ppm

PAC-3:

50-00-0	Formaldehyde	56 ppm
---------	--------------	--------

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/02/2021

Revision date 11/02/2021

Trade name: Catalase Formaldehyde Standard

67-56-1 Methanol

(Contd. from page 4)

7200* ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
Keep container tightly closed.
Store in accordance with information listed on the product insert.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**

50-00-0 Formaldehyde

PEL	Short-term value: 2 ppm Long-term value: 0.75 ppm see 29 CFR 1910.1048(c)
REL	Long-term value: 0.016 ppm Ceiling limit value: 0.1* ppm *15-min; See Pocket Guide App. A
TLV	Short-term value: 0.3 ppm Long-term value: 0.1 ppm DSEN; RSEN, A1

67-56-1 Methanol

PEL	Long-term value: 260 mg/m ³ , 200 ppm
REL	Short-term value: 325 mg/m ³ , 250 ppm Long-term value: 260 mg/m ³ , 200 ppm Skin
TLV	Short-term value: 250 ppm Long-term value: 200 ppm Skin; BEI

(Contd. on page 6)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/02/2021

Revision date 11/02/2021

Trade name: Catalase Formaldehyde Standard

(Contd. from page 5)

· **Ingredients with biological limit values:**

67-56-1 Methanol

BEI	15 mg/L
	Medium: urine
	Time: end of shift
	Parameter: Methanol (background, nonspecific)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Liquid
Color:	According to product specification
Odor:	Characteristic

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/02/2021

Revision date 11/02/2021

Trade name: Catalase Formaldehyde Standard

(Contd. from page 6)

· Odor threshold:	Not determined.
· Formulation	4.25 M formaldehyde
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	64.7 °C (148.5 °F)
· Flash point:	11 °C (51.8 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	~300 °C (~572 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	7 Vol %
Upper:	73 Vol %
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)
· Density at 20 °C (68 °F):	0.93323–1.00199 g/cm ³ (7.7878–8.36161 lbs/gal)
· Bulk density:	933–1,002 kg/m ³
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	15.9–17.9 %
Water:	82.1–83.8 %
VOC content:	15.9–17.9 %
	167–179.4 g/l / 1.39–1.5 lb/gal
Solids content:	12.4–12.7 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/02/2021

Revision date 11/02/2021

Trade name: Catalase Formaldehyde Standard

(Contd. from page 7)

- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Oral	LD50	>1,575–1,613 mg/kg (rat)
Dermal	LD50	2,362–2,419 mg/kg
Inhalative	LC50/4 h	3.94–4.03 mg/l

50-00-0 Formaldehyde

Oral	LDLO	70 mg/kg (hmn)
	TDLO	3.6 ml/kg (wmn)
	LD50	42 mg/kg (mouse) >200 mg/kg (rat)
Dermal	LD50	270 mg/kg (rabbit)
Inhalative	LC50/4 h	64,000 mg/m ³ (rat)
	LC50	250 mg/m ³ /2h (rat)
	TCLo	300 µg/m ³ (man)
Irritation of skin	Irritation	2 mg/24h (rabbit)
Irritation of eyes	Irritation	750 µg/24h (rabbit)

67-56-1 Methanol

Oral	LDLO	143 mg/kg (hmn)
	TDLO	5 ml/kg (rat)
	LD50	5,600 mg/kg (rat)
Dermal	LD50	15,800 mg/kg (rabbit)
Inhalative	LC50/4 h	64,000 mg/m ³ (rat)
	LC50	61,100 mg/m ³ /134 m (mouse)
Irritation of skin	Irritation	20 mg/24h (rabbit)
	Irritation	(rabbit)
	Irritation	5.63 mg/kg/exempt preparation (rabbit)
Irritation of eyes	Irritation	40 mg (rabbit)
	Intraperitoneal TDLO	5 mg/kg (rat)
	Intraperitoneal LD50	10,765 mg/kg (mouse)
	Subcutaneous LD50	143 mg/kg/human (mouse)
	Data	20 mg/24h (rabbit)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.

(Contd. on page 9)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/02/2021

Revision date 11/02/2021

Trade name: Catalase Formaldehyde Standard

(Contd. from page 8)

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Toxic
Harmful
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

50-00-0	Formaldehyde	1
---------	--------------	---

- **NTP (National Toxicology Program)**

50-00-0	Formaldehyde	K
---------	--------------	---

- **OSHA-Ca (Occupational Safety & Health Administration)**

50-00-0	Formaldehyde	
---------	--------------	--

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.

- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- **UN-Number**

- **DOT, IMDG, IATA**

UN3286

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/02/2021

Revision date 11/02/2021

Trade name: Catalase Formaldehyde Standard

(Contd. from page 9)

· UN proper shipping name	
· DOT	Flammable liquid, toxic, corrosive, n.o.s. (Methanol, Formaldehyde solutions, flammable)
· IMDG	FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (METHANOL, FORMALDEHYDE SOLUTION, FLAMMABLE)
· IATA	Flammable liquid, toxic, corrosive, n.o.s. (METHANOL, FORMALDEHYDE SOLUTION, FLAMMABLE)

· Transport hazard class(es)

· DOT



· Class

3 Flammable liquids

· Label

3, 6.1, 8

· IMDG



· Class

3 Flammable liquids

· Label

3/6.1/8

· IATA



· Class

3 Flammable liquids

· Label

3 (6.1, 8)

· Packing group

· DOT, IMDG, IATA

II

· Environmental hazards:

Not applicable.

· Special precautions for user

Warning: Flammable liquids

· Hazard identification number (Kemler code):

368

· EMS Number:

F-E,S-C

· Stowage Category

B

· Stowage Code

SW2 Clear of living quarters.

· Segregation Code

SG5 Segregation as for class 3

SG8 Stow "away from" class 4.1

· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

(Contd. on page 11)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/02/2021

Revision date 11/02/2021

Trade name: Catalase Formaldehyde Standard

(Contd. from page 10)

· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 1 L On cargo aircraft only: 5 L
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· IATA	
· Remarks:	When sold in quantities of less than or equal to 1 mL, or 1 g, with an Excepted Quantity Code of E1, E2, E4, or E5, this item meets the De Minimis Quantities exemption, per IATA 2.6.10. Therefore packaging does not have to be labeled as Dangerous Goods/Excepted Quantity.
· UN "Model Regulation":	UN 3286 FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (METHANOL, FORMALDEHYDE SOLUTION, FLAMMABLE), 3 (6.1+8), II

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):	
50-00-0	Formaldehyde

· Section 313 (Specific toxic chemical listings):	
50-00-0	Formaldehyde
67-56-1	Methanol

· TSCA (Toxic Substances Control Act):	
All components have the value ACTIVE.	

· Hazardous Air Pollutants	
50-00-0	Formaldehyde
67-56-1	Methanol

· Proposition 65	
· Chemicals known to cause cancer:	
50-00-0	Formaldehyde

· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	

· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	

· Chemicals known to cause developmental toxicity:	
67-56-1	Methanol

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/02/2021

Revision date 11/02/2021

Trade name: Catalase Formaldehyde Standard

(Contd. from page 11)

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

50-00-0	Formaldehyde	B1
---------	--------------	----

- **TLV (Threshold Limit Value)**

50-00-0	Formaldehyde	A2
---------	--------------	----

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

50-00-0	Formaldehyde	
---------	--------------	--

- **National regulations:**

- **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

All chemicals may pose unknown hazards and should be used with caution. This SDS applies only to the material as packaged. If this product is combined with other materials, deteriorates, or becomes contaminated, it may pose hazards not mentioned in this SDS. Cayman Chemical Company assumes no responsibility for incidental or consequential damages, including lost profits, arising from the use of these data. It shall be the user's responsibility to develop proper methods of handling and personal protection based on the actual conditions of use. While this SDS is based on technical data judged to be reliable, Cayman Chemical Company assumes no responsibility for the completeness or accuracy of the information contained herein.

- **Department issuing SDS:** Environment protection department.

- **Contact:** -

- **Date of preparation / last revision** 11/02/2021 / -

- **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 3: Acute toxicity – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Skin Sens. 1: Skin sensitisation – Category 1

Muta. 2: Germ cell mutagenicity – Category 2

Carc. 1B: Carcinogenicity – Category 1B

STOT SE 2: Specific target organ toxicity (single exposure) – Category 2

- *** Data compared to the previous version altered.**