

# Sodium arsenate dibasic heptahydrate

sc-212937



The Power is Question

## Material Safety Data Sheet

Hazard Alert Code Key: **EXTREME** **HIGH** **MODERATE** **LOW**

## Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

### PRODUCT NAME

Sodium arsenate dibasic heptahydrate

### STATEMENT OF HAZARDOUS NATURE

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

### NFPA



### SUPPLIER

Santa Cruz Biotechnology, Inc.  
2145 Delaware Avenue  
Santa Cruz, California 95060  
800.457.3801 or 831.457.3800

### EMERGENCY

ChemWatch  
Within the US & Canada: 877-715-9305  
Outside the US & Canada: +800 2436 2255  
(1-800-CHEMCALL) or call +613 9573 3112

### SYNONYMS

H-As-Na<sub>2</sub>-O<sub>4</sub>, AsHO<sub>4</sub>.2Na, H-As\_Na<sub>2</sub>-O<sub>4</sub>.7H<sub>2</sub>O, AsHO<sub>4</sub>.2Na.7H<sub>2</sub>O, H-As-Na<sub>2</sub>-O<sub>4</sub>.12H<sub>2</sub>O, AsHO<sub>4</sub>.2Na.12H<sub>2</sub>O, "arsenic acid, disodium salt, heptahydrate", "sodium arseniate", "dibasic sodium arsenate heptahydrate", "sodium arsenate heptahydrate", "sodium acid arsenate", "sodium monohydrogen orthoarsenate"

## Section 2 - HAZARDS IDENTIFICATION

### CHEMWATCH HAZARD RATINGS

	Min	Max
Flammability:	0	■
Toxicity:	3	■
Body Contact:	2	■
Reactivity:	0	■
Chronic:	4	■

Min/Nil=0  
Low=1  
Moderate=2  
High=3  
Extreme=4



### CANADIAN WHMIS SYMBOLS



## EMERGENCY OVERVIEW

### RISK

May cause CANCER.

Toxic by inhalation and if swallowed.

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### POTENTIAL HEALTH EFFECTS

#### ACUTE HEALTH EFFECTS

##### SWALLOWED

■ Toxic effects may result from the accidental ingestion of the material; animal experiments indicate that ingestion of less than 40 gram may be fatal or may produce serious damage to the health of the individual.

■ Ingestion may produce nausea, vomiting and diarrhea, bloody stools, shock, rapid pulse and coma.

Severe gastritis or gastroenteritis may occur as a result of lesions produced by vascular damage from absorbed arsenic (and not local corrosion); symptoms may be delayed for several hours.

##### EYE

■ Although the material is not thought to be an irritant, direct contact with the eye may cause transient discomfort characterized by tearing or conjunctival redness (as with windburn).

Slight abrasive damage may also result.

##### SKIN

■ There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons.

■ Open cuts, abraded or irritated skin should not be exposed to this material.

■ Arsenic can cause skin irritation characterized by eczema, scaling, sensitization, and discoloration and thickening of the palms and soles.

■ Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects.

Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

##### INHALED

■ Inhalation of dusts, generated by the material, during the course of normal handling, may produce toxic effects.

■ There is some evidence to suggest that the material can cause respiratory irritation in some persons.

The body's response to such irritation can cause further lung damage.

■ Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.

■ Inhaling materials containing arsenic can cause severe irritation to the nose, throat and lungs.

Prolonged exposure can cause severe structural damage to the nose.

■ BE AWARE: Repeated minor exposures with only mild symptoms may have serious cumulative poisoning effect.

##### CHRONIC HEALTH EFFECTS

■ There is sufficient evidence to suggest that this material directly causes cancer in humans.

Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.

There is limited evidence that, skin contact with this product is more likely to cause a sensitization reaction in some persons compared to the general population.

Long term exposure to high dust concentrations may cause changes in lung function i.e. pneumoconiosis; caused by particles less than 0.5 micron penetrating and remaining in the lung.

Long-term exposure to arsenic and its inorganic salts may produce loss of appetite, nausea and vomiting, low fever, persistent headache, pallor, weakness and phlegm. Skin effects include redness, eczema, pigmentation, diffuse hair loss, scaling of the palms and soles, sloughing, brittle nails, white lines or bands on the nails, loss of hair and nails, and localized swelling.

## Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
disodium arsenate heptahydrate	10048-95-0	> 98

## Section 4 - FIRST AID MEASURES

##### SWALLOWED

· IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY. · Where Medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed otherwise:

##### EYE

■ If this product comes in contact with the eyes: · Immediately hold eyelids apart and flush the eye continuously with running water. · Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.

##### SKIN

■ If skin contact occurs: · Immediately remove all contaminated clothing, including footwear · Flush skin and hair with running water (and soap if available).

#### **INHALED**

· If fumes or combustion products are inhaled remove from contaminated area. · Lay patient down. Keep warm and rested.

#### **NOTES TO PHYSICIAN**

■ For acute or short term repeated exposures to arsenic, soluble compounds: Treat as per arsenic poisoning.

· Acute skin lesions such as contact dermatitis usually do not require other treatment than removal from exposure.

· If more severe symptoms of the respiratory system, the skin or the gastro-intestinal tract occur, British Anti-Lewisite (BAL, dimercaprol) may be given. Prompt administration in such cases is vital; to obtain maximum benefit such treatment should be administered within 4 hours of poisoning.

\* Preplacement and periodic medical examinations are essential for workers exposed to arsenic on a regular basis. Preplacement physical examinations should give particular attention to allergic and chronic skin lesions, eye disease, psoriasis, chronic eczematous dermatitis, hyperpigmentation of the skin, keratosis and warts, baseline weight, baseline blood and haemoglobin counts, baseline urinary arsenic determinations.

Annual physical examinations should give attention to general health, weight, skin condition, and any evidence of excessive exposure or absorption of arsenic.

## **Section 5 - FIRE FIGHTING MEASURES**

Vapour Pressure (mmHG):	Not available.
Upper Explosive Limit (%):	Not applicable
Specific Gravity (water=1):	1.88
Lower Explosive Limit (%):	Not applicable

#### **EXTINGUISHING MEDIA**

· Water spray or fog.  
· Foam.

#### **FIRE FIGHTING**

· Alert Emergency Responders and tell them location and nature of hazard.  
· Wear full body protective clothing with breathing apparatus.

When any large container (including road and rail tankers) is involved in a fire, consider evacuation by 800 metres in all directions.

#### **GENERAL FIRE HAZARDS/HAZARDOUS COMBUSTIBLE PRODUCTS**

· Non combustible.  
· Not considered to be a significant fire risk, however containers may burn.  
Decomposition may produce toxic fumes of: metal oxides, arsenic compounds.  
May emit poisonous fumes.

In a fire decomposition products include toxic arsenic metal fumes. In some circumstances the material may give off highly poisonous (garlic odour) arsine gas.

#### **FIRE INCOMPATIBILITY**

■ None known.

#### **PERSONAL PROTECTION**

Glasses:

Chemical goggles.

Gloves:

Respirator:

Particulate

## **Section 6 - ACCIDENTAL RELEASE MEASURES**

#### **MINOR SPILLS**

· Clean up waste regularly and abnormal spills immediately.  
· Avoid breathing dust and contact with skin and eyes.  
· Wear protective clothing, gloves, safety glasses and dust respirator.  
· Use dry clean up procedures and avoid generating dust.  
· Vacuum up or sweep up. NOTE: Vacuum cleaner must be fitted with an exhaust micro filter (HEPA type) (consider explosion-proof machines designed to be grounded during storage and use).  
· Dampen with water to prevent dusting before sweeping.  
· Place in suitable containers for disposal.

#### **MAJOR SPILLS**

· Clear area of personnel and move upwind.  
· Alert Emergency Responders and tell them location and nature of hazard.  
· DO NOT touch the spill material.

## **Section 7 - HANDLING AND STORAGE**

#### **PROCEDURE FOR HANDLING**

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.

### RECOMMENDED STORAGE METHODS

■ Glass container.

- Lined metal can, Lined metal pail/drum
- Plastic pail.

For low viscosity materials

- Drums and jerricans must be of the non-removable head type.
- Where a can is to be used as an inner package, the can must have a screwed enclosure.

All inner and sole packagings for substances that have been assigned to Packaging Groups I or II on the basis of inhalation toxicity criteria, must be hermetically sealed.

### STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m <sup>3</sup>	STEL ppm	STEL mg/m <sup>3</sup>	Peak ppm	Peak mg/m <sup>3</sup>	TWA F/CC	Notes
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	disodium arsenate heptahydrate (Arsenic and compounds (as As))	-	0.5	-	0.5				
Canada - Ontario Occupational Exposure Limits	disodium arsenate heptahydrate (*Arsenic, elemental arsenic and inorganic compounds, and organic compounds (only where both inorganic and organic compounds are present), as As.)		0.01		0.05				
Canada - British Columbia Occupational Exposure Limits	disodium arsenate heptahydrate (Arsenic and inorganic compounds, as As)		0.01						A1, 1
US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants	disodium arsenate heptahydrate (Arsenic, inorganic compounds (as As); see 1910.1018.)	Varies with compound							
US - California Permissible Exposure Limits for Chemical Contaminants	disodium arsenate heptahydrate (Arsenic and inorganic arsenic compounds; see also Section 5214)		0.01						

US - Hawaii Air Contaminant Limits	disodium arsenate heptahydrate (Arsenic, inorganic compounds, (as As))	0.01			See ¶12-202-31
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	disodium arsenate heptahydrate (Arsenic, and inorganic compounds, (as As))	0.01	0.03		T20
US - Washington Permissible exposure limits of air contaminants	disodium arsenate heptahydrate (Arsenic, inorganic compounds (as As) (when use is covered by chapter 296-848 WAC))	0.01			
US - Washington Permissible exposure limits of air contaminants	disodium arsenate heptahydrate (Arsenic, inorganic compounds (as As) (when use is not covered by chapter 296-848 WAC))	0.2	0.6		
US NIOSH Recommended Exposure Limits (RELs)	disodium arsenate heptahydrate (Arsenic (inorganic compounds, as As))			0.002	See Appendix A; Ca; (Ceiling (15-minute))
Canada - Alberta Occupational Exposure Limits	disodium arsenate heptahydrate (Arsenic, elemental & inorganic compounds as As)	0.01			
US OSHA Permissible Exposure Levels (PELs) - Table Z1	disodium arsenate heptahydrate (Arsenic, inorganic compounds (as As); see 1910.1018)	0.01			
US - Michigan Exposure Limits for Air Contaminants	disodium arsenate heptahydrate (Arsenic, inorganic compounds (as As); see R 325.51601 et seq.F)	0.01			
Canada - Nova Scotia Occupational Exposure Limits	disodium arsenate heptahydrate (Arsenic -	0.01			Measured as As. TLV Basis: lung cancer

	Inorganic compounds)			
Canada - Northwest Territories Occupational Exposure Limits (English)	disodium arsenate heptahydrate (Arsenic & soluble compounds (as As))	0.2	0.6	
US - Oregon Permissible Exposure Limits (Z-1)	disodium arsenate heptahydrate (Arsenic, Organic Compounds (as As))	0.5		
US - California Permissible Exposure Limits for Chemical Contaminants	disodium arsenate heptahydrate (Arsenic, organic compounds, as As)	0.2		
US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants	disodium arsenate heptahydrate (Arsenic, organic compounds (as As))	0.5		
US ACGIH Threshold Limit Values (TLV)	disodium arsenate heptahydrate (Arsenic - Inorganic compounds)	0.01		Measured as As. TLV Basis: lung cancer
US - Oregon Permissible Exposure Limits (Z-1)	disodium arsenate heptahydrate (Arsenic, Inorganic Compounds (as As))	0.01		See 1910.1018
Canada - Prince Edward Island Occupational Exposure Limits	disodium arsenate heptahydrate (Arsenic - Inorganic compounds)	0.01		Measured as As. TLV Basis: lung cancer
Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)	disodium arsenate heptahydrate (Arsenic, elemental, and inorganic compounds (except Arsine), (as As))	0.1		

ENDOELTABLE

**PERSONAL PROTECTION**



## RESPIRATOR

Particulate

Consult your EHS staff for recommendations

## EYE

- Safety glasses with side shields.
- Chemical goggles.

## HANDS/FEET

■ Wear chemical protective gloves, eg. PVC.

NOTE: The material may produce skin sensitization in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: such as:

- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and
- dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739).

· When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended.

· When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended.

· Contaminated gloves should be replaced.

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

## OTHER

· Employees working with confirmed human carcinogens should be provided with, and be required to wear, clean, full body protective clothing (smocks, coveralls, or long-sleeved shirt and pants), shoe covers and gloves prior to entering the regulated area.

· Employees engaged in handling operations involving carcinogens should be provided with, and required to wear and use half-face filter-type respirators with filters for dusts, mists and fumes, or air purifying canisters or cartridges. A respirator affording higher levels of protection may be substituted.

· Emergency deluge showers and eyewash fountains, supplied with potable water, should be located near, within sight of, and on the same level with locations where direct exposure is likely.

· Prior to each exit from an area containing confirmed human carcinogens, employees should be required to remove and leave protective clothing and equipment at the point of exit and at the last exit of the day, to place used clothing and equipment in impervious containers at the point of exit for purposes of decontamination or disposal. The contents of such impervious containers must be identified with suitable labels. For maintenance and decontamination activities, authorized employees entering the area should be provided with and required to wear clean, impervious garments, including gloves, boots and continuous-air supplied hood.

· Prior to removing protective garments the employee should undergo decontamination and be required to shower upon removal of the garments and hood.

## ENGINEERING CONTROLS

· Employees exposed to confirmed human carcinogens should be authorized to do so by the employer, and work in a regulated area.

· Work should be undertaken in an isolated system such as a "glove-box" . Employees should wash their hands and arms upon completion of the assigned task and before engaging in other activities not associated with the isolated system.

· Within regulated areas, the carcinogen should be stored in sealed containers, or enclosed in a closed system, including piping systems, with any sample ports or openings closed while the carcinogens are contained within.

· Open-vessel systems are prohibited.

· Each operation should be provided with continuous local exhaust ventilation so that air movement is always from ordinary work areas to the operation.

· Exhaust air should not be discharged to regulated areas, non-regulated areas or the external environment unless decontaminated. Clean make-up air should be introduced in sufficient volume to maintain correct operation of the local exhaust system.

· For maintenance and decontamination activities, authorized employees entering the area should be provided with and required to wear clean, impervious garments, including gloves, boots and continuous-air supplied hood. Prior to removing protective garments the employee should undergo decontamination and be required to shower upon removal of the garments and hood.

· Except for outdoor systems, regulated areas should be maintained under negative pressure (with respect to non-regulated areas).

· Local exhaust ventilation requires make-up air be supplied in equal volumes to replaced air.

· Laboratory hoods must be designed and maintained so as to draw air inward at an average linear face velocity of 150 feet/ min. with a minimum of 125 feet/ min. Design and construction of the fume hood requires that insertion of any portion of the employees body, other than hands and arms, be disallowed.

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

### PHYSICAL PROPERTIES

Solid.

Mixes with water.

State	Divided solid	Molecular Weight	312.02 heptydr
Melting Range (°F)	266 - H2O	Viscosity	Not Applicable
Boiling Range (°F)	356 decomp.	Solubility in water (g/L)	Soluble
Flash Point (°F)	Not applicable	pH (1% solution)	Not available.
Decomposition Temp (°F)	Not Available	pH (as supplied)	Not applicable

Autoignition Temp (°F)	Not applicable	Vapour Pressure (mmHG)	Not available.
Upper Explosive Limit (%)	Not applicable	Specific Gravity (water=1)	1.88
Lower Explosive Limit (%)	Not applicable	Relative Vapor Density (air=1)	Not Applicable
Volatile Component (%vol)	Nil @ 38C	Evaporation Rate	Non Volatile

## APPEARANCE

Odourless, fine white or colourless crystals. Highly soluble in water. Sodium arsenate is available in several different forms: sodium orthoarsenate  $\text{AsH}_3\text{O}_4\cdot\text{Na}$  CAS 7631-89-2 disodium monohydrogen arsenate  $\text{AsHO}_4\cdot 2\text{Na}$  CAS 7778-43-0 disodium monohydrogen arsenate heptahydrate  $\text{AsHO}_4\cdot 2\text{Na}\cdot 7\text{H}_2\text{O}$  CAS 10048-95-0 sodium dihydrogen arsenate  $\text{AsH}_2\text{O}_4\cdot\text{Na}$  CAS 10103-60-3 trisodium arsenate  $\text{AsO}_4\cdot\text{Na}_3$  CAS 13464-38-3 sodium meta arsenate  $\text{AsO}_3\cdot\text{Na}$  CAS 15120-17-9

## Section 10 - CHEMICAL STABILITY

### CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.

### STORAGE INCOMPATIBILITY

- Contact with acids produces toxic fumes.
- Metals and their oxides or salts may react violently with chlorine trifluoride and bromine trifluoride.
- These trifluorides are hypergolic oxidisers. They ignites on contact (without external source of heat or ignition) with recognised fuels - contact with these materials, following an ambient or slightly elevated temperature, is often violent and may produce ignition.
- The state of subdivision may affect the results.
- Arsine, an extremely poisonous (lethal) gas with a garlic odour can be generated when the material reacts with acids, alkalis or water in the presence of an active metal (zinc, aluminium, magnesium, sodium, iron etc.).
- Avoid strong acids, bases.

For incompatible materials - refer to Section 7 - Handling and Storage.

## Section 11 - TOXICOLOGICAL INFORMATION

disodium arsenate heptahydrate

### TOXICITY AND IRRITATION

DISODIUM ARSENATE HEPTAHYDRATE:

■ unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY	IRRITATION
----------	------------

Intramuscular (mouse) LD50: 87.36 mg/kg Nil Reported

■ Arsenic compounds are classified by the European Union as toxic by inhalation and ingestion and toxic to aquatic life and long lasting in the environment. IARC classify arsenic indrinkng water as a confirmed human carcinogen (IARC 1).

### CARCINOGEN

	US - Rhode Island Hazardous Substance List	IARC	C
INORGANIC ARSENIC COMPOUNDS	US Environmental Defense Scorecard Recognized Carcinogens	Reference(s)	P65
INORGANIC ARSENIC COMPOUNDS	US Environmental Defense Scorecard Suspected Carcinogens	Reference(s)	P65
ARSENIC (ORGANIC OR INORGANIC COMPOUNDS)	US Environmental Defense Scorecard Suspected Carcinogens	Reference(s)	P65-MC
ARSENIC COMPOUNDS	US Environmental Defense Scorecard Suspected Carcinogens	Reference(s)	HAZMAP, IARC
VPVB_(VERY~	US - Maine Chemicals of High Concern List	Carcinogen	CA Prop 65; IARC; IRIS; NTP 11th ROC
VPVB_(VERY~	US - Maine Chemicals of High Concern List	Carcinogen	IARC
VPVB_(VERY~	US - Maine Chemicals of High Concern List	Carcinogen	EU Carcinogen

## Section 12 - ECOLOGICAL INFORMATION

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

This material and its container must be disposed of as hazardous waste.

Avoid release to the environment.

Refer to special instructions/ safety data sheets.



## Section 13 - DISPOSAL CONSIDERATIONS

### US EPA Waste Number & Descriptions

A. General Product Information

Toxicity characteristic: use EPA hazardous waste number D004 (waste code E) if this substance, in a solid waste, produces an extract containing greater than 5 mg/L of arsenic.

### Disposal Instructions

All waste must be handled in accordance with local, state and federal regulations.

! Puncture containers to prevent re-use and bury at an authorized landfill.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- Reuse
- Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

DO NOT allow wash water from cleaning equipment to enter drains. Collect all wash water for treatment before disposal.

- Recycle wherever possible or consult manufacturer for recycling options.
- Consult Waste Management Authority for disposal.

## Section 14 - TRANSPORTATION INFORMATION



DOT:

Symbols: None Hazard class or Division: 6.1

Identification Numbers: UN1685 PG: II

Label Codes: 6.1 Special provisions: IB8, IP2,

IP4, T3,

TP33

Packaging: Exceptions: 153 Packaging: Non- bulk: 212

Packaging: Exceptions: 153 Quantity limitations: 25 kg

Passenger aircraft/rail:

Quantity Limitations: Cargo 100 kg Vessel stowage: Location: A aircraft only:

Vessel stowage: Other: None

Hazardous materials descriptions and proper shipping names:

Sodium arsenate

### Air Transport IATA:

ICAO/IATA Class: 6.1 ICAO/IATA Subrisk: None

UN/ID Number: 1685 Packing Group: II

Special provisions: None

Cargo Only

Packing Instructions: 100 kg Maximum Qty/Pack: 25 kg

Passenger and Cargo Passenger and Cargo

Packing Instructions: 615 Maximum Qty/Pack: 613

Passenger and Cargo Limited Quantity Passenger and Cargo Limited Quantity

Packing Instructions: 1 kg Maximum Qty/Pack: Y613

Shipping Name: SODIUM ARSENATE

### Maritime Transport IMDG:

IMDG Class: 6.1 IMDG Subrisk: None

UN Number: 1685 Packing Group: II

EMS Number: F-A , S-A Special provisions: None

Limited Quantities: 500 g Marine Pollutant: Yes

Shipping Name: SODIUM ARSENATE

## Section 15 - REGULATORY INFORMATION

**disodium arsenate heptahydrate (CAS: 10048-95-0,7778-43-0) is found on the following regulatory lists;**

"Canada Domestic Substances List (DSL)","Canada Ingredient Disclosure List (SOR/88-64)","Canada Toxicological Index Service -

## Section 16 - OTHER INFORMATION

### Ingredients with multiple CAS Nos

Ingredient Name CAS disodium arsenate heptahydrate 10048-95-0, 7778-43-0

*Reasonable care has been taken in the preparation of this information, but the author makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The author makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. For additional technical information please call our toxicology department on +800 CHEMCALL.*

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:  
[www.chemwatch.net/references](http://www.chemwatch.net/references).

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

*This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.*

Issue Date: Dec-22-2009

Print Date: Mar-5-2011