

EMERGENCY OVERVIEW RISK POTENTIAL HEALTH EFFECTS ACUTE HEALTH EFFECTS

sc-215946



**Material Safety Data Sheet** 

Hazard Alert Code Key:	EXTREME	HIGH	MODERATE	LOW

#### SWALLOWED

■ The material has NOT been classified as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g. liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality (death) rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, unintentional ingestion is not thought to be cause for concern.

#### EYE

■ Although the material is not thought to be an irritant, direct contact with the eye may cause transient discomfort characterized by tearing or conjunctival redness (as with windburn). Slight abrasive damage may also result. The material may produce foreign body irritation in certain individuals.

#### SKIN

■ The material is not thought to produce adverse health effects or skin irritation following contact (as classified using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.

Open cuts, abraded or irritated skin should not be exposed to this material.

• Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

#### INHALED

■ The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.

■ Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.

#### **CHRONIC HEALTH EFFECTS**


■ Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.

There is some evidence that human exposure to the material may result in developmental toxicity. This evidence is based on animal studies where effects have been observed in the absence of marked maternal toxicity, or at around the same dose levels as other toxic effects but which are not secondary non-specific consequences of the other toxic effects.

Long term exposure to high dust concentrations may cause changes in lung function i.e. pneumoconiosis; caused by particles less than 0.5 micron penetrating and remaining in the lung. Prime symptom is breathlessness; lung shadows show on X-ray.

Chronic intoxication with ionic bromides, historically, has resulted from medical use of bromides but not from environmental or occupational exposure; depression, hallucinosis, and schizophreniform psychosis can be seen in the absence of other signs of intoxication. Bromides may also induce sedation, irritability, agitation, delirium, memory loss, confusion, disorientation, forgetfulness (aphasias), dysarthria, weakness, fatigue, vertigo, stupor, coma, decreased appetite, nausea and vomiting, diarrhoea, hallucinations, an acne like rash on the face, legs and trunk, known as bronchoderma (seen in 25-30% of case involving bromide ion), and a profuse discharge from the nostrils (coryza). Ataxia and generalised hyperreflexia have also been observed. Correlation of neurologic symptoms with blood levels of bromide is inexact. The use of substances such as brompheniramine, as antihistamines, largely reflect current day usage of bromides; ionic bromides have been largely withdrawn from therapeutic use due to their toxicity. Several cases of foetal abnormalities have been described in mothers who took large doses of bromides during pregnancy.

# Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS



sc-215946



Material Safety Data Sheet LOW Hazard Alert Code Key: EXTREME HIGH MODERATE Section 4 - FIRST AID MEASURES **SWALLOWED** Immediately give a glass of water. ٠ First aid is not generally required. If in doubt, contact a Poisons Information Center or a doctor. EYE If this product comes in contact with eyes: • Wash out immediately with water. • If irritation continues, seek medical attention. Removal of contact lenses after an eve injury should only be undertaken by skilled personnel. SKIN If skin or hair contact occurs: Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation. INHALED If dust is inhaled, remove from contaminated area. • • Encourage patient to blow nose to ensure clear passage of breathing. • If irritation or discomfort persists seek medical attention.

#### NOTES TO PHYSICIAN

Treat symptomatically.

## Section 5 - FIRE FIGHTING MEASURES

Vapour Pressure (mmHG):	Negligible
Upper Explosive Limit (%):	Not available.
Specific Gravity (water=1):	Not available
Lower Explosive Limit (%):	Not available

## **EXTINGUISHING MEDIA**

- Water spray or fog.
- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

#### **FIRE FIGHTING**

- Alert Emergency Responders and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- Use water delivered as a fine spray to control fire and cool adjacent area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

#### **GENERAL FIRE HAZARDS/HAZARDOUS COMBUSTIBLE PRODUCTS**

- Combustible solid which burns but propagates flame with difficulty.
- Avoid generating dust, particularly clouds of dust in a confined or unventilated space as dusts may form an explosive mixture with air, and any source of ignition, i.e. flame or spark, will cause fire or explosion. Dust clouds generated by the fine grinding of the solid are a particular hazard; accumulations of fine dust may burn rapidly and fiercely if ignited.
- Dry dust can be charged electrostatically by turbulence, pneumatic transport, pouring, in exhaust ducts and during transport.

# sc-215946



#### Material Safety Data Sheet

	Hazard Alert Code Key:	EXTREME	HIGH	MODERATE	LOW			
•	<ul> <li>Build-up of electrostatic charge may be prevented by bonding and grounding.</li> </ul>							
•	Powder handling equipm venting.	nent such as dust collectors	s, dryers and mills may re	equire additional protection m	neasures such as explosion			

Combustion products include: carbon monoxide (CO), carbon dioxide (CO2), sulfur oxides (SOx), other pyrolysis products typical of burning organic material.

#### May emit poisonous fumes. FIRE INCOMPATIBILITY

Avoid contamination with oxidizing agents i.e. nitrates, oxidizing acids, chlorine bleaches, pool chlorine etc. as ignition may result.

### PERSONAL PROTECTION

Glasses: Chemical goggles. Gloves: Respirator: Particulate

# Section 6 - ACCIDENTAL RELEASE MEASURES

#### MINOR SPILLS

- Clean up all spills immediately.
- Avoid breathing dust and contact with skin and eyes.
- Wear protective clothing, gloves, safety glasses and dust respirator.
- Use dry clean up procedures and avoid generating dust.
- Sweep up, shovel up or vacuum up (consider explosion-proof machines designed to be grounded during storage and use).
- Place spilled material in clean, dry, sealable, labeled container.

MAJOR SPILLS

Moderate hazard.

- CAUTION: Advise personnel in area.
- Alert Emergency Responders and tell them location and nature of hazard.
- Control personal contact by wearing protective clothing.
- Prevent, by any means available, spillage from entering drains or water courses.
- Recover product wherever possible.
- IF DRY: Use dry clean up procedures and avoid generating dust. Collect residues and place in sealed plastic bags or other containers for disposal. IF WET: Vacuum/shovel up and place in labelled containers for disposal.
- ALWAYS: Wash area down with large amounts of water and prevent runoff into drains.
- If contamination of drains or waterways occurs, advise emergency services.

### ACUTE EXPOSURE GUIDELINE LEVELS (AEGL) (in ppm)

AEGL 1: The airborne concentration of a substance above which it is predicted that the general population, including susceptible individuals, could experience notable discomfort, irritation, or certain asymptomatic nonsensory effects. However, the effects are not disabling and are transient and reversible upon cessation of exposure. AEGL 2: The airborne concentration of a substance above which it is predicted that the general population, including susceptible individuals, could experience irreversible or other serious, long-lasting adverse health effects or an impaired ability to escape. AEGL 3: The airborne concentration of a substance above which it is predicted that the formation of the serious of the serious and the series of the

that the general population, including susceptible individuals, could

experience life-threatening health effects or death.

## Section 7 - HANDLING AND STORAGE

## PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.

# sc-215946



#### Material Safety Data Sheet

LOW Hazard Alert Code Key: EXTREME HIGH MODERATE · Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. • DO NOT enter confined spaces until atmosphere has been checked. • DO NOT allow material to contact humans, exposed food or food utensils. Avoid contact with incompatible materials. • When handling, DO NOT eat, drink or smoke. • Keep containers securely sealed when not in use. • Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Launder contaminated clothing before re-use. Use good occupational work practice. Observe manufacturer's storing and handling recommendations. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained. Empty containers may contain residual dust which has the potential to accumulate following settling. Such dusts may explode in the presence of an appropriate ignition source. Do NOT cut, drill, grind or weld such containers. • In addition ensure such activity is not performed near full, partially empty or empty containers without appropriate workplace safety authorisation or permit. **RECOMMENDED STORAGE METHODS** • Polyethylene or polypropylene container. Check all containers are clearly labelled and free from leaks. ۰

### STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



X: Must not be stored together

O: May be stored together with specific preventions

+: May be stored together

# Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

#### **EXPOSURE CONTROLS**

Source	Material	TWA ppm		STEL ppm	STEL mg/m³	Peak mg/m³	TWA F/CC	Notes
US - Oregon Permissible Exposure Limits (Z3)	tetrabromophenol blue, sodium salt (Inert or Nuisance Dust: (d) Total dust)		10					*

# sc-215946





Hazard Alert Code Key:	EXTREME	HIGH	MODERA	TE	LOW
US OSHA Permissible Exposure Levels (PELs) - Table Z3	tetrabromophenol blue, sodiu (Inert or Nuisance Dust: (d) R fraction)		i		
US OSHA Permissible Exposure Levels (PELs) - Table Z3	tetrabromophenol blue, sodiu (Inert or Nuisance Dust: (d) Te	1	5		
US - Hawaii Air Contaminant Limits	tetrabromophenol blue, sodiu (Particulates not other wise re Total dust)		0		
US - Hawaii Air Contaminant Limits	tetrabromophenol blue, sodiu (Particulates not other wise re Respirable fraction)		i		
US - Oregon Permissible Exposure Limits (Z3)	tetrabromophenol blue, sodiu (Inert or Nuisance Dust: (d) R fraction)		i		*
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	tetrabromophenol blue, sodiu (Particulates not otherwise re Respirable fraction)		i		
US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants	tetrabromophenol blue, sodiu (Particulates not otherwise re (PNOR)(f)- Respirable fractio	gulated 5	i		
US - Michigan Exposure Limits for Air Contaminants	tetrabromophenol blue, sodiu (Particulates not otherwise re Respirable dust)		i		

### MATERIAL DATA

TETRABROMOPHENOL BLUE, SODIUM SALT:

It is the goal of the ACGIH (and other Agencies) to recommend TLVs (or their equivalent) for all substances for which there is evidence of health effects at airborne concentrations encountered in the workplace.

At this time no TLV has been established, even though this material may produce adverse health effects (as evidenced in animal experiments or clinical experience). Airborne concentrations must be maintained as low as is practically possible and occupational exposure must be kept to a minimum.

NOTE: The ACGIH occupational exposure standard for Particles Not Otherwise Specified (P.N.O.S) does NOT apply.

### PERSONAL PROTECTION



Consult your EHS staff for recommendations

## EYE

- Safety glasses with side shields •
- Chemical goggles.

Contact lenses pose a special hazard; soft lenses may absorb irritants and all lenses concentrate them. •

#### HANDS/FEET

- Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: such as:
- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and
- dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739).

# sc-215946



Material Safety Data Sheet

Hazard Alert Code Key:	EXTREME	HIGH	MODERATE	LOW
<ul> <li>When prolonged or frequen 240 minutes according to El</li> </ul>		occur, a glove with a protect	tion class of 5 or higher (bro	eakthrough time greater than
<ul> <li>When only brief contact is e to EN 374) is recommended</li> </ul>		protection class of 3 or highe	r (breakthrough time greate	er than 60 minutes according
<ul> <li>Contaminated gloves should</li> </ul>				
Gloves must only be worn on c	lean hands. After using g	loves, hands should be wash	hed and dried thoroughly. A	pplication of a non-perfume
moisturiser is recommended. Experience indicates that the fo	llowing polymore are quit	able as alove meterials for p	rataction against undiscolur	d drugolida whore chreaiv
particles are not present.	mowing polymers are suite	able as glove materials for pr	Intection against unuissoive	a, ary solius, where abrasiv
<ul> <li>polychloroprene</li> </ul>				
<ul> <li>nitrile rubber</li> </ul>				
butyl rubber				
• fluorocaoutchouc				
<ul> <li>polyvinyl chloride</li> </ul>				
Gloves should be examined for	wear and/ or degradation	i constantly.		
OTHER	-			
-				
• Overalls.				
<ul> <li>P.V.C. apron.</li> </ul>				
<ul> <li>Barrier cream.</li> </ul>				
<ul> <li>Skin cleansing cream.</li> </ul>				
<ul> <li>Eye wash unit.</li> </ul>				
•				
	, , ,	l administrative controls do n		
		be based on professional		
		lihood of the worker's expos		, ,
2	ress or distress due to pe	ersonal protective equipment	(powered, positive now, it	ili face apparatus may be a
<ul><li>option).</li><li>Published occupational exp</li></ul>	ocura limita whore they a	vist will assist in determinin	a the adequacy of the colo	atad respiratory These ma
be government mandated o			g the adequacy of the sele	cieu respiratory . These ma
<ul> <li>Certified respirators will be</li> </ul>		ers from inhalation of partic	lates when properly select	ed and fit tested as part of
complete respiratory protect			alates when property select	ed and in tested as part of
• Use approved positive flow		ies of dust becomes airborne	<b>)</b> .	
<ul> <li>Try to avoid creating dust co</li> </ul>	<b>v</b> .			
RESPIRATOR				
Protection Factor	Half-Face Respirator	Full-Face Res	pirator Powe	red Air Respirator
10 x PEL	P1	-	PAPR	•
	Air-line*	-	-	
50 x PEL	Air-line**	P2	PAPR	-P2
100 x PEL	-	P3	-	

100+ x PEL

\* - Negative pressure demand \*\* - Continuous flow

Explanation of Respirator Codes:

Class 1 low to medium absorption capacity filters.

Class 2 medium absorption capacity filters.

Class 3 high absorption capacity filters.

PAPR Powered Air Purifying Respirator (positive pressure) cartridge.

Type A for use against certain organic gases and vapors.

Type AX for use against low boiling point organic compounds (less than 65°C).

Type B for use against certain inorganic gases and other acid gases and vapors.

Type E for use against sulfur dioxide and other acid gases and vapors.

Type K for use against ammonia and organic ammonia derivatives

Class P1 intended for use against mechanically generated particulates of sizes most commonly encountered in industry, e.g. asbestos, silica. Class P2 intended for use against both mechanically and thermally generated particulates, e.g. metal fume.

Air-line\*

Air-line\*\*

PAPR-P3

Class P3 intended for use against all particulates containing highly toxic materials, e.g. beryllium.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

Use appropriate NIOSH-certified respirator based on informed professional judgement. In conditions where no reasonable estimate of

# sc-215946



SANTA CRUZ	
The Power to Questio	a

Hazard Alert Code Key:	EXTREME	HIGH	MODERATE	LOW

exposure can be made, assume the exposure is in a concentration IDLH and use NIOSH-certified full face pressure demand SCBA with a minimum service life of 30 minutes, or a combination full facepiece pressure demand SAR with auxiliary self-contained air supply. Respirators provided only for escape from IDLH atmospheres shall be NIOSH-certified for escape from the atmosphere in which they will be used.

### ENGINEERING CONTROLS

- •
- Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction.
- Exhaust ventilation should be designed to prevent accumulation and recirculation of particulates in the workplace.
- If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered. Such protection might consist of:
- (a): particle dust respirators, if necessary, combined with an absorption cartridge;
- (b): filter respirators with absorption cartridge or canister of the right type;
- (c): fresh-air hoods or masks
- Build-up of electrostatic charge on the dust particle, may be prevented by bonding and grounding.
- Powder handling equipment such as dust collectors, dryers and mills may require additional protection measures such as explosion venting.

Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to efficiently remove the contaminant.

Type of Contaminant:	Air Speed:
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)
Within each range the appropriate value depends on:	
Lower end of the range	Upper end of the range
1: Room air currents minimal or favorable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 4-10 m/s (800-2000 f/min) for extraction of crusher dusts generated 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

# Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

### PHYSICAL PROPERTIES

Solid. Mixes with water.			
State	Divided solid	Molecular Weight	1007.58
Melting Range (°F)	Not available	Viscosity	Not Applicable
Boiling Range (°F)	Not applicable	Solubility in water (g/L)	Miscible
Flash Point (°F)	Not available	pH (1% solution)	Not available
Decomposition Temp (°F)	Not available	pH (as supplied)	Not applicable
Autoignition Temp (°F)	Not available	Vapour Pressure (mmHG)	Negligible
Upper Explosive Limit (%)	Not available.	Specific Gravity (water=1)	Not available
Lower Explosive Limit (%)	Not available	Relative Vapor Density (air=1)	>1

# sc-215946



Hazard Alert Code Key:	EXTREME	HIGH	MODERATE	LOW
Volatile Component (%vol)	Negligible	Evaporation Rate		Not applicable

APPEARANCE

Material Safety Data Sheet

Dark-brown metallic crystalline powder; mixes with water.

# Section 10 - CHEMICAL STABILITY

#### CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerization will not occur.

#### STORAGE INCOMPATIBILITY

Avoid reaction with oxidizing agents.

For incompatible materials - refer to Section 7 - Handling and Storage.

### Section 11 - TOXICOLOGICAL INFORMATION

tetrabromophenol blue, sodium salt

#### TOXICITY AND IRRITATION

No significant acute toxicological data identified in literature search.

#### CARCINOGEN

BROMINE COMPOUNDS (ORGANIC OR INORGANIC)

US Environmental Defense Scorecard Suspected Carcinogens

Reference(s) P65-MC

## Section 12 - ECOLOGICAL INFORMATION

Refer to data for ingredients, which follows:

TETRABROMOPHENOL BLUE, SODIUM SALT:

Bromide ion may be introduced to the environment after the dissociation of various salts and complexes or the degradation of organobromide compounds.

Although not a significant toxin in mammalian or avian systems it is highly toxic to rainbow trout and Daphnia magna. Bromides may also affect the growth of micro-organisms and have been used for this purpose in industry.

Bromides in drinking water are occasionally subject to disinfection processes involving ozone of chlorine. Bromide may be oxidised to produce hypobromous acid which in turn may react with natural organic matter to form brominated compounds. The formation of bromoform has been well documented, as has the formation of bromoacetic acids, bromopicrin, cyanogen bromide, and bromoacetone. Bromates may also be formed following ozonation or chlorination if pH is relatively high. Bromates may be animal carcinogens.

DO NOT discharge into sewer or waterways.

# Section 13 - DISPOSAL CONSIDERATIONS

#### **Disposal Instructions**

All waste must be handled in accordance with local, state and federal regulations.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- Reuse
- Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or

# sc-215946



Material Safety Data Sheet

Hazard Alert Code Key: EXTREME HIGH MODERATE LOW

reuse may not always be appropriate.

DO NOT allow wash water from cleaning equipment to enter drains. Collect all wash water for treatment before disposal.

- Recycle wherever possible.
- Consult manufacturer for recycling options or consult Waste Management Authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: Burial in a licensed land-fill or Incineration in a licensed apparatus (after admixture with suitable combustible material)
- Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

## **Section 14 - TRANSPORTATION INFORMATION**

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: DOT, IATA, IMDG

## Section 15 - REGULATORY INFORMATION

#### tetrabromophenol blue, sodium salt (CAS: 108321-10-4) is found on the following regulatory lists;

"US - Hawaii Air Contaminant Limits", "US - Oregon Permissible Exposure Limits (Z3)", "US OSHA Permissible Exposure Levels (PELs) - Table Z3"

# Section 16 - OTHER INFORMATION

#### LIMITED EVIDENCE

Cumulative effects may result following exposure\*.

May be harmful to the fetus/ embryo\*.

\* (limited evidence).

Reasonable care has been taken in the preparation of this information, but the author makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The author makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. For additional technical information please call our toxicology department on +800 CHEMCALL.

Classification of the mixture and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references. A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references.

• The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: Apr-4-2009 Print Date:May-11-2010