

Strontium titanate

sc-251072



The Power is Question

Material Safety Data Sheet

Hazard Alert Code
Key:

EXTREME

HIGH

MODERATE

LOW

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION


PRODUCT NAME

Strontium titanate

STATEMENT OF HAZARDOUS NATURE

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

NFPA



SUPPLIER

Company: Santa Cruz Biotechnology, Inc.

Address:

2145 Delaware Ave

Santa Cruz, CA 95060

Telephone: 800.457.3801 or 831.457.3800

Emergency Tel: CHEMWATCH: From within the US and
Canada: 877-715-9305

Emergency Tel: From outside the US and Canada: +800 2436
2255 (1-800-CHEMCALL) or call +613 9573 3112

PRODUCT USE

Flux.

SYNONYMS

SrO.TiO₃, Sr-Ti-O₃

Section 2 - HAZARDS IDENTIFICATION

CANADIAN WHMIS SYMBOLS



EMERGENCY OVERVIEW

RISK

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

- Accidental ingestion of the material may be damaging to the health of the individual.
- Strontium salts induce vomiting and diarrhea when swallowed in large quantity. Absorbed strontium may produce painful contractions of the limbs and may be involved in abnormalities of the heart.
- Dusts of titanium and titanium compounds are thought to exhibit little or no toxic effects.

EYE

- Although the material is not thought to be an irritant, direct contact with the eye may cause transient discomfort

characterized by tearing or conjunctival redness (as with windburn). Slight abrasive damage may also result. The material may produce foreign body irritation in certain individuals.

SKIN

- The material is not thought to produce adverse health effects or skin irritation following contact (as classified using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.
- Open cuts, abraded or irritated skin should not be exposed to this material.
- Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

INHALED

- The material is not thought to produce respiratory irritation (as classified using animal models). Nevertheless inhalation of dusts, or fume, especially for prolonged periods, may produce respiratory discomfort and occasionally, distress.
- Inhalation of dusts, generated by the material during the course of normal handling, may be damaging to the health of the individual.
- Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.
- Effects on lungs are significantly enhanced in the presence of respirable particles.

CHRONIC HEALTH EFFECTS

- Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.

Overexposure to respirable dust may cause coughing, wheezing, difficulty in breathing and impaired lung function. Chronic symptoms may include decreased vital lung capacity, chest infections. Repeated exposures, in an occupational setting, to high levels of fine- divided dusts may produce a condition known as pneumoconiosis which is the lodgement of any inhaled dusts in the lung irrespective of the effect. This is particularly true when a significant number of particles less than 0.5 microns (1/50,000 inch), are present. Lung shadows are seen in the X-ray. Symptoms of pneumoconiosis may include a progressive dry cough, shortness of breath on exertion (exertional dyspnea), increased chest expansion, weakness and weight loss. As the disease progresses the cough produces a stringy mucous, vital capacity decreases further and shortness of breath becomes more severe. Other signs or symptoms include altered breath sounds, diminished lung capacity, diminished oxygen uptake during exercise, emphysema and pneumothorax (air in lung cavity) as a rare complication.






Removing workers from possibility of further exposure to dust generally leads to halting the progress of the lung abnormalities. Where worker-exposure potential is high, periodic examinations with emphasis on lung dysfunctions should be undertaken. Dust inhalation over an extended number of years may produce pneumoconiosis.. Pneumoconiosis is the accumulation of dusts in the lungs and the tissue reaction in its presence. It is further classified as being of noncollagenous or collagenous types. Noncollagenous pneumoconiosis, the benign form, is identified by minimal stromal reaction, consists mainly of reticulin fibres, an intact alveolar architecture and is potentially reversible.

Strontium accumulates in teeth and bone, especially in the growth plates of rapidly growing bone. A chronic diet high in strontium and low in calcium produces severe bone deformities, inco-ordination, weakness and paralysis. Most health concerns related to strontium arise from radioisotopes of strontium which occur in "fall-out" following testing of nuclear weapons.

Long term exposure to titanium and several of its compounds produces lung scarring and chronic bronchitis. Breathing is impaired and cardiac changes with right heart enlargements occur. There is an increased chance of developing cancers of the respiratory tract.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

HAZARD RATINGS

	Min	Max	
Flammability:	0		
Toxicity:	2		
Body Contact:	0		
Reactivity:	0		Min/Nil=0 Low=1 Moderate=2 High=3 Extreme=4
Chronic:	2		

NAME	CAS RN	%
strontium titanate	12060-59-2	>98

Section 4 - FIRST AID MEASURES

SWALLOWED

-
- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Seek medical advice.

EYE

- If this product comes in contact with the eyes:
 - Wash out immediately with fresh running water.
 - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
 - If pain persists or recurs seek medical attention.

- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin or hair contact occurs:
 - Flush skin and hair with running water (and soap if available).
 - Seek medical attention in event of irritation.

INHALED

- - If fumes or combustion products are inhaled remove from contaminated area.
 - Lay patient down. Keep warm and rested.
 - Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
 - Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
 - Transport to hospital, or doctor.

NOTES TO PHYSICIAN

- Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES

Vapour Pressure (mmHG):	Not applicable.
Upper Explosive Limit (%):	Not applicable
Specific Gravity (water=1):	4.810
Lower Explosive Limit (%):	Not applicable

EXTINGUISHING MEDIA

- - There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

FIRE FIGHTING

- - Alert Emergency Responders and tell them location and nature of hazard.
 - Wear breathing apparatus plus protective gloves for fire only.
 - Prevent, by any means available, spillage from entering drains or water course.
 - Use fire fighting procedures suitable for surrounding area.
 - Do not approach containers suspected to be hot.
 - Cool fire exposed containers with water spray from a protected location.
 - If safe to do so, remove containers from path of fire.
 - Equipment should be thoroughly decontaminated after use.

GENERAL FIRE HAZARDS/HAZARDOUS COMBUSTIBLE PRODUCTS

- - Non combustible.
 - Not considered to be a significant fire risk, however containers may burn.

May emit poisonous fumes.

FIRE INCOMPATIBILITY

- None known.

PERSONAL PROTECTION

Glasses:

Chemical goggles.

Gloves:

Respirator:

Particulate

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- - Remove all ignition sources.
 - Clean up all spills immediately.
 - Avoid contact with skin and eyes.
 - Control personal contact by using protective equipment.
 - Use dry clean up procedures and avoid generating dust.
 - Place in a suitable, labelled container for waste disposal.

MAJOR SPILLS

- Moderate hazard.
 - CAUTION: Advise personnel in area.
 - Alert Emergency Responders and tell them location and nature of hazard.
 - Control personal contact by wearing protective clothing.
 - Prevent, by any means available, spillage from entering drains or water courses.
 - Recover product wherever possible.
 - IF DRY: Use dry clean up procedures and avoid generating dust. Collect residues and place in sealed plastic bags or other containers for disposal. IF WET: Vacuum/shovel up and place in labelled containers for disposal.
 - ALWAYS: Wash area down with large amounts of water and prevent runoff into drains.
 - If contamination of drains or waterways occurs, advise emergency services.

ACUTE EXPOSURE GUIDELINE LEVELS (AEGL) (in ppm)

AEGL 1: The airborne concentration of a substance above which it is predicted that the general population, including susceptible individuals, could experience notable discomfort, irritation, or certain asymptomatic nonsensory effects. However, the effects are not disabling and are transient and reversible upon cessation of exposure.

AEGL 2: The airborne concentration of a substance above which it is predicted that the general population, including susceptible individuals, could experience irreversible or other serious, long-lasting adverse health effects or an impaired ability to escape.

AEGL 3: The airborne concentration of a substance above which it is predicted that the general population, including susceptible individuals, could experience life-threatening health effects or death.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

-
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- DO NOT allow material to contact humans, exposed food or food utensils.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Launder contaminated clothing before re-use.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

RECOMMENDED STORAGE METHODS

-
- Polyethylene or polypropylene container.
- Check all containers are clearly labelled and free from leaks.

STORAGE REQUIREMENTS

-
- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



X: Must not be stored together

O: May be stored together with specific preventions

+: May be stored together

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	TWA F/CC	Notes
US - Oregon Permissible Exposure Limits (Z3)	strontium titanate (Inert or Nuisance Dust: (d) Total dust)		10						*
US - Oregon Permissible Exposure Limits (Z3)	strontium titanate (Inert or Nuisance Dust: (d) Respirable fraction)		5						*
US OSHA Permissible Exposure	strontium titanate (Inert or		15						

Levels (PELs) - Table Z3	Nuisance Dust: (d) Total dust	15	
US OSHA Permissible Exposure Levels (PELs) - Table Z3	strontium titanate (Inert or Nuisance Dust: (d) Respirable fraction)	5	
US - Hawaii Air Contaminant Limits	strontium titanate (Particulates not otherwise regulated - Total dust)	10	
US - Hawaii Air Contaminant Limits	strontium titanate (Particulates not otherwise regulated - Respirable fraction)	5	
US - Michigan Exposure Limits for Air Contaminants	strontium titanate (Particulates not otherwise regulated, Respirable dust)	5	
US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants	strontium titanate (Particulates not otherwise regulated (PNOR)(f)- Respirable fraction)	5	
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	strontium titanate (Particulates not otherwise regulated Respirable fraction)	5	
Canada - Alberta Occupational Exposure Limits	strontium titanate (Particulate Not Otherwise Regulated - Respirable)	3	
US - Oregon Permissible Exposure Limits (Z1)	strontium titanate (Particulates not otherwise regulated (PNOR) (f) Respirable Fraction)	5	*

MATERIAL DATA

STRONTIUM TITANATE:

■ It is the goal of the ACGIH (and other Agencies) to recommend TLVs (or their equivalent) for all substances for which there is evidence of health effects at airborne concentrations encountered in the workplace.

At this time no TLV has been established, even though this material may produce adverse health effects (as evidenced in animal experiments or clinical experience). Airborne concentrations must be maintained as low as is practically possible and occupational exposure must be kept to a minimum.

NOTE: The ACGIH occupational exposure standard for Particles Not Otherwise Specified (P.N.O.S) does NOT apply.

The concentration of respirable dust for application of this limit is to be determined from the fraction that penetrates a separator whose size collection efficiency is described by a cumulative lognormal function with a median aerodynamic diameter of 4.0 µm (+-) 0.3 µm and with a geometric standard deviation of 1.5 µm (+-) 0.1 µm, i.e. less than 5 µm.

PERSONAL PROTECTION



Consult your EHS staff for recommendations

EYE

-
- Safety glasses with side shields
- Chemical goggles.
- Contact lenses pose a special hazard; soft lenses may absorb irritants and all lenses concentrate them.

HANDS/FEET

- Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: such as:
 - frequency and duration of contact,
 - chemical resistance of glove material,
 - glove thickness and
 - dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739).

- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended.
- When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended.
- Contaminated gloves should be replaced.

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Experience indicates that the following polymers are suitable as glove materials for protection against undissolved, dry solids, where abrasive particles are not present.

- polychloroprene
- nitrile rubber
- butyl rubber
- fluorocautchouc
- polyvinyl chloride

Gloves should be examined for wear and/ or degradation constantly.

OTHER

■

- Overalls.
- P.V.C. apron.
- Barrier cream.
- Skin cleansing cream.
- Eye wash unit.
-
- Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.
- The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).
- Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory . These may be government mandated or vendor recommended.
- Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.
- Use approved positive flow mask if significant quantities of dust becomes airborne.
- Try to avoid creating dust conditions.

RESPIRATOR

Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
10 x PEL	P1	-	PAPR-P1
	Air-line*	-	-
50 x PEL	Air-line**	P2	PAPR-P2
100 x PEL	-	P3	-
	-	Air-line*	-
100+ x PEL	-	Air-line**	PAPR-P3

* - Negative pressure demand ** - Continuous flow

Explanation of Respirator Codes:

Class 1 low to medium absorption capacity filters.

Class 2 medium absorption capacity filters.

Class 3 high absorption capacity filters.

PAPR Powered Air Purifying Respirator (positive pressure) cartridge.

Type A for use against certain organic gases and vapors.

Type AX for use against low boiling point organic compounds (less than 65°C).

Type B for use against certain inorganic gases and other acid gases and vapors.

Type E for use against sulfur dioxide and other acid gases and vapors.

Type K for use against ammonia and organic ammonia derivatives

Class P1 intended for use against mechanically generated particulates of sizes most commonly encountered in industry, e.g. asbestos, silica.

Class P2 intended for use against both mechanically and thermally generated particulates, e.g. metal fume.

Class P3 intended for use against all particulates containing highly toxic materials, e.g. beryllium.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

Use appropriate NIOSH-certified respirator based on informed professional judgement. In conditions where no reasonable estimate of exposure can be made, assume the exposure is in a concentration IDLH and use NIOSH-certified full face pressure demand SCBA with a minimum service life of 30 minutes, or a combination full facepiece pressure demand SAR with auxiliary self-contained air supply. Respirators provided only for escape from IDLH atmospheres shall be NIOSH-certified for escape from the atmosphere in which they will be used.

ENGINEERING CONTROLS

■ Local exhaust ventilation usually required. If risk of overexposure exists, wear an approved respirator. Correct fit is essential to obtain adequate protection an approved self contained breathing apparatus (SCBA) may be required in some situations. Provide adequate ventilation in warehouse or closed storage area.

Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapors, degreasing etc., evaporating from tank (in still air).	0.25-0.5 m/s (50-100 f/min.)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favorable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank

2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL PROPERTIES

Solid.
Does not mix with water.
Sinks in water.

State	Divided solid	Molecular Weight	183.52
Melting Range (°F)	Not available	Viscosity	Not available
Boiling Range (°F)	Not available	Solubility in water (g/L)	Immiscible
Flash Point (°F)	Not applicable	pH (1% solution)	Not applicable
Decomposition Temp (°F)	Not available	pH (as supplied)	Not applicable
Autoignition Temp (°F)	Not available	Vapour Pressure (mmHG)	Not applicable.
Upper Explosive Limit (%)	Not applicable	Specific Gravity (water=1)	4.810
Lower Explosive Limit (%)	Not applicable	Relative Vapor Density (air=1)	Not applicable
Volatile Component (%vol)	Not applicable	Evaporation Rate	Not applicable

APPEARANCE

Off-white powder; does not mix with water.

Section 10 - CHEMICAL STABILITY

CONDITIONS CONTRIBUTING TO INSTABILITY

-
- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerization will not occur.

STORAGE INCOMPATIBILITY

-
- WARNING: Avoid or control reaction with peroxides. All transition metal peroxides should be considered as potentially explosive. For example transition metal complexes of alkyl hydroperoxides may decompose explosively.
- The pi-complexes formed between chromium(0), vanadium(0) and other transition metals (haloarene-metal complexes) and mono-or poly-fluorobenzene show extreme sensitivity to heat and are explosive.
- Avoid reaction with borohydrides or cyanoborohydrides

None known.

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

strontium titanate

TOXICITY AND IRRITATION

- No significant acute toxicological data identified in literature search.

Section 12 - ECOLOGICAL INFORMATION

Refer to data for ingredients, which follows:

STRONTIUM TITANATE:

- For strontium:

Environmental fate:

Strontium present in the atmosphere is in the form of wet or dry aerosols. The principal chemical species in the air is strontium oxide (SrO). Strontium oxide will react rapidly in the presence of moisture to form Sr²⁺ and SrOH⁺ ions. Strontium is dispersed by atmospheric cycling and is subsequently deposited by wet deposition on the earth's surface. In surface water and groundwater, strontium exists primarily as a hydrated ion. Strontium can form ionic complexes with other inorganic or organic substances. Strontium is relatively mobile in water. However, the formation of insoluble complexes or sorption of strontium to soils can reduce its mobility in water. Strontium sorbs to soils by ion exchange, and tends to be more mobile in soils with a high concentration of exchangeable ions or in soils with low cation exchange capacities. Strontium is taken up and retained by aquatic and terrestrial plants and is concentrated in the bony tissues of animals that eat contaminated vegetation. The concentration of radioactive ⁹⁰Sr in the atmosphere has steadily decreased since its maximum concentration in 1963, probably as a result of reduced numbers of tests involving nuclear explosives. However radioactive strontium occurs naturally in the earth's crust and partitions between various environmental compartments.

Strontium exists almost exclusively in the environment as a +2 cation, and will form different species, some of which are more soluble than others. Because the different species have different solubilities, they will have different mobilities in the environment and different exposure potentials. Strontium exists as a hydrated cation, an ionic solution complex, or an ionic salt. In the environment, typical solution species for strontium are Sr²⁺ and SrOH⁺, and some strontium compounds (SrCO₃ and SrSO₄) are practically insoluble in neutral water.

The principal abiotic processes that transform strontium in soils and sediments are mediated by sorption and desorption

reactions between the soil solution and matrix (precipitation, complexation, and ion exchange), and controlled by pH, ionic strength, solution speciation, mineral composition, organic matter, biological organisms, and temperature. For many soil systems, in the short term, strontium sorption is dominated by simple ion exchange, and strontium ions are readily exchangeable. At longer time scales, however, strontium ions may be relocated into sterically hindered sites that are not readily exchangeable.

Because strontium is an element, its atoms do not degrade by environmental processes such as hydrolysis or biodegradation. However, radioactive strontium will be subject to radioactive decay and transformation to other elements. Eventually, all of the radioactive strontium will be transformed into stable zirconium by the process of radioactive decay

^{90}Sr ($t_{1/2} = 29$ years) \rightarrow ^{90}Y ($t_{1/2} = 64$ hours) \rightarrow ^{90}Zr (stable) \rightarrow β^-

Both radioactive and nonradioactive strontium compounds are subject to both biotic and abiotic transformation mechanisms.

Like calcium, strontium has moderate mobility in soils and sediments, and sorbs moderately to metal oxides and clays. The Sr^{2+} ion is strongly hydrated and is firmly coordinated with six or more water molecules in aqueous solution. When Sr^{2+} ions sorb on negatively charged mineral surface sites, the hydration sphere is retained. Strontium sorbs as hydrated ions on the surface of clay minerals (kaolinite), weathered minerals (amorphous silica), and iron oxides. Sorbed carbonate on iron oxides enhances the sorption of Sr^{2+} and permits the nucleation of Sr^{2+} as strontium carbonate. On calcite (calcium carbonate), Sr^{2+} sorption occurs by electrostatic attraction as hydrated ions. However, at higher concentrations, precipitation of strontianite (strontium carbonate) occurs, and strontium is likely to be less mobile.

Strontium is not necessary for growth or reproduction for most plants, but is typically absorbed to satisfy the plant's metabolic requirements for calcium. Soil to plant concentration ratios for strontium (the ratio of the concentration of strontium in wet vegetation to the concentration of strontium in dry soil) are, and indicate that strontium can be easily absorbed into plants from soil. The uptake of strontium by plants is greatest in sandy soils having low clay and organic matter content. The concentration of nutritive mineral elements in soil such as calcium lower the intake of strontium to the aboveground phytomass. The average reduction of the soil-to-plant concentration ratios for ^{90}Sr caused by amendment with Ca or K is around 50-60% .

Strontium may be deposited on plant surfaces from the atmosphere, remain on the plant, be washed off, or be absorbed directly into the plant through leaves. Contamination by direct deposition on foliage surfaces is predominantly a short-term mechanism with a weathering half-life of approximately 14 days. Once absorbed in the plant, strontium translocates to other parts of the plant, such as the leaves or fruit. Translocation of strontium in plants is affected by the particular species and stage of organism growth, and the most metabolically active parts (growing) will accumulate higher concentrations of strontium.

The primary routes of human exposure to strontium are from inhalation of aerosols and ingestion of food and drinking water containing strontium. The intake of strontium, therefore, depends upon the concentration of strontium in air, drinking water, and in the food items that comprise a person's diet, which may be highly variable.

External exposure to ^{90}Sr is not a concern because of minor emission of penetrating radiation from ^{90}Sr .

No estimate of the concentration of ^{90}Sr in air is available. However, it is assumed that ambient concentrations of ^{90}Sr in the atmosphere are small relative to exposures from water and diet. If the concentration of ^{90}Sr in average U.S. drinking water is estimated as 0.1 pCi/L (4 mBq/L) or one radiochemical event per 5-10 minutes, and the consumption rate of drinking water by a normal adult is assumed to be 2 L/day, then the exposure from drinking water would be 0.2 pCi (7 mBq) per day.

The distributions of ^{90}Sr in the body are significantly different for males and females. As expected, the highest concentrations of ^{90}Sr are measured in the bony tissue. Males and females averaged 10.4 and 65 pCi/kg (0.38 and 2.4 Bq/kg) wet weight, respectively. Males had a much higher concentration of ^{90}Sr in the muscular tissue compared to females. The heart and psoas muscles had respective concentrations of ^{90}Sr for men averaging 13.9 and 18.7 pCi/kg (0.51 and 0.69 Bq) wet weight versus respective concentrations of 7.4 and 1.9 pCi/kg (0.27 Bq/kg and 70 mBq/kg) wet weight for females.

Occupational exposure to strontium compounds affords the opportunity to accumulate higher levels of all forms of strontium.

Children drink more fluids, eat more food, breathe more air per kilogram of body weight, and have a larger skin surface in proportion to their body volume. A child's diet often differs from that of adults. The developing human's source of nutrition changes with age: from placental nourishment to breast milk or formula to the diet of older children who eat more of certain types of foods than adults. A child's behavior and lifestyle also influence exposure. Compared to adults, the potential for radiostrontium exposure is greater for children who consume foods (e.g., milk, grains) produced in areas with elevated concentrations of radiostrontium in the soil and for children with elevated concentrations of radiostrontium in their drinking water. Children are more likely to be exposed to ^{90}Sr in cow's milk produced in contaminated areas..

Agency for Toxic Substances and Disease Registry (ATSDR); Toxicological Profile for Strontium.

■ DO NOT discharge into sewer or waterways.

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Instructions

All waste must be handled in accordance with local, state and federal regulations.

! Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- Reuse
- Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

DO NOT allow wash water from cleaning equipment to enter drains. Collect all wash water for treatment before disposal.

- Recycle wherever possible or consult manufacturer for recycling options.
- Consult Waste Management Authority for disposal.
- Bury residue in an authorized landfill.
- Recycle containers where possible, or dispose of in an authorized landfill.

Section 14 - TRANSPORTATION INFORMATION

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: DOT, IATA, IMDG

Section 15 - REGULATORY INFORMATION

strontium titanate (CAS: 12060-59-2) is found on the following regulatory lists;

Section 16 - OTHER INFORMATION

LIMITED EVIDENCE

- Inhalation and/or ingestion may produce health damage*.
- Cumulative effects may result following exposure*.

* (limited evidence).

Reasonable care has been taken in the preparation of this information, but the author makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The author makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. For additional technical information please call our toxicology department on +800 CHEMCALL.

- Classification of the mixture and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:
www.chemwatch.net/references.

- The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: Aug-7-2009

Print Date: Apr-22-2010