Magnesium methoxide solution: sc-257683



MATERIAL SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Product Number:	Magnesium methoxide solution sc-257683
Supplier:	Santa Cruz Biotechnology, Inc. 2145 Delaware Avenue Santa Cruz, CA 95060 800.457.3801 or 831.457.3800
Emergency:	ChemWatch Within the US & Canada: 877–715–9305 Outside the US & Canada: +800 2436 2255 (1–800-CHEMCALL) or call +613 9573 3112

2. COMPOSITION/INFORMATION ON INGREDIENTS

Formula : C2H6MgO2

CAS-No.	EC-No.	Index-No.	Concentration
Methanol			
67–56–1 Magnesium methanolate	200–659–6	603–001–00-X	>= 90.01 - <= 96 %
109–88–6	203–715–8	-	>= 4 - <= 9.99 %

3. HAZARDS IDENTIFICATION

Emergency Overview OSHA Hazards Flammable liquid, Target Organ Effect, Toxic by inhalation., Toxic by ingestion, Toxic by skin absorption, Irritant **Target Organs** Eyes, Kidney, Liver, Heart, Central nervous system **HMIS Classification** Health hazard: 3 Chronic Health Hazard: * Flammability: Physical hazards: 0 3 NFPA Rating Health hazard: Fire: 3 Reactivity Hazard: 0 4 **Potential Health Effects** Inhalation Toxic if inhaled. Causes respiratory tract irritation. Toxic if absorbed through skin. Causes skin irritation. Skin Eyes Causes eye irritation. Toxic if swallowed. Ingestion

4. FIRST AID MEASURES

General advice Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled If breathed in, move person into fresh air. If not breathing give artificial respiration Consult a physician.

In case of skin contact Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

In case of eye contact Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. **If swallowed** Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

5. FIRE-FIGHTING MEASURES

Flammable properties

Flash point7.77 °C (45.99 °F) – closed cupIgnition temperatureno data available

Suitable extinguishing media

For small (incipient) fires, use media such as "alcohol" foam, dry chemical, or carbon dioxide. For large fires, apply water from as far as possible. Use very large quantities (flooding) of water applied as a mist or spray; solid streams of water may be ineffective. Cool all affected containers with flooding quantities of water.

Special protective equipment for fire-fighters

Wear self contained breathing apparatus for fire fighting if necessary.

Further information

Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

Wear respiratory protection. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Methods for cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

7. HANDLING AND STORAGE

Handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Keep away from sources of ignition – No smoking. Take measures to prevent the build up of electrostatic charge. **Storage**

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in cool place.

Store under inert gas. Moisture sensitive.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value	Control parameters	Update	Basis		
Methanol	67-56-1	TWA	200 ppm	2007-01-01	USA. ACGIH Threshold Limit Values (TLV)		
Remarks		Headache Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption					
		STEL	250 ppm	2007-01-01	USA. ACGIH Threshold Limit Values (TLV)		
		Headache Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption					
		TWA	200 ppm 260 mg/m3	1989-01-19	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000		
	Skin notation						
		STEL	250 ppm 325 mg/m3	1989-01-19	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000		
	Skin notation						
		TWA	200 ppm 260 mg/m3	1997-08-04	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants		
	The value in	The value in mg/m3 is approximate.					

Personal protective equipment

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). Hand protection

Handle with gloves.

Eye protection

Face shield and safety glasses

Skin and body protection

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	
Form	liquid
Safety data	
pН	no data available
Melting point	no data available
Boiling point	no data available
Flash point	7.77 °C (45.99 °F) – closed cup
Ignition temperature	no data available
Lower explosion limit	no data available
Upper explosion limit	no data available
Density	0.816 g/cm3
Water solubility	no data available

10. STABILITY AND REACTIVITY

Storage stability
Stable under recommended storage conditions.
Conditions to avoid
Heat, flames and sparks.
Materials to avoid
Acids, Oxidizing agents, Alkali metals, Strong oxidizing agents, Acid chlorides, Acid anhydrides, Reducing agents
Hazardous decomposition products
Hazardous decomposition products formed under fire conditions. – Carbon oxides, Magnesium oxide
Hazardous reactions
Vapours may form explosive mixture with air.

11. TOXICOLOGICAL INFORMATION

Acute toxicity no data available Irritation and corrosion no data available Sensitisation no data available Chronic exposure IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC. No component of this product present at levels greater than or equal to 0.1% is identified as a ACGIH: carcinogen or potential carcinogen by ACGIH. NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a

Signs and Symptoms of Exposure

Warning: contains methanol. May be fatal or cause blindness if swallowed. Cannot be made nonpoisonous., burning sensation, Cough, wheezing, laryngitis, Shortness of breath, Headache, spasm, inflammation and edema of the larynx, spasm, inflammation and edema of the bronchi, pneumonitis **Potential Health Effects**

Inhalation	Toxic if inhaled. Causes respiratory tract irritation.
Skin	Toxic if absorbed through skin. Causes skin irritation.
Eyes	Causes eye irritation.
Ingestion	Toxic if swallowed.
Target Organs	Eyes, Kidney, Liver, Heart, Central nervous system,

carcinogen or potential carcinogen by OSHA.

12. ECOLOGICAL INFORMATION

Elimination information (persistence and degradability) no data available Ecotoxicity effects no data available Further information on ecology no data available

13. DISPOSAL CONSIDERATIONS

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Observe all federal, state, and local environmental regulations. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

UN-Number: 3274 Class: 3 (8) Packing group: II Proper shipping name: Alcoholates solution, n.o.s. (Methanol, Magnesium methanolate) Reportable Quantity (RQ): 5208 lbs Marine pollutant: No Poison Inhalation Hazard: No IMDG UN-Number: 3274 Class: 3 (8) Packing group: II EMS-No: F-E. S-C Proper shipping name: ALCOHOLATES SOLUTION, N.O.S. (Methanol, Magnesium methanolate) Marine pollutant: No ΙΑΤΑ UN-Number: 3274 Class: 3 (8) Packing group: II Proper shipping name: Alcoholates solution n.o.s. (Methanol, Magnesium methanolate)

15. REGULATORY INFORMATION

OSHA Hazards

Flammable liquid, Target Organ Effect, Toxic by inhalation., Toxic by ingestion, Toxic by skin absorption, Irritant **DSL Status**

This product contains the following components listed on the Canadian NDSL list. All other components are on the Canadian DSL list.

Magnesium methanolate	CAS-No.
	109–88–6

SARA 302 Components

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302. SARA 313 Components

Methanol	CAS-No.
	67–56–1
SARA 311/312 Hazards	

Fire Hazard, Acute Health Hazard, Chronic Health Hazard Massachusetts Right To Know Components

Magnesium methanolate

CAS-No. 109–88–6

Pennsylvania Right To Know Components

Methanol	CAS-No. 67–56–1
Magnesium methanolate	CAS-No. 109–88–6
New Jersey Right To Know Components	
Methanol	CAS-No. 67–56–1
Magnesium methanolate	CAS-No. 109–88–6

California Prop. 65 Components

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

16. OTHER INFORMATION

The above information is believed to be correct but does not purport to be complete and should be used only as a guide. The burden of safe use of this material rests entirely with the user.

01/12/2011